
**CONDITIONAL LETTER OF MAP REVISION
FOR
LONGFORD GROUP/DUCK CREEK CHANNEL**

758.002

June 2004

**04-09-817R
05-09-0913P**

**Prepared for:
Longford Group
3127 E. Warm Springs Road, Ste. 100
Las Vegas, NV 89120
(702) 454-5300
(702) 454-1376**



G. C. WALLACE, INC.
Engineers/Planners/Surveyors

**CONDITIONAL LETTER OF MAP REVISION
FOR
LONGFORD GROUP/DUCK CREEK CHANNEL**

2004 JUN 19 AM 8:58
RFCD

758.002

June 2004

**Prepared for:
Longford Group
3127 E. Warm Springs Road, Ste. 100
Las Vegas, NV 89120
(702) 454-5300
(702) 454-1376**



G. C. WALLACE, INC.
Engineers • Planners • Surveyors

G. C. WALLACE, PE/SE, PLS
JAMES A. DUDDLESTEN, PE
MICHAEL D. ROSS, PE
CHRISTOPHER W. ANDERSON, PE
CALVIN L. BLACK, PE, PLS
E. ROBERT PETERSON
SCOTT R. PLUMMER, PE
BENJAMIN C. SMITH, PE
EUGENE W. WRIGHT, PE

THOMAS P. DYSON, PE
DOUGLAS M. HANKEL
BERT A. HUGHES, PE
RICKEY D. HUNSAKER, PE, LC
NOEL C. LAUGHLIN, PE
MARVIN W. MAIZE
DANNY S. McFADDEN, PE
S. WILLIAM NEIGHBORS, PE
THOMAS R. NICHOLS, PE
FREDERICK W. ORBAN, PLS
JERRY E. PRUITT, PE
BRIAN L. SCHNIDT, PE
JEFF W. STAYTON, PE
JOHN R. TOBIN, PE, PTOE
HOWARD K. VANDER MEER, PE, WRS
G. IRA WALLACE, PE

JIM B. BAKKEDAH, PE
JOSEPH A. BODROG, PLS
ROY D. CLARK, PE
HEIDI A. DEXHEIMER, PE
ERIC J. GALVAN
RANDALL K. GREMLICH, PE
PASCAL HAYES, PE/SE
J. P. HIGGINS, PLS, WRS
DANNY E. HILL, PLS
DAPHNE L. HOFFMAN
DONALD L. HOTCHKISS JR., PE
BILL HUNTER, PE
RANDY W. MROWICKI, PLS
JOHNIE R. PATE JR., PE, PTOE
FRED A. SELLE
SAUNDRA L. VANCE, CCS, CCCA

FAYSAL ARIDI, PE
RYAN R. BELSICK, PE
JOHN T. BROWN, PE
PATRICK S. BYRD, PE
MARY A. CARR, PE
RICHARD G. CLARKE
GLENN R. CURTIS, III, CMI
IAIN DOLEMAN
MARK A. FERDA, PE
JOHN FITCH, PE
ERIC G. GILES, PE/SE
NICHOLAS G. GOLZ, PE
BRIJ M. GULATI, PE, PTOE
KEITH HATTON, PE
TODD C. HAYNE, PE
GERALD L. HOLTON, PLS, WRS
RUSSELL D. JAMISON, PLS
JOSH JOHNSON, PE
KAYANN JONGSMA, PE
TODD N. KELLEY, PE
DENNIS R. KETTERMAN
FRED KHANBOLOUKI, PE
SCOTT R. LANDERMAN, PLS
PAUL R. LOHMAN, PE
MICHAEL J. LUDWIG, PE
CHRISTOPHER M. LUQUETTE, PE, CFM
JEFFERY J. MCBRIDE, PE
WILLIAM METCALF
MATTHEW D. MEYER, PE
WILLIAM J. MEYER, PE
RIMAH I. NAZZAL, PE/SE
GIA D. NGUYEN, PE
JERRY E. PASCOE, PLS
WESLEY T. PETTY, PE
CHRISTOPHER W. PLUTTE, PE
GEOFFREY G. PURSE, PE
RICK J. READ, PE
BRADFORD G. ROCKWELL, PE
CHRISTOPHER B. SMITH, PE
DONNA J. STRALOW, PLS
S. TRACY STRATTON
CHURAIRAT (ANN) TANAKUL, PE
GRANT Y. TOKUMI, PE
KEVIN L. TOMLINSON, PE
JERRY TSUNETA
F. EDUARDO VILLALOBOS, PE/SE
PAUL J. VILLALUZ, PE
KEVIN W. WALLACE, PLS
GLENN B. WATANABE, PE
STEPHEN L. WEATHERMAN, PE
MANSON W. WONG, PE, PTOE
DEBRA M. YAMACHIKA, PE
DERICK D.J. YORO, PE

AFFILIATE OFFICE IN
SACRAMENTO, CA

758.002

June 22, 2004

Ms. Pernille Buch-Pedersen
Michael Baker Jr., Inc.
FEMA Map Coordination Contractor
3601 Eisenhower Avenue, Suite 600
Alexandria, Virginia 22304

Subject: CLOMR for Longford Group/Duck Creek Channel

Dear Ms. Buch-Pedersen:

G. C. Wallace, Inc. (GCW) has been contracted by Longford Group to submit a Conditional Letter of Map Revision (CLOMR) for a portion of the Duck Creek Channel located immediately downstream of Eastern Avenue within the unincorporated area of Clark County, Nevada. This CLOMR is based on the improvements designed for the Duck Creek Channel between Eastern Avenue and Warm Springs Road. The affected community panel is Number 32003C 2590E, revised August 13, 2003. See Figures 1 and 2 for the project vicinity and location.

The Duck Creek Channel hydrology and hydraulic characteristics were recently analyzed as part of the Duck Creek FIS Restudy, LOMR 03-09-0980X, incorporated August 13, 2003. As established in the Duck Creek FIS Restudy, the 100-year peak flow conveyed by this section of the Duck Creek Channel is 8,562 cfs. As currently constructed, a breakout of storm flows from the Duck Creek Channel occurs just upstream of Warm Springs Road during major storm events. According to the Duck Creek FIS Restudy, approximately 3,000 cfs during a 100-year storm event overtops the right overbank of the channel at this location. The flow from this breakout re-enters the channel via Pine Street, Pecos Road, and Quail Run Road, between downstream HEC-2 Cross Sections 12000 and 11100. This portion of the channel was modeled with HEC-2 files DCL1SUBC.dat (Subcritical Conditions) and DCL1SPRC.dat (Supercritical Conditions) in the Duck Creek FIS Restudy. Electronic copies of these calculations are included for reference.

The proposed improvements include the construction of concrete-lined rectangular and trapezoidal channel the length of the unimproved channel between Eastern Avenue and Warm Springs Road. In addition, a bridge will be added at Topaz Street. With the proposed improvements to the Duck Creek Channel, the 8,562 cfs peak flow will be confined to the channel in this area, eliminating the breakout upstream of Warm Springs Road. The HEC-2 models generated for this section of Duck Creek Channel were taken and updated to reflect the proposed conditions within the channel. The proposed HEC-2



G. C. WALLACE, INC.

Engineers • Planners • Surveyors

Michael Baker Jr., Inc.

June 22, 2004

Page 2

758.002

models use the established water surface elevations at Cross Section 15500 and Cross Section 10600, the upstream and downstream limits of the new model. The peak flow, 8,562 cfs, was used for the entire length of the channel between these two cross sections. According to the proposed models, the peak storm flow is contained along the entire length of the channel between Cross Sections 15500 and 10600, the limits of the new model. The Water Surface Elevations at the downstream end of the project are unchanged from the Duck Creek FIS Restudy calculations. The calculated Water Surface Elevation at the upstream end of the study limits is slightly lower than the Water Surface Elevation calculated by the Duck Creek FIS Restudy as shown in the HEC-2 Model Summary Table included in Section 3.

The proposed changes to the F.I.R.M. Panel 32003C 2590E are included on Figure 4. These changes eliminate the Flood Zone A created by the breakout in the channel between Eastern Avenue and Warm Springs Road.

FEMA Forms MT2-1, MT2-2, and MT2-3 are included in Section 1, as well as a copy of the payment for \$4,000 made payable to the National Flood Insurance Program. The original check has been forwarded to the FEMA Fee-Charge System Administrator, as instructed.

If you have any questions or require additional information, please contact us at 804-2000.

Very truly yours,

G. C. WALLACE, INC.

Calvin L. Black, P.E.
Executive Vice President
Flood Control Division

CLB:KJ:jj

Enc.

cc: Joe P. Gwerder, P.E., Longford Group
Dave Betley, P.E., Clark County Department of Public Works
Kevin Eubanks, P.E., Clark County Regional Flood Control District

Supporting Documentation for CLOMR

Section 1 – FEMA Forms

- MT-2 Form 1: Overview & Concurrence Form
- MT-2 Form 2: Riverine Hydrology & Hydraulics Form
- MT-2 Form 3: Riverine Structures Form
- Copy of Payment Information Form sent directly to FEMA

Section 2 – Maps

- Figure 1: Vicinity Map
- Figure 2: Location Map
- Figure 3: Effective FIRM
- Figure 4: Proposed FIRM Revisions
- Figure 5: HEC-2 Cross Section Map

Section 3 – Hydraulic Analyses

- Summary of HEC-2 Results
- HEC-2 Model for Subcritical Conditions
- HEC-2 Model for Supercritical Conditions

Section 4 – Reference Material

- Duck Creek FIS Restudy

Section 5 – Electronic Files

- Figure 3: Effective FIRM
- Figure 4: Proposed FIRM Revisions
- Figure 5: HEC-2 Cross Section Map
- Summary of HEC-2 Results (HEC2Summ.xls)
- HEC-2 Model for Subcritical Conditions (DCL1SUBX.dat)
- HEC-2 Model for Supercritical Conditions (DCL1SPRX.dat)
- HEC-2 Model for Subcritical Conditions from FIS Restudy (DCL1SUBC.out)
- HEC-2 Model for Supercritical Conditions from FIS Restudy (DCL1SPRC.out)

Section 6 – Drawings for Proposed Facilities

- Duck Creek Channel Improvements
- Pictures of Existing Facilities

SECTION 1

FEMA Forms

MT-2 Form 1: Overview & Concurrence Form
MT-2 Form 2: Riverine Hydrology & Hydraulics Form
MT-2 Form 3: Riverine Structures Form
Copy of Payment Information Form sent directly to FEMA

FEDERAL EMERGENCY MANAGEMENT AGENCY
OVERVIEW & CONCURRENCE FORM

O.M.B No. 3067-0148
Expires September 30, 2005

PAPERWORK BURDEN DISCLOSURE NOTICE

Public reporting burden for this form is estimated to average 1 hour per response. The burden estimate includes the time for reviewing instructions, searching existing data sources, gathering and maintaining the needed data, and completing, reviewing, and submitting the form. You are not required to respond to this collection of information unless a valid OMB control number appears in the upper right corner of this form. Send comments regarding the accuracy of the burden estimate and any suggestions for reducing this burden to: Information Collections Management, Federal Emergency Management Agency, 500 C Street, SW, Washington DC 20472, Paperwork Reduction Project (3067-0148). Submission of the form is required to obtain or retain benefits under the National Flood Insurance Program. **Please do not send your completed survey to the above address.**

A. REQUESTED RESPONSE FROM FEMA

This request is for a (check one):

- ☒ **CLOMR:** A letter from FEMA commenting on whether a proposed project, if built as proposed, would justify a map revision, or proposed hydrology changes (See 44 CFR Ch. 1, Parts 60, 65 & 72).
- ☐ **LOMR:** A letter from FEMA officially revising the current NFIP map to show the changes to floodplains, regulatory floodway or flood elevations. (See Parts 60 & 65 of the NFIP Regulations.)

B. OVERVIEW

1. The NFIP map panel(s) affected for all impacted communities is (are):

Community No.	Community Name	State	Map No.	Panel No.	Effective Date
Ex: 480301	City of Katy	TX	480301	0005D	02/08/83
480287	Harris County	TX	48201C	0220G	09/28/90
320003	Clark County, Unincorporated Areas	NV	32003C	2590E	08/13/03

2. Flooding Source: Duck Creek Channel

3. Project Name/Identifier: Longford Group/Duck Creek Channel Improvements

4. FEMA zone designations affected: A, AE (choices: A, AH, AO, A1-A30, A99, AE, AR, V, V1-V30, VE, B, C, D, X)

5. Basis for Request and Type of Revision:

a. The basis for this revision request is (check all that apply)

- ☒ Physical Change ☐ Improved Methodology/Data
- ☐ Regulatory Floodway Revision ☐ Other (Attach Description)

Note: A photograph and narrative description of the area of concern is not required, but is very helpful during review.

b. The area of revision encompasses the following types of flooding and structures (check all that apply)

- Types of Flooding: ☒ Riverine ☐ Coastal ☐ Shallow Flooding (e.g., Zones AO and AH)
- ☐ Alluvial fan ☐ Lakes ☐ Other (Attach Description)
- Structures: ☒ Channelization ☐ Levee/Floodwall ☒ Bridge/Culvert
- ☐ Dam ☐ Fill ☐ Other, Attach Description

C. REVIEW FEE

Has the review fee for the appropriate request category been included?

☒ Yes

Fee amount: \$4,000

☐ No, Attach Explanation

Please see the FEMA Web site at http://www.fema.gov/fhm/fm_fees.shtm for Fee Amounts and Exemptions.

D. SIGNATURE

All documents submitted in support of this request are correct to the best of my knowledge. I understand that any false statement may be punishable by fine or imprisonment under Title 18 of the United States Code, Section 1001.

Name: Joe P. Gwerder, P.E.

Company: Longford Group

Mailing Address:
3127 E. Warm Springs Road
Suite 100
Las Vegas, Nevada 89120

Daytime Telephone No.:
(702) 454-5300

Fax No.:
(702) 454-1376

E-Mail Address:

Signature of Requester (required):

Joe P. Gwerder

Date:

7-2-04

As the community official responsible for floodplain management, I hereby acknowledge that we have received and reviewed this Letter of Map Revision (LOMR) or conditional LOMR request. Based upon the community's review, we find the completed or proposed project meets or is designed to meet all of the community floodplain management requirements, including the requirement that no fill be placed in the regulatory floodway, and that all necessary Federal, State, and local permits have been, or in the case of a conditional LOMR, will be obtained. In addition, we have determined that the land and any existing or proposed structures to be removed from the SFHA are or will be reasonably safe from flooding as defined in 44CFR 65.2(c), and that we have available upon request by FEMA, all analyses and documentation used to make this determination.

Community Official's Name and Title: Denis Cederburg, P.E. -- Manager, Design Engineering, CC Development Services

Telephone No.:
(702) 455-6064

Community Name: Clark County

Community Official's Signature (required):

Denis Cederburg

Date:

7-1-04

CERTIFICATION BY REGISTERED PROFESSIONAL ENGINEER AND/OR LAND SURVEYOR

This certification is to be signed and sealed by a licensed land surveyor, registered professional engineer, or architect authorized by law to certify elevation information. All documents submitted in support of this request are correct to the best of my knowledge. I understand that any false statement may be punishable by fine or imprisonment under Title 18 of the United States Code, Section 1001.

Certifier's Name: Calvin Black

License No.: 4525

Expiration Date:
12/31/04

Company Name: G. C. Wallace, Inc.

Telephone No.: (702) 804-2000

Fax No.:
(702) 804-2298

Signature:

Calvin L. Black

Date:

7/1/04

Ensure the forms that are appropriate to your revision request are included in your submittal.

Form Name and (Number)

Required if ...

☒ Riverine Hydrology and Hydraulics Form (Form 2)

New or revised discharges or water-surface elevations

☒ Riverine Structures Form (Form 3)

Channel is modified, addition/revision of bridge/culverts, addition/revision of levee/floodwall, addition/revision of dikes

☐ Coastal Analysis Form (Form 4)


New or revised coastal elevations

☐ Coastal Structures Form (Form 5)

Addition/revision of coastal structure

☐ Alluvial Fan Flooding Form (Form 6)

Flood control measures on alluvial fans



FEDERAL EMERGENCY MANAGEMENT AGENCY
RIVERINE HYDROLOGY & HYDRAULICS FORM

*O.M.B No. 3067-0148
Expires September 30, 2005*

PAPERWORK REDUCTION ACT

Public reporting burden for this form is estimated to average 3 hours per response. The burden estimate includes the time for reviewing instructions, searching existing data sources, gathering and maintaining the needed data, and completing, reviewing, and submitting the form. You are not required to respond to this collection of information unless a valid OMB control number appears in the upper right corner of this form. Send comments regarding the accuracy of the burden estimate and any suggestions for reducing this burden to: Information Collections Management, Federal Emergency Management Agency, 500 C Street, SW, Washington DC 20472, Paperwork Reduction Project (3067-0148). Submission of the form is required to obtain or retain benefits under the National Flood Insurance Program. **Please do not send your completed survey to the above address.**

Flooding Source: Duck Creek Channel

Note: Fill out one form for each flooding source studied

A. HYDROLOGY

1. Reason for New Hydrologic Analysis (check all that apply)

- | | | |
|---|--|--|
| ☒ Not revised (skip to section 2) | ☐ No existing analysis | ☐ Improved data |
| ☐ Alternative methodology | ☐ Proposed Conditions (CLOMR) | ☐ Changed physical condition of watershed |

2. Comparison of Representative 1%-Annual-Chance Discharges

Location	Drainage Area (Sq. Mi.)	FIS (cfs)	Revised (cfs)
N/A			

3. Methodology for New Hydrologic Analysis (check all that apply)

- | | | |
|---|--|------------------------------|
| ☐ Statistical Analysis of Gage Records | ☐ Precipitation/Runoff Model | [TR-20, HEC-1, HEC-HMS etc.] |
| ☐ Regional Regression Equations | ☐ Other (please attach description) | |

Please enclose all relevant models in digital format, maps, computations (including computation of parameters) and documentation to support the new analysis. The document, "Numerical Models Accepted by FEMA for NFIP Usage" lists the models accepted by FEMA. This document can be found at: http://www.fema.gov/fhm/en_modl.shtml.

4. Review/Approval of Analysis

If your community requires a regional, state, or federal agency to review the hydrologic analysis, please attach evidence of approval/review.

5. Impacts of Sediment Transport on Hydrology

Was sediment transport considered? ☐ Yes ☐ No If yes, then fill out Section F (Sediment Transport) of Form 3. If No, then attach your explanation for why sediment transport was not considered.

B. HYDRAULICS

1. Reach to be Revised

	Description	Cross Section	Water-Surface Elevations (ft.)	
			Effective	Proposed/Revised
Downstream Limit	Duck Creek Channel	10600	1949.3	1949.3
Upstream Limit	Duck Creek Channel at Eastern Avenue	15500	2037.8	2037.1

2. Hydraulic Method Used

Hydraulic Analysis HEC-2 [HEC-2, HEC-RAS, Other (Attach description)]

B. HYDRAULICS (CONTINUED)

3. Pre-Submittal Review of Hydraulic Models

FEMA has developed two review programs, CHECK-2 and CHECK-RAS, to aid in the review of HEC-2 and HEC-RAS hydraulic models, respectively. These review programs verify that the hydraulic estimates and assumptions in the model data are in accordance with NFIP requirements, and that the data are comparable with the assumptions and limitations of HEC-2/HEC-RAS. CHECK-2 and CHECK-RAS identify areas of potential error or concern. These tools do not replace engineering judgment. CHECK-2 and CHECK-RAS can be downloaded from http://www.fema.gov/fhm/frm_soft.shtm. We recommend that you review your HEC-2 and HEC-RAS models with CHECK-2 and CHECK-RAS. If you disagree with a message, please attach an explanation of why the message is not valid in this case. Review of your submittal and resolution of valid modeling discrepancies will result in reduced review time.

HEC-2/HEC-RAS models reviewed with CHECK-2/CHECK-RAS? ☒ Yes ☐ No

4. Models Submitted

Duplicate Effective Model*	Natural File Name:	Floodway File Name:
Corrected Effective Model*	Natural File Name:	Floodway File Name:
Existing or Pre-Project Conditions Model	Natural File Name: DCL1SPRC.dat	Floodway File Name: N/A
Revised or Post-Project Conditions Model	Natural File Name: DCL1SPRX.dat	Floodway File Name: N/A
Other - (attach description)	Natural File Name:	Floodway File Name:

*Not required for revisions to approximate 1%-annual-chance floodplains (Zone A) – for details, refer to the corresponding section of the instructions.

The document "Numerical Models Accepted by FEMA for NFIP Usage" lists the models accepted by FEMA. This document can be found at: http://www.fema.gov/fhm/en_modl.shtm.

C. MAPPING REQUIREMENTS

A **certified topographic map** must be submitted showing the following information (where applicable): the boundaries of the effective, existing, and proposed conditions 1%-annual-chance floodplain (for approximate Zone A revisions) or the boundaries of the 1%- and 0.2%-annual-chance floodplains and regulatory floodway (for detailed Zone AE, AO, and AH revisions); location and alignment of all cross sections with stationing control indicated; stream, road, and other alignments (e.g., dams, levees, etc.); current community easements and boundaries; boundaries of the requester's property; certification of a registered professional engineer registered in the subject State; location and description of reference marks; and the referenced vertical datum (NGVD, NAVD, etc.).

Note that the boundaries of the existing or proposed conditions floodplains and regulatory floodway to be shown on the revised FIRM and/or FBFM must tie-in with the effective floodplain and regulatory floodway boundaries. Please attach a **copy of the effective FIRM and/or FBFM**, annotated to show the boundaries of the revised 1%- and 0.2%-annual-chance floodplains and regulatory floodway that tie-in with the boundaries of the effective 1%- and 0.2%-annual-chance floodplain and regulatory floodway at the upstream and downstream limits of the area of revision.

D. COMMON REGULATORY REQUIREMENTS

1. For CLOMR requests, do Base Flood Elevations (BFEs) increase? ☒ Yes ☐ No

For CLOMR requests, if either of the following is true, please submit evidence of compliance with Section 65.12 of the NFIP regulations:

- The proposed project encroaches upon a regulatory floodway and would result in increases above 0.00 foot.
- The proposed project encroaches upon a SFHA with BFEs established and would result in increases above 1.00 foot.

2. Does the request involve the placement or proposed placement of fill? ☐ Yes ☒ No

If Yes, the community must be able to certify that the area to be removed from the special flood hazard area, to include any structures or proposed structures, meets all of the standards of the local floodplain ordinances, and is reasonably safe from flooding in accordance with the NFIP regulations set forth at 44 CFR 60.3(a)(3), 65.5(a)(4), and 65.6(a)(14). Please see the MT-2 instructions for more information.

3. For LOMR requests, is the regulatory floodway being revised? ☐ Yes ☐ No

If Yes, attach evidence of regulatory floodway revision notification. As per Paragraph 65.7(b)(1) of the NFIP Regulations, notification is required for requests involving revisions to the regulatory floodway. (Not required for revisions to approximate 1%-annual-chance floodplains [studied Zone A designation] unless a regulatory floodway is being added. Elements and examples of regulatory floodway revision notification can be found in the MT-2 Form 2 Instructions.)

4. For LOMR requests, does this request require property owner notification and acceptance of BFE increases? ☐ Yes ☐ No

If Yes, please attach proof of property owner notification and acceptance (if available). Elements of and examples of property owner notification can be found in the MT-2 Form 2 Instructions.

FEDERAL EMERGENCY MANAGEMENT AGENCY
RIVERINE STRUCTURES FORM

O.M.B. No. 3067-0148
Expires September 30, 2005

PAPERWORK REDUCTION ACT

Public reporting burden for this form is estimated to average 7 hours per response. The burden estimate includes the time for reviewing instructions, searching existing data sources, gathering and maintaining the needed data, and completing, reviewing, and submitting the form. You are not required to respond to this collection of information unless a valid OMB control number appears in the upper right corner of this form. Send comments regarding the accuracy of the burden estimate and any suggestions for reducing this burden to: Information Collections Management, Federal Emergency Management Agency, 500 C Street, SW, Washington DC 20472, Paperwork Reduction Project (3067-0148). Submission of the form is required to obtain or retain benefits under the National Flood Insurance Program. **Please do not send your completed survey to the above address.**

Flooding Source: Duck Creek Channel

Note: Fill out one form for each flooding source studied

A. GENERAL

Complete the appropriate section(s) for each Structure listed below:

Channelization.....complete Section B
Bridge/Culvert.....complete Section C
Damcomplete Section D
Levee/Floodwallcomplete Section E
Sediment Transportcomplete Section F (if required)

Description Of Structure

1. Name of Structure: Duck Creek Channel

Type (check one): ☒ Channelization ☐ Bridge/Culvert ☐ Levee/Floodwall ☐ Dam

Location of Structure: Duck Creek Channel

Downstream Limit/Cross Section: Warm Springs Road Bridge / Cross Section 14700

Upstream Limit/Cross Section: Between Eastern Avenue and Topaz Street / Cross Section 15300

2. Name of Structure: Topaz Street Bridge

Type (check one): ☐ Channelization ☒ Bridge/Culvert ☐ Levee/Floodwall ☐ Dam

Location of Structure: Duck Creek Channel between Eastern Avenue and Warm Springs Road

Downstream Limit/Cross Section: 14850

Upstream Limit/Cross Section: 14950

3. Name of Structure:

Type (check one) ☐ Channelization ☐ Bridge/Culvert ☐ Levee/Floodwall ☐ Dam

Location of Structure:

Downstream Limit/Cross Section:

Upstream Limit/Cross Section:

NOTE: For more structures, attach additional pages as needed.

B. CHANNELIZATION

Flooding Source: Duck Creek Channel

Name of Structure: Duck Creek Channel

1. Accessory Structures

The channelization includes (check one):

- | | |
|---|--|
| ☐ Levees [Attach Section E (Levee/Floodwall)] | ☐ Drop structures |
| ☐ Superelevated sections | ☐ Transitions in cross sectional geometry |
| ☐ Debris basin/detention basin | ☐ Energy dissipator |
| ☒ Other (Describe): Duck Creek Channel Improvements | |

2. Drawing Checklist

Attach the plans of the channelization certified by a registered professional engineer, as described in the instructions.

3. Hydraulic Considerations

The channel was designed to carry 8562 (cfs) and/or the 100-year flood.

The design elevation in the channel is based on (check one):

- ☒ Subcritical flow ☐ Critical flow ☒ Supercritical flow ☐ Energy grade line

If there is the potential for a hydraulic jump at the following locations, check all that apply and attach an explanation of how the hydraulic jump is controlled without affecting the stability of the channel.

- ☐ Inlet to channel ☐ Outlet of channel ☐ At Drop Structures ☐ At Transitions
☐ Other locations (specify):

4. Sediment Transport Considerations

Was sediment transport considered? ☐ Yes ☒ No If Yes, then fill out Section F (Sediment Transport).
If No, then attach your explanation for why sediment transport was not considered.

C. BRIDGE/CULVERT

Flooding Source: Duck Creek Channel

Name of Structure: Topaz Street Bridge

1. This revision reflects (check one):

- ☒ New bridge/culvert not modeled in the FIS
☐ Modified bridge/culvert previously modeled in the FIS
☐ New analysis of bridge/culvert previously modeled in the FIS

2. Hydraulic model used to analyze the structure (e.g., HEC-2 with special bridge routine, WSPRO, HY8): HEC-2 w/special bridge routine If different than hydraulic analysis for the flooding source, justify why the hydraulic analysis used for the flooding source could not analyze the structures. Attach justification.

3. Attach plans of the structures certified by a registered professional engineer. The plan detail and information should include the following (check the information that has been provided):

- | | |
|--|--|
| ☒ Dimensions (height, width, span, radius, length) | ☐ Erosion Protection |
| ☐ Shape (culverts only) | ☒ Low Chord Elevations – Upstream and Downstream |
| ☒ Material | ☒ Top of Road Elevations – Upstream and Downstream |
| ☐ Beveling or Rounding | ☐ Structure Invert Elevations – Upstream and Downstream |
| ☐ Wing Wall Angle | ☒ Stream Invert Elevations – Upstream and Downstream |
| ☐ Skew Angle | ☒ Cross-Section Locations |
| ☒ Distances Between Cross Sections | |

4. Sediment Transport Considerations

Was sediment transport considered? ☐ Yes ☒ No If yes, then fill out Section F (Sediment Transport).
If No, then attach your explanation for why sediment transport was not considered.

D. DAM

Flooding Source:

Name of Structure: N/A

1. This request is for (check one): ☐ Existing dam ☐ New dam ☐ Modification of existing dam

2. The dam was designed by (check one): ☒ Federal agency ☐ State agency ☐ Local government agency

☐ Private organization Name of the agency or organization:

3. Does the project involve revised hydrology? ☐ Yes ☐ No

If Yes, complete the Riverine Hydrology & Hydraulics Form (Form 2).

4. Does the submittal include debris/sediment yield analysis? ☐ Yes ☐ No

If yes, then fill out Section F (Sediment Transport).

If No, then attach your explanation for why debris/sediment analysis was not considered.

5. Does the Base Flood Elevation behind the dam or downstream of the dam change?

☐ Yes ☐ No If Yes, complete the Riverine Hydrology & Hydraulics Form (Form 2) and complete the table below.

Stillwater Elevation Behind the Dam

FREQUENCY (% annual chance)

FIS

REVISED

10-year (10%)

50-year (2%)

100-year (1%)

500-year (0.2%)

Normal Pool Elevation

6. Please attach a copy of the formal Operation and Maintenance Plan

E. LEVEE/FLOODWALL

1 System Elements

a. This Levee/Floodwall analysis is based on (check one):

- ☐ upgrading of an existing levee/floodwall system
☐ a newly constructed levee/floodwall system
☐ reanalysis of an existing levee/floodwall system

b. Levee elements and locations are (check one):

- | | | |
|---|---------|----|
| ☐ earthen embankment, dike, berm, etc. | Station | to |
| ☐ structural floodwall | Station | to |
| ☐ Other (describe): | Station | to |

c. Structural Type (check one):

- ☐ monolithic cast-in place reinforced concrete
☐ reinforced concrete masonry block
☐ sheet piling
☐ Other (describe):

d. Has this levee/floodwall system been certified by a Federal agency to provide protection from the base flood?

☐ Yes ☐ No

If Yes, by which agency?

e. Attach certified drawings containing the following information (indicate drawing sheet numbers):

- | | |
|--|----------------|
| 1. Plan of the levee embankment and floodwall structures. | Sheet Numbers: |
| 2. A profile of the levee/floodwall system showing the Base Flood Elevation (BFE), levee and/or wall crest and foundation, and closure locations for the total levee system. | Sheet Numbers: |
| 3. A profile of the BFE, closure opening outlet and inlet invert elevations, type and size of opening, and kind of closure. | Sheet Numbers: |
| 4. A layout detail for the embankment protection measures. | Sheet Numbers: |
| 5. Location, layout, and size and shape of the levee embankment features, foundation treatment, floodwall structure, closure structures, and pump stations. | Sheet Numbers: |

2. Freeboard

a. The minimum freeboard provided above the BFE is:

Riverine

- 3.0 feet or more at the downstream end and throughout
 3.5 feet or more at the upstream end
 4.0 feet within 100 feet upstream of all structures and/or constrictions

☐ Yes	☐ No
☐ Yes	☐ No
☐ Yes	☐ No

Coastal

1.0 foot above the height of the one percent wave associated with the 1%-annual-chance stillwater surge elevation or maximum wave runup (whichever is greater).

☐ Yes ☐ No

2.0 feet above the 1%-annual-chance stillwater surge elevation

☐ Yes ☐ No

E. LEVEE/FLOODWALL (CONTINUED)

2. Freeboard (continued)

Please note, occasionally exceptions are made to the minimum freeboard requirement. If an exception is requested, attach documentation addressing Paragraph 65.10(b)(1)(ii) of the NFIP Regulations.

If No is answered to any of the above, please attach an explanation.

- b. Is there an indication from historical records that ice-jamming can affect the BFE? ☐ Yes ☐ No

If Yes, provide ice-jam analysis profile and evidence that the minimum freeboard discussed above still exists.

3. Closures

- a. Openings through the levee system (check one): ☐ exists ☐ does not exist

If opening exists, list all closures:

Channel Station	Left or Right Bank	Opening Type	Highest Elevation for Opening Invert	Type of Closure Device

(Extend table on an added sheet as needed and reference)

Note: Geotechnical and geologic data

In addition to the required detailed analysis reports, data obtained during field and laboratory investigations and used in the design analysis for the following system features should be submitted in a tabulated summary form. (Reference U.S. Army Corps of Engineers [USACE] EM-1110-2-1906 Form 2086.)

4. Embankment Protection

- a. The maximum levee slope landside is:
- b. The maximum levee slope floodside is:
- c. The range of velocities along the levee during the base flood is: (min.) to (max.)
- d. Embankment material is protected by (describe what kind):
- e. Riprap Design Parameters (check one): ☐ Velocity ☐ Tractive stress
Attach references

Reach	Sideslope	Flow Depth	Velocity	Curve or Straight	Stone Riprap			Depth of Toedown
					D ₁₀₀	D ₅₀	Thickness	
Sta to								
Sta to								
Sta to								
Sta to								
Sta to								
Sta to								

(Extend table on an added sheet as needed and reference each entry)

E. LEVEE/FLOODWALL (CONTINUED)

4. Embankment Protection (continued)

- f. Is a bedding/filter analysis and design attached? ☐ Yes ☐ No
- g. Describe the analysis used for other kinds of protection used (include copies of the design analysis):

Attach engineering analysis to support construction plans.

5. Embankment And Foundation Stability

- a. Identify locations and describe the basis for selection of critical location for analysis:

☐ Overall height: Sta. ; height ft.

☐ Limiting foundation soil strength:

Sta. , depth to

strength ϕ = degrees, c = psf

slope: SS = (h) to (v)

(Repeat as needed on an added sheet for additional locations)

- b. Specify the embankment stability analysis methodology used (e.g., circular arc, sliding block, infinite slope, etc.):

- c. Summary of stability analysis results:

Case	Loading Conditions	Critical Safety Factor	Criteria (Min.)
I	End of construction		1.3
II	Sudden drawdown		1.0
III	Critical flood stage		1.4
IV	Steady seepage at flood stage		1.4
VI	Earthquake (Case I)		1.0

(Reference: USACE EM-1110-2-1913 Table 6-1)

- d. Was a seepage analysis for the embankment performed? ☐ Yes ☐ No

If Yes, describe methodology used:

- e. Was a seepage analysis for the foundation performed? ☐ Yes ☐ No

- f. Were uplift pressures at the embankment landside toe checked? ☐ Yes ☐ No

- g. Were seepage exit gradients checked for piping potential? ☐ Yes ☐ No

- h. The duration of the base flood hydrograph against the embankment is hours.

Attach engineering analysis to support construction plans.

E. LEVEE/FLOODWALL (CONTINUED)

6. Floodwall And Foundation Stability

a. Describe analysis submittal based on Code (check one):

☐ UBC (1988) or ☐ Other (specify):

b. Stability analysis submitted provides for:

☐ Overturning ☐ Sliding If not, explain:

c. Loading included in the analyses were:

☐ Lateral earth @ $P_A =$ psf; $P_p =$ psf

☐ Surcharge-Slope @ , ☐ surface psf

☐ Wind @ $P_w =$ psf

☐ Seepage (Uplift); ☐ Earthquake @ $P_{eq} =$ %g

☐ 1%-annual-chance significant wave height: ft.

☐ 1%-annual-chance significant wave period: sec.

d. Summary of Stability Analysis Results: Factors of Safety.

Itemize for each range in site layout dimension and loading condition limitation for each respective reach.

Loading Condition	Criteria (Min)		Sta	To	Sta	To
	Overturn	Sliding	Overturn	Sliding	Overturn	Sliding
Dead & Wind	1.5	1.5				
Dead & Soil	1.5	1.5				
Dead, Soil, Flood, & Impact	1.5	1.5				
Dead, Soil, & Seismic	1.3	1.3				

(Ref: FEMA 114 Sept 1986; USACE EM 1110-2-2502)

(Note: Extend table on an added sheet as needed and reference)

e. Foundation bearing strength for each soil type:

Bearing Pressure	Sustained Load (psf)	Short Term Load (psf)
Computed design maximum		
Maximum allowable		

f. Foundation scour protection ☐ is, ☐ is not provided. If provided, attach explanation and supporting documentation:

Attach engineering analysis to support construction plans.

E. LEVEE/FLOODWALL (CONTINUED)

7. Settlement

- a. Has anticipated potential settlement been determined and incorporated into the specified construction elevations to maintain the established freeboard margin? ☐ Yes ☐ No
- b. The computed range of settlement is ft. to ft.
- c. Settlement of the levee crest is determined to be primarily from :
- ☐ Foundation consolidation
- ☐ Embankment compression
- ☐ Other (Describe):
- d. Differential settlement of floodwalls ☐ has ☐ has not been accommodated in the structural design and construction.
- Attach engineering analysis to support construction plans.

8. Interior Drainage

- a. Specify size of each interior watershed:
- Draining to pressure conduit: acres
- Draining to ponding area: acres
- b. Relationships Established
- | | | |
|------------------------------------|------------------------------|-----------------------------|
| Ponding elevation vs. storage | ☐ Yes | ☐ No |
| Ponding elevation vs. gravity flow | ☐ Yes | ☐ No |
| Differential head vs. gravity flow | ☐ Yes | ☐ No |
- c. The river flow duration curve is enclosed: ☐ Yes ☐ No
- d. Specify the discharge capacity of the head pressure conduit: cfs
- e. Which flooding conditions were analyzed?
- | | | |
|-------------------------------------|------------------------------|-----------------------------|
| • Gravity flow (Interior Watershed) | ☐ Yes | ☐ No |
| • Common storm (River Watershed) | ☐ Yes | ☐ No |
| • Historical ponding probability | ☐ Yes | ☐ No |
| • Coastal wave overtopping | ☐ Yes | ☐ No |
- If No for any of the above, attach explanation.
- f. Interior drainage has been analyzed based on joint probability of interior and exterior flooding and the capacities of pumping and outlet facilities to provide the established level of flood protection. ☐ Yes ☐ No
- If No, attach explanation.
- g. The rate of seepage through the levee system for the base flood is cfs
- h. The length of levee system used to drive this seepage rate in item g: ft.

E. LEVEE/FLOODWALL (CONTINUED)

8. Interior Drainage (continued)

- i. Will pumping plants be used for interior drainage?

☐ Yes ☐ No

If Yes, include the number of pumping plants:
For each pumping plant, list:

	Plant #1	Plant #2
The number of pumps		
The ponding storage capacity		
The maximum pumping rate		
The maximum pumping head		
The pumping starting elevation		
The pumping stopping elevation		
Is the discharge facility protected?		
Is there a flood warning plan?		
How much time is available between warning and flooding?		

Will the operation be automatic?

☐ Yes ☐ No

If the pumps are electric, are there backup power sources?

☐ Yes ☐ No

(Reference: USACE EM-1110-2-3101, 3102, 3103, 3104, and 3105)

Include a copy of supporting documentation of data and analysis. Provide a map showing the flooded area and maximum ponding elevations for all interior watersheds that result in flooding.

9. Other Design Criteria

- a. The following items have been addressed as stated:

Liquefaction ☐ is ☐ is not a problem

Hydrocompaction ☐ is ☐ is not a problem

Heave differential movement due to soils of high shrink/swell ☐ is ☐ is not a problem

- b. For each of these problems, state the basic facts and corrective action taken:

Attach supporting documentation

- c. If the levee/floodwall is new or enlarged, will the structure adversely impact flood levels and/or flow velocities floodside of the structure?

☐ Yes ☐ No

Attach supporting documentation

- d. Sediment Transport Considerations:

Was sediment transport considered? ☐ Yes ☐ No If Yes, then fill out Section F (Sediment Transport).

If No, then attach your explanation for why sediment transport was not considered.

E. LEVEE/FLOODWALL (CONTINUED)

10. Operational Plan And Criteria

- a. Are the planned/installed works in full compliance with Part 65.10 of the NFIP Regulations? ☐ Yes ☐ No
- b. Does the operation plan incorporate all the provisions for closure devices as required in Paragraph 65.10(c)(1) of the NFIP regulations?
☐ Yes ☐ No
- c. Does the operation plan incorporate all the provisions for interior drainage as required in Paragraph 65.10(c)(2) of the NFIP regulations?
☐ Yes ☐ No

If the answer is No to any of the above, please attach supporting documentation.

11. Maintenance Plan

- a. Are the planned/installed works in full compliance with Part 65.10 of the NFIP Regulations? ☐ Yes ☐ No
If No, please attach supporting documentation.

12. Operations and Maintenance Plan

Please attach a copy of the formal Operations and Maintenance Plan for the levee/floodwall.

F. SEDIMENT TRANSPORT

Flooding Source:

Name of Structure:

If there is any indication from historical records that sediment transport (including scour and deposition) can affect the Base Flood Elevation (BFE); and/or based on the stream morphology, vegetative cover, development of the watershed and bank conditions, there is a potential for debris and sediment transport (including scour and deposition) to affect the BFEs, then provide the following information along with the supporting documentation:

Sediment load associated with the base flood discharge: Volume acre-feet

Debris load associated with the base flood discharge: Volume acre-feet

Sediment transport rate (percent concentration by volume)

Method used to estimate sediment transport:

Most sediment transport formulas are intended for a range of hydraulic conditions and sediment sizes; attach a detailed explanation for using the selected method.

Method used to estimate scour and/or deposition:

Method used to revise hydraulic or hydrologic analysis (model) to account for sediment transport:

Please note that bulked flows are used to evaluate the performance of a structure during the base flood; however, FEMA does not map BFEs based on bulked flows.

If a sediment analysis has not been performed, an explanation as to why sediment transport (including scour and deposition) will not affect the BFEs or structures must be provided

**FEDERAL EMERGENCY MANAGEMENT AGENCY
PAYMENT INFORMATION FORM**

Community Name: Unincorporated Areas, Clark County, NV

Project Identifier: Longford Homes/Duck Creek Channel

THIS FORM MUST BE MAILED, ALONG WITH THE APPROPRIATE FEE, TO ONE OF TWO POST OFFICE BOXES (SEE BELOW) OR FAXED TO THE FAX NUMBER BELOW.

Type of Request:

MT-1 application fee }
MT-2 application fee } (Insert 3173 as the P.O. Box number in the address below)

External Data Requests (EDRs) (Insert 398 as the P.O. Box number in the address below)

Federal Emergency Management Agency
Revisions Fee-Collection System Administrator
P.O. Box 3173
Merrifield, Virginia 22116
Fax: (703) 849-0282

Request No.: (if known)

Amount: \$4,000

☐ INITIAL FEE* ☒ FINAL FEE ☐ FEE BALANCE** ☐ MASTER CARD ☐ VISA ☒ CHECK ☐ MONEY ORDER

*Note: Check only for EDR and/or Alluvial Fan requests (as appropriate).

**Note: Check only if submitting a corrected fee for an ongoing request.

COMPLETE THIS SECTION ONLY IF PAYING BY CREDIT CARD

EXP. DATE

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16
CARD NUMBER

Month Year

Date

Signature

NAME (AS IT APPEARS ON CARD):
(please print or type)

ADDRESS:
(for your
credit card
receipt-please
print or type)

DAYTIME PHONE:

National5 National Flood Insurance Program
Las Vegas, NV

Longford Plaza III, LLC
Check Number 531-00000043
Check Date Jun 25, 2004

Date	Invoice	Reference	Invoice Amt	Retention	Discount	Payment
0053	Longford Plaza III, LLC					
06/25/04	062504	LPIII fee for FEMA	4,000.00	0.00	0.00	4,000.00
Total Remittance			4,000.00	0.00	.00	4,000.00

FOR SECURITY PURPOSES, THE FACE OF THIS DOCUMENT CONTAINS A COLORED BACKGROUND AND MICROPRINTING IN THE BORDER

Longford Plaza III, LLC

3077 E. Warm Springs
Las Vegas, NV 89120

1st National Bank of Nevada
4950 W. Flamingo Road
Las Vegas, NV 89103

94-72
1224

Date
Jun 25, 2004

Check Number
531-00000043

Void After 90 Days

Pay *Four Thousand Dollars 00 Cents *

Amount
\$4,000.00

To
The
Order
Of
National Flood Insurance Program
Las Vegas, NV

Per Jennifer L. Dudek
PAYABLE IN US DOLLARS

⑈00000043⑈ ⑆122401723⑆ 031507006⑈

THE REVERSE SIDE OF THIS DOCUMENT INCLUDES AN ARTIFICIAL WATERMARK - HOLD AT ANGLE TO VIEW

SECTION 2

Maps

Figure 1: Vicinity Map

Figure 2: Location Map

Figure 3: Effective FIRM

Figure 4: Proposed FIRM Revisions



Figure 5: HEC-2 Cross Section Map

Figure 6: Annotated FIRM (Copies of Affected Effective FIRM Panels)

rhunter

06-21-04 15:55:48

G:\758-002\drainage\CLOMR\Fig1.dwg



GRAPHIC SCALE



(IN FEET)

1 inch = 12000 ft



LONGFORD HOMES CLOMR

FIGURE 1
VICINITY MAP




G.C. WALLACE, INC.
Engineers/Planners/Surveyors

1555 SOUTH RAINBOW BLVD. / LAS VEGAS, NEVADA 89146



GRAPHIC SCALE



(IN FEET)

1 inch = 2000 ft.


LONGFORD HOMES CLOMR

FIGURE 2
LOCATION MAP



G.C. WALLACE, INC.
Engineers/Planners/Surveyors

1555 SOUTH RAINBOW BLVD / LAS VEGAS, NEVADA 89146



1 inch = 2000 ft.





FIGURE 3
EFFECTIVE F.I.R.M. MAP

1535 SOUTH RAINBOW BLVD. / LAS VEGAS, NEVADA 89146



NOTES

FLOODING SOURCES: DUCK CREEK, NORTH AND MIDDLE BRANCHES OF THE BLUE DIAMOND WASH
CLARK COUNTY, NEVADA

MAP BASED ON 1-INCH = 400 FEET TOPOGRAPHIC MAPPING
CONTOUR INTERVAL = 4 FEET
FLIGHT DATE: JULY 18, 2000
BY KENNEY AERIAL MAPPING, INC.

FIRM PANEL(S) AFFECTED: 32003C2567 D, DATED AUGUST 16, 1995
32003C2590 D, DATED AUGUST 16, 1995

ELEVATION REFERENCE MARKERS (ERM)			
REFERENCE NUMBER	ELEVATION REFERENCE MARKER ID	ELEVATION (FT, NGVD 29)	LOCATION DESCRIPTION
204	CCBM 8C21 12NWS	2036.60	RIVET AND SQUARE ALUMINUM PLATE, IN TOP OF CURB, SOUTHEAST CORNER OF EASTERN AVENUE AND WARM SPRINGS ROAD NEAR P.C. OF EASTERN AVENUE.

NAVD 88 = NGVD 29 + 2.37 FT

- LEGEND
- 206 ELEVATION REFERENCE MARKER
 - EFFECTIVE 100-YR FLOODPLAIN AND FLOODWAY BOUNDARY
 - REVIS 100-YR FLOODPLAIN BOUNDARY
 - REVIS 100-YR FLOODWAY BOUNDARY
 - SHADED ZONE X
 - ZONE AE REVIS FLOOD ZONE DESIGNATION
 - HEC-2 CROSS SECTION
 - 2058 BASE FLOOD ELEVATION
 - 8562 100-YEAR FLOW (CFS, FLOODPLAIN ONLY)

LONGFORD HOMES CLOMR
DUCK CREEK FROM EASTERN TO 10600
CROSS SECTION EXHIBIT

SHEET
FIG 5
5 OF 5 SHTS

G.C. WALLACE, INC.
Engineers/Planners/Surveyors
8500 BLOOMINGDALE BLVD., SUITE 200, LAS VEGAS, NEVADA 89146
TELEPHONE: (702) 584-2255 FAX: (702) 584-2259
G:\758-002\drainage\CLOMR\vsnap5.dwg

DESIGN
DRAWN
CHECK
ISSUE DATE
PLOT DATE
PLOT TIME

DESCRIPTION

DATE
LOGN
APPD
DATE
COW
APPD
DATE

SECTION 3

Hydraulic Analyses

Summary of HEC-2 Results
HEC-2 Model for Subcritical Conditions
HEC-2 Model for Supercritical Conditions

HEC-2 SUMMARY TABLE

GENERAL				FLOODWAY		REVISED	
HEC-2 XS	STREAM NAME	HEC-2 MODEL	FLOW REGIME	OLD Q (CFS)	OLD WSE (FT)	Q (CFS)	WSE (FT)
10600	DUCK CREEK	DCL1SPRX	SUPER	8562	1949.3	8562	1949.3
10700	DUCK CREEK	DCL1SPRX	SUPER	8562	1954.7	8562	1954.7
10800	DUCK CREEK	DCL1SPRX	SUPER	8562	1958.6	8562	1958.6
10900	DUCK CREEK	DCL1SPRX	SUPER	8562	1963.2	8562	1963.2
11000	DUCK CREEK	DCL1SPRX	SUPER	8562	1968.2	8562	1967.9
11100	DUCK CREEK	DCL1SPRX	SUPER	8562	1971.3	8562	1969.5
11200	DUCK CREEK	DCL1SPRX	SUPER	7820	1970.9	8562	1970.7
11300	DUCK CREEK	DCL1SPRX	SUPER	7700	1972.1	8562	1971.6
11400	DUCK CREEK	DCL1SPRX	SUPER	7700	1971.4	8562	1970.8
11500	DUCK CREEK	DCL1SPRX	SUPER	7700	1971.6	8562	1971.0
11600	DUCK CREEK	DCL1SPRX	SUPER	6562	1976.0	8562	1976.1
11700	DUCK CREEK	DCL1SPRX	SUPER	6562	1975.6	8562	1976.5
11800	DUCK CREEK	DCL1SPRX	SUPER	6562	1977.3	8562	1978.0
11900	DUCK CREEK	DCL1SPRX	SUPER	6562	1979.3	8562	1979.5
12000	DUCK CREEK	DCL1SPRX	SUPER	6562	1979.4	8562	1979.6
12100	DUCK CREEK	DCL1SPRX	SUPER	5562	1980.2	8562	1981.9
12200	DUCK CREEK	DCL1SPRX	SUPER	5562	1984.7	8562	1985.8
12300	DUCK CREEK	DCL1SPRX	SUPER	5562	1987.9	8562	1988.0
12400	DUCK CREEK	DCL1SPRX	SUPER	5562	1987.1	8562	1988.2
12500	DUCK CREEK	DCL1SPRX	SUPER	5562	1987.5	8562	1988.6
12600	DUCK CREEK	DCL1SPRX	SUPER	5562	1990.5	8562	1992.0
12700	DUCK CREEK	DCL1SPRX	SUPER	5562	1993.0	8562	1994.4
12800	DUCK CREEK	DCL1SPRX	SUPER	5562	1995.8	8562	1997.2
12900	DUCK CREEK	DCL1SPRX	SUPER	5562	1997.4	8562	1998.9
13000	DUCK CREEK	DCL1SPRX	SUPER	5562	1997.8	8562	1999.4
13100	DUCK CREEK	DCL1SPRX	SUPER	5562	2003.8	8562	2005.6
13200	DUCK CREEK	DCL1SPRX	SUPER	5562	2006.5	8562	2008.4
13300	DUCK CREEK	DCL1SPRX	SUPER	5562	2006.5	8562	2007.6
13400	DUCK CREEK	DCL1SPRX	SUPER	5562	2006.7	8562	2007.9
13500	DUCK CREEK	DCL1SPRX	SUPER	5562	2006.9	8562	2008.1
13600	DUCK CREEK	DCL1SPRX	SUPER	5562	2010.5	8562	2011.6
13700	DUCK CREEK	DCL1SPRX	SUPER	5562	2011.9	8562	2013.6

GENERAL				FLOODWAY		REVISED	
HEC-2 XS	STREAM NAME	HEC-2 MODEL	FLOW REGIME	OLD Q (CFS)	OLD WSE (FT)	Q (CFS)	WSE (FT)
13800	DUCK CREEK	DCL1SPRX	SUPER	5562	2013.5	8562	2015.4
13900	DUCK CREEK	DCL1SPRX	SUPER	5562	2014.7	8562	2017.0
14000	DUCK CREEK	DCL1SPRX	SUPER	5562	2015.5	8562	2017.9
14100	DUCK CREEK	DCL1SPRX	SUPER	5562	2017.7	8562	2020.5
14200	DUCK CREEK	DCL1SPRX	SUPER	5562	2018.3	8562	2020.5
14220	DUCK CREEK	DCL1SPRX	SUPER	----	----	8562	2021.0
14240	DUCK CREEK	DCL1SPRX	SUPER	----	----	8562	2021.5
14300	DUCK CREEK	DCL1SPRX	SUPER	----	----	8562	2022.0
14400	DUCK CREEK	DCL1SPRX	SUPER	----	----	8562	2021.8
14450	DUCK CREEK	DCL1SPRX	SUPER	----	----	8562	2022.2
14500	DUCK CREEK	DCL1SPRX	SUPER	----	----	8562	2023.5
14550	DUCK CREEK	DCL1SPRX	SUPER	----	----	8562	2024.8
14600	DUCK CREEK	DCL1SPRX	SUPER	----	----	8562	2025.6
14700	DUCK CREEK	DCL1SPRX	SUPER	----	----	8562	2025.6
14750	DUCK CREEK	DCL1SPRX	SUPER	----	----	8562	2026.4
14800	DUCK CREEK	DCL1SPRX	SUPER	----	----	8562	2027.1
14850	DUCK CREEK	DCL1SPRX	SUPER	----	----	8562	2028.8
14900	DUCK CREEK	DCL1SPRX	SUPER	----	----	8562	2029.2
14950	DUCK CREEK	DCL1SPRX	SUPER	----	----	8562	2029.4
15000	DUCK CREEK	DCL1SPRX	SUPER	----	----	8562	2029.8
15050	DUCK CREEK	DCL1SPRX	SUPER	----	----	8562	2030.7
15100	DUCK CREEK	DCL1SPRX	SUPER	----	----	8562	2032.3
15110	DUCK CREEK	DCL1SUBX	SUB	----	----	8562	2032.4
15150	DUCK CREEK	DCL1SUBX	SUB	----	----	8562	2035.2
15200	DUCK CREEK	DCL1SUBX	SUB	----	----	8562	2035.0
15250	DUCK CREEK	DCL1SUBX	SUB	----	----	8562	2034.4
15300	DUCK CREEK	DCL1SUBX	SUB	----	----	8562	2034.8
15400	DUCK CREEK	DCL1SUBX	SUB	8562	2038.3	8562	2036.4
15500	DUCK CREEK	DCL1SUBX	SUB	8562	2037.8	8562	2037.1

HEC-2 Model for Subcritical Conditions

DCL1SUBX.dat

```

1*****
* HEC-2 WATER SURFACE PROFILES *
* *
* Version 4.6.2; May 1991 *
* *
* RUN DATE 16JUN04 TIME 14:17:54 *
*****

```

```

*****
* U.S. ARMY CORPS OF ENGINEERS *
* HYDROLOGIC ENGINEERING CENTER *
* 609 SECOND STREET, SUITE D *
* DAVIS, CALIFORNIA 95616-4687 *
* (916) 756-1104 *
*****

```

```

X X XXXXXXX XXXXX XXXXX
X X X X X X X
X X X X X X
XXXXXXXX XXXX X XXXXX XXXXX
X X X X X X
X X X X X X
X X XXXXXXX XXXXX XXXXXXX

```

```

1 16JUN04 14:17:54 PAGE 1

```

THIS RUN EXECUTED 16JUN04 14:17:54

```

*****
HEC-2 WATER SURFACE PROFILES
Version 4.6.2; May 1991
*****

```

```

T1 758.002 PHASE 209
T2 CLOMR FOR LONGFORD HOMES
T3 DCL1SUBX
T4 HEC-2 MODEL FROM DUCK CREEK/BLUE DIAMOND FIS RESTUDY: DCL1SUBC.DAT
T4 FLOODPLAIN/FLOODWAY MODEL; BREAKOUT AT WARM SPRINGS RD CONTAINED
T4 SUBCRITICAL
T4 STREAM NAME: DUCK CREEK
T4 UPSTREAM LIMIT: CROSS SECTION 15400, DOWNSTREAM OF EASTERN AVE
T4 DOWNSTREAM LIMIT: CROSS SECTION 10600

```

J1	ICHECK	INQ	NINV	IDIR	STRT	METRIC	HVINS	Q	WSEL	FQ
		0						8562	1949.3	
J2	NPROF	IPLOT	PREVS	XSECV	XSECH	FN	ALLDC	IBW	CHNIM	ITRACE
	1		-1			-1		-6		0

```

J3 VARIABLE CODES FOR SUMMARY PRINTOUT
200 150 101 100

```

```

1 16JUN04 14:17:54 PAGE 2

```

```

NC 0.08 0.11 0.015 0.1 0.3

```

DOWNSTREAM LIMIT OF MODEL
ORIGINAL MODEL: DCLISUBC.DAT

ESTABLISHED WATER SURFACE ELEVATION = 1949.3 FT (SUPERCRITICAL CONDITI

X1	10600	8	2209.95	2299.38	356.88	402.83	378.87			
GR	1950	2209.95	1948	2229.01	1944	2237.56	1942	2242.81	1942	2270.77
GR	1944	2274.76	1948	2281.52	1952	2299.38				
NC	0.08	0.11	0.015	0.1	0.3					

1

16JUN04 14:17:54

PAGE 3

X1	10700	7	1984.66	2093.9	430.71	421.11	418.08			
GR	1956	1984.66	1952	2025.37	1948	2033.98	1948	2067.44	1952	2074.65
GR	1956	2083.13	1960	2093.9						
NC	0.11	0.11	0.015	0.1	0.3					

X1	10800	6	2155.44	2258.77	410.33	392.26	386.03			
GR	1960	2155.44	1956	2186.29	1952	2195.29	1952	2229.27	1956	2236.88
GR	1960	2258.77								
NC	0.08	0.11	0.015	0.1	0.3					
X1	10900	7	1859.99	1943.58	386.71	376.94	388.5			
GR	1964	1859.99	1960	1889.41	1956	1897.52	1956	1933.17	1960	1938.52
GP	1964	1943.58	1968	1950.63						
NC	0.08	0.11	0.015	0.1	0.3					
X1	11000	8	1814.89	1912.16	347.02	420.02	392.7			
GR	1972	1799.08	1968	1814.89	1964	1845.64	1960	1853.3	1960	1887.79
GR	1964	1894.39	1968	1900.91	1972	1912.16				
NC	0.08	0.11	0.015	0.1	0.3					

16JUN04 14:17:54

PAGE 4

X1	11100	8	1886.46	1971.49	325.47	495.3	411.3			
GR	1972	1886.46	1968	1899.6	1964	1906.8	1960	1912.18	1960	1941.39
GP	1964	1946.06	1968	1955.18	1972	1971.49				
NC	0.015	0.015	0.015	0.1	0.3					
X1	11200	6	1924.66	1989.1	319.86	510.47	430.53			
GR	1972	1924.66	1968	1933.3	1962	1940.2	1962	1974.26	1968	1981.39
GR	1972	1989.1								
NC	0.015	0.015	0.015	0.1	0.3					
X1	11300	6	1846.27	1907.7	469.26	455.15	474			
GR	1972	1846.27	1968	1854.64	1964	1863.11	1964	1892.84	1968	1900.18
GR	1972	1907.7								
NC	0.015	0.015	0.015	0.1	0.3					
DOWNSTREAM FACE OF PECOS ROAD BRIDGE										
DOWNSTREAM FACE OF PECOS ROAD BRIDGE										
X1	11400	4	1000	1042	243.24	244.99	243.55			
GR	1975.5	1000	1964.02	1000	1964.02	1042	1975.5	1042		
NC	0.015	0.015	0.015	0.1	0.3					
SB		1.5	3	42	42		252	0	1964.52	1964.02
UPSTREAM FACE OF PECOS ROAD BRIDGE										
UPSTREAM FACE OF PECOS ROAD BRIDGE										
X1	11500	4	2258.08	2300.08		100	100	100		
X2			1	1990.52	1972.82					
GR	1975.3	2258.08	1964.52	2258.08	1964.52	2300.08	1975.3	2300.08		
NC	0.015	0.015	0.015	0.1	0.3					
DOWNSTREAM FACE OF CROSSING										
DOWNSTREAM FACE OF CROSSING										
X1	11600	4	1000	1034.4	215.89	214.6	215			
GR	1979.8	1000	1967.32	1000	1967.32	1034.4	1979.8	1034.4		
NC	0.015	0.015	0.015	0.1	0.3					
SB	0.9	1.5	3	34.4	34.4	1.5	297	0	1968.25	1967.32
UPSTREAM FACE OF CROSSING										
UPSTREAM FACE OF CROSSING										
X1	11700	4	966.89	1001.29		16	16	16		
X2			1	1996.89	1999.84				1.33	
GR	1979.8	966.89	1968.25	966.89	1968.25	1001.29	1979.8	1001.29		
NC	0.015	0.015	0.015	0.1	0.3					
X1	11800	4	1000	1034.4		86	86	86		
GR	1981.1	1000	1969.57	1000	1969.57	1034.4	1981.1	1034.4		
NC	0.015	0.015	0.015	0.1	0.3					
DOWNSTREAM FACE OF CROSSING										

16JUN04 14:17:54

PAGE 5

DOWNSTREAM FACE OF CROSSING										
X1	11900	4	996.53	1030.83		92	92	92		
GR	1990	996.53	1970.88	996.53	1970.88	1030.83	1990	1030.83		
NC	0.015	0.015	0.015	0.1	0.3					
SB		1.5	3	34.3	34.3		260	0	1970.97	1970.88
UPSTREAM FACE OF CROSSING										
UPSTREAM FACE OF CROSSING										
X1	12000	4	970.15	1004.49		5	5	5		
X2			1	1998.54	1990.99					
GR	1990	970.15	1970.97	970.15	1970.97	1004.49	1990.99	1004.49		
NC	0.015	0.015	0.015	0.1	0.3					
X1	12100	4	1205.25	1246.05		252	252	252		
GR	1984.6	1205.25	1974.6	1205.25	1974.6	1246.05	1984.6	1246.05		
NC	0.015	0.015	0.015	0.1	0.3					
X1	12200	4	1207.74	1252.82	289.39	297.62	287.98			
GR	1988.8	1207.74	1978.83	1207.74	1978.83	1252.82	1988.8	1252.82		
NC	0.015	0.015	0.015	0.1	0.3					
DOWNSTREAM FACE OF TOMIYASU BRIDGE										
DOWNSTREAM FACE OF TOMIYASU BRIDGE										
X1	12300	4	1394.43	1468.12	277.2	272.41	277.73			
GR	1989.4	1394.43	1982.84	1406.28	1982.84	1456.28	1989.4	1468.12		
NC	0.015	0.015	0.015	0.1	0.3					

SB	1.25	1.5	3	73	50	1	351	1.8	1983.11	1982.84
UPSTREAM FACE OF TOMIYASU LANE BRIDGE										
UPSTREAM FACE OF TOMIYASU LANE BRIDGE										
X1	12400	4	2222.53	2295.25	78.79	77.02	75.37			
X2			1	2009.42	2012			2		
GR	1989.4	2222.53	1983.11	2233.89	1983.11	2283.89	1989.4	2295.25		

NC	0.015	0.015	0.015	0.1	0.3					
TRANSITION DOWNSTREAM TRAP										
PLANS STA 38+89.86										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
TRANSITION DOWNSTREAM TRAP										
PLANS STA 38+89.86										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
X1	12500	4	2495.63	2571.5	85.83	90.77	88.6			
GR	1991.1	2495.63	1983.7	2508.99	1983.7	2559.02	1991.1	2571.5		

NC	0.015	0.015	0.015	0.1	0.3					
TRANSITION UPSTREAM RECT										
PLANS STA 38+14.44										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
TRANSITION UPSTREAM RECT										

1 16JUN04 14:17:54 PAGE 6

PLANS STA 38+14.44										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
X1	12600	4	1000	1050	75	75	75			
GR	1993.6	1000	1985.63	1000	1985.63	1050	1993.6	1050		

NC	0.015	0.015	0.015	0.1	0.3					
PLANS STA 35+00.00										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
PLANS STA 35+00.00										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
X1	12700	4	2430.44	2480.44	317.32	309.52	313.04			
GR	1995.1	2430.44	1988.15	2430.44	1988.15	2480.44	1995.1	2480.44		

NC	0.015	0.015	0.015	0.1	0.3					
PLANS STA 31+00.00										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
PLANS STA 31+00.00										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
X1	12800	4	2505.21	2555.21	405	405	405			
GR	1998.3	2505.21	1991.35	2505.21	1991.35	2555.21	1998.3	2555.21		

NC	0.015	0.015	0.015	0.1	0.3					
DOWNSTREAM FACE OF MIRA VISTA BRIDGE										
PLANS STA 28+43.76										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
DOWNSTREAM FACE OF MIRA VISTA BRIDGE										
PLANS STA 28+43.76										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
X1	12900	4	2630.84	2680.84	260.12	257.73	258.77			
GR	2004.2	2630.84	1993.47	2630.84	1993.47	2680.84	2004.2	2680.84		

NC	0.015	0.015	0.015	0.1	0.3					
SB	1.5	3	50	50		350	0	1993.9	1993.47	

UPSTREAM FACE OF MIRA VISTA STREET BRIDGE										
PLANS STA 28+10.59										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
UPSTREAM FACE OF MIRA VISTA STREET BRIDGE										
PLANS STA 28+10.59										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
X1	13000	4	2587.74	2637.74	33	33	33			
X2			1	2020.9	2004.2					
GR	2004.2	2587.74	1993.9	2587.74	1993.9	2637.74	2004.2	2637.74		

NC	0.015	0.015	0.015	0.1	0.3					
PLANS STA 27+00.00										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
PLANS STA 27+00.00										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
X1	13100	6	994.85	1044.85	98	98	98			
GR	2006	994.85	2005	994.85	1998.99	994.85	1998.99	1044.85	2005	1044.85
GR	2006	1044.85								

1 16JUN04 14:17:54 PAGE 7

NC	0.015	0.015	0.015	0.1	0.3					
TRANSITION - DOWNSTREAM RECT										
PLANS STA 24+90.00										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
TRANSITION - DOWNSTREAM RECT										
PLANS STA 24+90.00										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
X1	13200	4	995	1045	209.18	210.5	211.13			
GP	2008.5	995	2001.4	995	2001.4	1045	2008.5	1045		

NC 0.08 0.08 0.015 0.1 0.3
 TRANSITION - UPSTREAM TRAP
 PLANS STA 24+12.75
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 TRANSITION - UPSTREAM TRAP
 PLANS STA 24+12.75
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 X1 13300 4 997.5 1072.5 80 80 80
 GR 2009.3 997.5 2002.29 1010 2002.29 1060 2009.3 1072.5

NC 0.08 0.08 0.015 0.1 0.3
 DOWNSTREAM FACE OF PACHUCA BRIDGE
 PLANS STA 23+16.50
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 DOWNSTREAM FACE OF PACHUCA BRIDGE
 PLANS STA 23+16.50
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 X1 13400 4 2794.52 2869.52 100.24 100 100
 GR 2009.7 2794.52 2002.77 2807.02 2002.77 2857.02 2009.7 2869.52

NC 0.08 0.08 0.015 0.1 0.3
 SB 1.5 3 75 50 438 1.8 2003.07 2002.77
 UPSTREAM FACE OF PACHUCA STREET BRIDGE
 PLANS STA 22+83.50
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 UPSTREAM FACE OF PACHUCA STREET BRIDGE
 PLANS STA 22+83.50
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 X1 13500 4 1409.5 1484.5 37.16 36.94 36
 X2 1 2030.07 2012.33
 GR 2010 1409.5 2003.07 1422 2003.07 1472 2010 1484.5

NC 0.015 0.015 0.015 0.1 0.3
 TRANSITION DOWNSTREAM TRAP
 PLANS STA 21+81.14
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 TRANSITION DOWNSTREAM TRAP
 PLANS STA 21+81.14

1 16JUN04 14:17:54 PAGE 8

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 X1 13600 4 1395.5 1470.5 151.8 88.79 88.14
 GR 2013.1 1395.5 2006.11 1408 2006.11 1458 2013.1 1470.5

NC 0.015 0.015 0.015 0.1 0.3
 TRANSITION UPSTREAM RECT
 PLANS STA 21+06.00
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 TRANSITION UPSTREAM RECT
 PLANS STA 21+06.00
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 X1 13700 6 1000 1050 75 75 75
 GR 2014 1000 2013.5 1000 2006.56 1000 2006.56 1050 2013.5 1050
 GR 2014 1050

NC 0.015 0.015 0.015 0.1 0.3
 PLANS STA 18+00.00
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 PLANS STA 18+00.00
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 X1 13800 4 1000 1050 306 306 306
 GR 2015.4 1000 2008.4 1000 2008.4 1050 2015.4 1050

NC 0.015 0.015 0.015 0.1 0.3
 GRADEBREAK AT DOWNSTREAM FACE OF VISTA DEL SOL AVENUE
 PLANS STA 15+00.00
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 GRADEBREAK AT DOWNSTREAM FACE OF VISTA DEL SOL AVENUE
 PLANS STA 15+00.00
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 X1 13900 4 1000 1050 300 300 300
 GR 2019.4 1000 2010.21 1000 2010.21 1050 2019.4 1050

NC 0.015 0.015 0.015 0.1 0.3
 SB 1.5 3 50 50 425 0 2010.89 2010.21
 GRADEBREAK NEAR UPSTREAM FACE OF VISTA DEL SOL AVENUE BRIDGE
 PLANS STA 14+43.43
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 GRADEBREAK NEAR UPSTREAM FACE OF VISTA DEL SOL AVENUE BRIDGE
 PLANS STA 14+43.43
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 X1 14000 4 1000 1050 57 57 57
 X2 1 2039.39 2021.13
 GR 2019.4 1000 2010.89 1000 2010.89 1050 2019.4 1050

NC 0.015 0.015 0.015 0.1 0.3
 TRANSITION DOWNSTREAM RECT

PLANS STA 13+42.00

1

16JUN04 14:17:54

PAGE 9

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

TRANSITION DOWNSTREAM RECT
PLANS STA 13+42.00
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

X1	14100	8	1545.26	1624.79	101	101	101			
GR	2024	1545.26	2020	1556.5	2019.82	1559.32	2012.82	1559.32	2012.82	1609.32
GR	2019.8	1609.32	2020	1612.61	2024	1624.79				

NC	0.015	0.015	0.015	0.1	0.3					
----	-------	-------	-------	-----	-----	--	--	--	--	--

TRANSITION UPSTREAM 60' RECT TO 50' RECT

PLANS STA 12+67.00

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

TRANSITION UPSTREAM 60' RECT TO 50' RECT

PLANS STA 12+67.00

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

X1	14200	4	1000	1060	75	75	75			
GR	2022.7	1000	2014.24	1000	2014.24	1060	2022.7	1060		

NC	0.015	0.015	0.015	0.1	0.3					
X1	14220	4	1000	1060	20	20	20			
GR	2024.1	1000	2014.62	1000	2014.62	1060	2022.13	1060		

NC	0.015	0.015	0.015	0.1	0.3					
X1	14240	4	1000	1060	20	20	20			
GR	2024.5	1000	2015	1000	2015	1060	2022.53	1060		

NC	0.015	0.015	0.015	0.1	0.3					
DOWNSTREAM FACE OF UPRR BRIDGE - HENDERSON SPUR										
X1	14300	4	1701.5	1761.5	20	20	20			
GR	2028.8	1701.5	2015.3	1701.5	2015.3	1761.5	2028.8	1761.5		

NC	0.015	0.015	0.015	0.1	0.3					
SB	1.25	1.5	3	17	60	4	452	0	2015.8	2015.3

1

16JUN04 14:17:54

PAGE 10

UPSTREAM FACE OF UPRR BRIDGE - HENDERSON SPUR

X1	14400	4	1782	1842	20	20	20			
X2			1	2030	2031.2				2	
GR	2025.1	1782	2015.8	1782	2015.8	1842	2028.8	1842		

NC	0.015	0.015	0.015	0.1	0.3					
----	-------	-------	-------	-----	-----	--	--	--	--	--

X1	14450	4	1000	1060	20	20	20			
GR	2025.1	1000	2016.13	1000	2016.13	1060	2023.63	1060		

NC	0.015	0.015	0.015	0.1	0.3					
----	-------	-------	-------	-----	-----	--	--	--	--	--

X1	14500	4	1000	1060	50	50	50	
GR	2024.6	1000	2017.1	1000	2017.1	1060	2024.6	1060
NC	0.015	0.015	0.015	0.1	0.3			

X1	14550	4	1000	1060.06	40	40	40	
GR	2025.4	1000	2017.93	1000	2017.93	1060	2025.4	1060.06

1
16JUN04 14:17:54

PAGE 11

NC	0.015	0.015	0.015	0.1	0.3
----	-------	-------	-------	-----	-----

DOWNSTREAM FACE OF WARM SPRINGS ROAD BRIDGE

DOWNSTREAM FACE OF WARM SPRINGS ROAD BRIDGE

X1	14600	4	1390.42	1450.42	20	20	20	
GR	2030.2	1390.42	2018.37	1390.42	2018.37	1450.42	2030.2	1450.42

SB 1.25 1.5 3 103 60 2.13 588 0 2018.71 2018.37

BEGIN CHANGES FOR LONGFORD HOMES CLOMR
UPSTREAM FACE OF WARM SPRINGS ROAD BRIDGE
PLANS STA 9+39.84
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

NC	0.015	0.015	0.015	0.1	0.3
----	-------	-------	-------	-----	-----

BEGIN CHANGES FOR LONGFORD HOMES CLOMR
UPSTREAM FACE OF WARM SPRINGS ROAD BRIDGE
PLANS STA 9+39.84
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

X1	14700	5	1000	1060	111.98	111.98	
X2			1	2038.69	2040.21		2
GR	2027.9	1000	2019.47	1000	2018.87	1030	2019.47 1060 2029.88 1060

PT
PLANS STA 8+83.50
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

NC	0.015	0.015	0.015	0.1	0.3
----	-------	-------	-------	-----	-----

PT
PLANS STA 8+83.50
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

X1	14750	5	1000	1060	56.34	56.34	56.34	
GR	2028.5	1000	2020.1	1000	2019.5	1030	2020.1 1060 2030.51 1060	

BEGIN RECTANGULAR CHANNEL BOTTOM TRANSITION
PLANS STA 7+84.00
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

NC	0.015	0.015	0.015	0.1	0.3
----	-------	-------	-------	-----	-----

PT
PLANS STA 8+83.50
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

X1	14750	5	1000	1060	56.34	56.34	56.34	
GR	2028.5	1000	2020.1	1000	2019.5	1030	2020.1 1060 2030.51 1060	

BEGIN RECTANGULAR CHANNEL BOTTOM TRANSITION
PLANS STA 7+84.00
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

NC	0.015	0.015	0.015	0.1	0.3
----	-------	-------	-------	-----	-----

1
16JUN04 14:17:54

PAGE 12

BEGIN RECTANGULAR CHANNEL BOTTOM TRANSITION
PLANS STA 7+84.00
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

X1	14800	5	1000	1065	99.5	99.5	99.5	
GR	2029.6	1000	2021.2	1000	2020.6	1035	2021.2 1065 2031.61 1065	

PVI
PLANS STA 6+81.44
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

NC	0.015	0.015	0.015	0.1	0.3
----	-------	-------	-------	-----	-----

PVI
PLANS STA 6+81.44
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

X1	14850	5	1000	1065	102.56	102.56	102.56			
GR	2030.8	1000	2022.34	1000	2021.74	1035	2022.34	1065	2032.75	1065
BRIDGE AT TOPAZ STREET										
PLANS STA 6+44.08										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
NC	0.015	0.015	0.015	0.1	0.3					
BRIDGE AT TOPAZ STREET										
PLANS STA 6+44.08										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
X1	14900	5	1000	1065	37.36	37.36	37.36			
GR	2031	1000	2022.61	1000	2022.01	1035	2022.61	1065	2033.02	1065
SB	0.90	1.5	3	90	65	1.5	455	0	2022.40	2022.01
BRIDGE AT TOPAZ STREET -- RIGHT WALL HEIGHT ADJUSTED										
PLANS STA 5+91.39										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
NC	0.015	0.015	0.015	0.1	0.3					
BRIDGE AT TOPAZ STREET -- RIGHT WALL HEIGHT ADJUSTED										
PLANS STA 5+91.39										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
X1	14950	7	1000	1065	52.69	52.69	52.69			
X2			1	2040	2042					
GR	2031	1000	2030.42	1000	2023	1000	2022.4	1035	2023	1065
GR	2030.4	1065	2031	1065						
FVI										
PLANS STA 5+28.97										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
NC	0.015	0.015	0.015	0.1	0.3					
FVI										
PLANS STA 5+28.97										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
X1	15000	0	0	0	84.63	84.63	84.63	0	0.51	
PC										
PLANS STA 4+44.34										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										

1 16JUN04 14:17:54 PAGE 13

NC	0.015	0.015	0.015	0.1	0.3					
PC										
PLANS STA 4+44.34										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
X1	15050	0	0	0	62.42	62.42	62.42	0	0.38	
FVI										
PLANS STA 3+28.97										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
NC	0.015	0.015	0.015	0.1	0.3					
FVI										
PLANS STA 3+28.97										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
X1	15100	0	0	0	115.37	115.37	115.37	0	0.69	
PT										
PLANS STA 3+25.54										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
NC	0.015	0.015	0.015	0.1	0.3					
FT										
PLANS STA 3+25.54										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
X1	15110	7	1000	1065	3.43	3.43	3.43	0	0.02	
GR	2033	1000	2032.02	1000	2024.6	1000	2024	1035	2024.6	1065
GR	2032.0	1065	2033	1065						
BEGIN TRANSITION FROM TRAPEZOIDAL TO RECTANGULAR CHANNEL										
PLANS STA 1+25.54										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
NC	0.015	0.015	0.015	0.1	0.3					
BEGIN TRANSITION FROM TRAPEZOIDAL TO RECTANGULAR CHANNEL										
PLANS STA 1+25.54										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
X1	15150	7	1000	1095	200	200	200			
GR	2036	1000	2033.34	1000	2025.84	1015	2025.24	1050	2025.84	1080
GR	2033.3	1095	2036	1095						
PLANS STA 0+12.31										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
NC	0.015	0.015	0.015	0.1	0.3					
PLANS STA 0+12.31										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
X1	15200	7	1000	1095	113.23	113.23	113.23			
GR	2037	1000	2034.04	1000	2026.54	1015	2025.94	1050	2026.54	1080
GR	2034.0	1095	2037	1095						
PC										
PLANS STA -0+49.25										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										

```

NC      0.015      0.015      0.015      0.1      0.3
      FC
      PLANS STA -0+49.25
      PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
X1      15250      7      1000      1092.26      61.56      61.56      61.56
GR      2037      1000      2034.43      1000      2026.93      1015      2026.33      1047.26      2026.93      1077.26
GR      2034.4      1092.26      2037      1092.26
      BEGIN CHANNEL IMPROVEMENTS/BEGIN TRAP CHANNEL BOTTOM TRANSITION
      PLANS STA -1+00
      PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
      LIMIT OF REVISIONS FOR LONGFORD HOMES CLOMR

NC      0.015      0.015      0.015      0.1      0.3
      BEGIN CHANNEL IMPROVEMENTS/BEGIN TRAP CHANNEL BOTTOM TRANSITION
      PLANS STA -1+00
      PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
      END OF REVISIONS FOR LONGFORD HOMES CLOMR
X1      15300      7      1000      1090      50.75      50.75      50.75
GR      2037      1000      2034.74      1000      2027.24      1015      2026.64      1045      2027.24      1075
GR      2034.7      1090      2037      1090

NC      0.08      0.11      0.015      0.1      0.3
X1      15400      8      1203.85      1302.87      439.74      434.2      471.4
GR      2040      1000      2040      1203.85      2036      1212.42      2027.5      1221.41      2027.5      1289.16
GR      2036      1295.88      2040      1302.87      2044      1611.48

NC      0.08      0.11      0.015      0.1      0.3
      DOWNSTREAM FACE OF EASTERN AVENUE BRIDGE
      DOWNSTREAM FACE OF EASTERN AVENUE BRIDGE
      START OF MODEL
      ORIGINAL MODEL: DCL1SUPC.DAT
      ESTABLISHED WATER SURFACE ELEVATION = 2037.8 FT (SUBCRITICAL CONDITIONS)
X1      15500      6      1642.82      1699.82      214.02      136.16      166.19
GR      2040      1400.58      2039.5      1642.82      2028.25      1642.82      2028.25      1699.82      2039.5      1699.82
GR      2044      1982.77

```

SECNO	DEPTH	CWSEL	CRWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*PROF 1

CRITICAL DEPTH TO BE CALCULATED AT ALL CROSS SECTIONS

0

CCHV= .100 CEHV= .300

*SECNO 10600.000

3280 CROSS SECTION 10600.00 EXTENDED 2.43 FEET

3720 CRITICAL DEPTH ASSUMED

DOWNSTREAM LIMIT OF MODEL

ORIGINAL MODEL: DCL1SUBC.DAT

ESTABLISHED WATER SURFACE ELEVATION = 1949.3 FT (SUPERCRITICAL CONDITI

10600.000	10.43	1952.43	1952.43	1949.30	1955.75	3.32	.00	.00	1950.00
8562.0	.0	8562.0	.0	.0	585.6	.0	.0	.0	1952.00
.00	.00	14.62	.00	.000	.015	.000	.000	1942.00	2209.95
.001945	357.	379.	403.	0	10	0	.00	89.43	2299.38

CCHV= .100 CEHV= .300

*SECNO 10700.000

3280 CROSS SECTION 10700.00 EXTENDED 1.49 FEET

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

10700.000	9.49	1957.49	1957.49	.00	1960.54	3.05	.82	.03	1956.00
8562.0	.0	8562.0	.0	.0	610.8	.0	5.7	.9	1960.00
.01	.00	14.02	.00	.000	.015	.000	.000	1948.00	1984.66
.001969	431.	418.	421.	0	11	0	.00	102.48	2087.14

CCHV= .100 CEHV= .300

*SECNO 10800.000

3280 CROSS SECTION 10800.00 EXTENDED 1.34 FEET

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

10800.000	9.34	1961.34	1961.34	.00	1964.35	3.01	.76	.00	1960.00
8562.0	.0	8562.0	.0	.0	615.4	.0	11.2	1.8	1960.00
.02	.00	13.91	.00	.000	.015	.000	.000	1952.00	2155.44
.001949	410.	386.	390.	0	8	0	.00	103.33	2258.77

16JUN04 14:17:54

PAGE 16

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

CCHV= .100 CEHV= .300

*SECNO 10900.000

3280 CROSS SECTION 10900.00 EXTENDED 1.63 FEET

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

10900.000	9.63	1965.63	1965.63	.00	1969.12	3.49	.75	.14	1964.00
8562.0	.0	8560.9	1.1	.0	571.2	2.3	16.5	2.7	1964.00
.02	.00	14.99	.47	.000	.015	.110	.000	1956.00	1859.99
.001923	387.	389.	377.	0	8	0	.00	86.46	1946.45

CCHV= .100 CEHV= .300

*SECNO 11000.000

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

11000.000	9.76	1969.76	1969.76	.00	1973.01	3.25	.74	.02	1968.00
8562.0	4.4	8557.6	.0	6.1	591.7	.0	21.8	3.5	1972.00
.03	.72	14.46	.00	.080	.015	.000	.000	1960.00	1807.94
.001854	347.	393.	420.	0	5	0	.00	97.92	1905.86

CCHV= .100 CEHV= .300

*SECNO 11100.000

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

11100.000	11.56	1971.56	1971.56	.00	1975.05	3.49	.77	.07	1972.00
8562.0	.0	8562.0	.0	.0	571.4	.0	27.3	4.3	1972.00
.04	.00	14.98	.00	.000	.015	.000	.000	1960.00	1887.90
.001873	325.	411.	495.	0	8	0	.00	81.91	1969.71

CCHV= .100 CEHV= .300

*SECNO 11200.000

3280 CROSS SECTION 11200.00 EXTENDED .81 FEET

16JUN04 14:17:54

PAGE 17

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3301 HV CHANGED MORE THAN HVINS

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

11200.000	10.81	1972.81	1972.81	.00	1976.96	4.15	.82	.20	1972.00
8562.0	.0	8562.0	.0	.0	523.9	.0	32.7	5.1	1972.00
.05	.00	16.34	.00	.000	.015	.000	.000	1962.00	1924.66
.001943	320.	431.	510.	0	11	0	.00	64.44	1989.10

CCHV= .100 CEHV= .300

*SECNO 11300.000

3280 CROSS SECTION 11300.00 EXTENDED 2.51 FEET

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

11300.000	10.51	1974.51	1974.51	.00	1978.74	4.24	.92	.03	1972.00
8562.0	.0	8562.0	.0	.0	518.4	.0	38.4	5.8	1972.00
.05	.00	16.52	.00	.000	.015	.000	.000	1964.00	1846.27
.001935	469.	474.	455.	0	8	0	.00	61.43	1907.70

CCHV= .100 CEHV= .300

*SECNO 11400.000

3301 HV CHANGED MORE THAN HVINS

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

DOWNSTREAM FACE OF PECOS ROAD BRIDGE

11400.000	10.85	1974.87	1974.87	.00	1980.35	5.48	.54	.37	1975.50
8562.0	.0	8562.0	.0	.0	455.6	.0	41.1	6.0	1975.50
.06	.00	18.79	.00	.000	.015	.000	.000	1964.02	1000.00
.002611	243.	244.	245.	0	8	0	.00	42.00	1042.00

CCHV= .100 CEHV= .300

1

16JUN04 14:17:54

PAGE 18

SECNO	DEPTH	CWSEL	CRISW	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	.00	1.50	3.00	42.00	42.00	.00	252.00	.00	1964.52	1964.02

*SECNO 11500.000

6070, LOW FLOW BY NORMAL BRIDGE

EGPRS= .000 EGLWC= 1980.852 ELLC= 1990.520 PCWSE= 1974.868 ELTRD= 1972.820
3280 CROSS SECTION 11500.00 EXTENDED .07 FEET

3370 NORMAL BRIDGE, NRD= 0 MIN ELTRD= 1972.82 MAX ELLC= 1990.52

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

UPSTREAM FACE OF PECOS ROAD BRIDGE

11500.000	10.85	1975.37	1975.37	.00	1980.85	5.48	.26	.00	1975.30
8562.0	.0	8562.0	.0	.0	455.6	.0	42.1	6.1	1975.30
.06	.00	18.79	.00	.000	.015	.000	.000	1964.52	2258.08
.002610	100.	100.	100.	0	15	0	.00	42.00	2300.08

CCHV= .100 CEHV= .300

*SECNO 11600.000

3301 HV CHANGED MORE THAN HVINS

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

DOWNSTREAM FACE OF CROSSING

11600.000	12.42	1979.74	1979.74	.00	1985.98	6.23	.59	.22	1979.80
8562.0	.0	8562.0	.0	.0	427.4	.0	44.3	6.3	1979.80
.06	.00	20.03	.00	.000	.015	.000	.000	1967.32	1000.00
.002933	216.	215.	215.	0	8	0	.00	34.40	1034.40

CCHV= .100 CEHV= .300

1

16JUN04 14:17:54

PAGE 19

SECNO	DEPTH	CWSEL	CRISW	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

SPECIAL BRIDGE

5227 DOWNSTREAM ELEV IS 1977.87 , NOT 1979.74 HYDRAULIC JUMP OCCURS DOWNSTREAM (IF LOW FLOW CONTROLS)

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	.90	1.50	3.00	34.40	34.40	1.50	297.00	.00	1968.25	1967.32

*SECNO 11700.000

3280 CROSS SECTION 11700.00 EXTENDED 4.20 FEET

3301 HV CHANGED MORE THAN HVINS

CLASS B LOW FLOW

3420 BRIDGE W.S.= 1980.59 BRIDGE VELOCITY= 20.32 CALCULATED CHANNEL AREA= 406.

EGPRS	EGLWC	H3	QWEIR	QLOW	BAREA	TRAPEZOID AREA	ELLC	ELTRD	WEIRLN
.00	1987.88	.00	0.	8562.	297.	942.	1996.89	1999.84	0.

UPSTREAM FACE OF CROSSING

11700.000	15.75	1984.00	.00	.00	1987.88	3.88	1.90	.00	1979.80
8562.0	.0	8562.0	.0	.0	541.9	.0	44.5	6.3	1979.80
.06	.00	15.80	.00	.000	.015	.000	.000	1968.25	966.89
.001533	16.	16.	16.	0	0	0	.00	34.40	1001.29

CCHV= .100 CEHV= .300
 *SECNO 11800.000
 3280 CROSS SECTION 11800.00 EXTENDED 2.21 FEET

3301 HV CHANGED MORE THAN HVINS

11800.000	13.74	1983.31	1981.96	.00	1988.40	5.10	.16	.37	1981.10
8562.0	.0	8562.0	.0	.0	472.6	.0	45.5	6.4	1981.10
.06	.00	18.12	.00	.000	.015	.000	.000	1969.57	1000.00
.002224	86.	86.	86.	3	15	0	.00	34.40	1034.40

CCHV= .100 CEHV= .300

1

16JUN04 14:17:54

PAGE 20

SECNO	DEPTH	CWSEL	CRISW	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XLN	LNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 11900.000

3301 HV CHANGED MORE THAN HVINS

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

DOWNSTREAM FACE OF CROSSING

11900.000	12.42	1983.30	1983.30	.00	1989.57	6.28	.23	.35	1990.00
8562.0	.0	8562.0	.0	.0	425.8	.0	46.4	6.5	1990.00
.06	.00	20.11	.00	.000	.015	.000	.000	1970.88	996.53
.002961	92.	92.	92.	0	11	0	.00	34.30	1030.83

CCHV= .100 CEHV= .300

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	.00	1.50	3.00	34.30	34.30	.00	260.00	.00	1970.97	1970.88

*SECNO 12000.000

6070, LOW FLOW BY NORMAL BRIDGE

EGPRS= .000 EGLWC= 1989.648 ELLC= 1998.540 PCWSE= 1983.295 ELTRD= 1990.990

3370 NORMAL BRIDGE, NRD= 0 MIN ELTRD= 1990.99 MAX ELLC= 1998.54

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

UPSTREAM FACE OF CROSSING

12000.000	12.42	1983.39	1983.39	.00	1989.65	6.26	.01	.00	1990.00
8562.0	.0	8562.0	.0	.0	426.5	.0	46.5	6.5	1990.99
.06	.00	20.08	.00	.000	.015	.000	.000	1970.97	970.15
.002950	5.	5.	5.	0	9	0	.00	34.34	1004.49

CCHV= .100 CEHV= .300

*SECNO 12100.000

3280 CROSS SECTION 12100.00 EXTENDED 1.06 FEET

3301 HV CHANGED MORE THAN HVINS

7185 MINIMUM SPECIFIC ENERGY

1

16JUN04 14:17:54

PAGE 21

SECNO	DEPTH	CWSEL	CRISW	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XLN	LNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3720 CRITICAL DEPTH ASSUMED

12100.000	11.06	1985.66	1985.66	.00	1991.25	5.59	.70	.07	1984.60
8562.0	.0	8562.0	.0	.0	451.2	.0	49.0	6.7	1984.60
.07	.00	18.97	.00	.000	.015	.000	.000	1974.60	1205.25
.002652	252.	252.	252.	0	11	0	.00	40.80	1246.05

CCHV= .100 CEHV= .300
 *SECNO 12200.000
 3280 CROSS SECTION 12200.00 EXTENDED .38 FEET

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

12200.000	10.35	1989.18	1989.18	.00	1994.41	5.23	.74	.04	1988.80
8562.0	.0	8562.0	.0	.0	466.5	.0	52.0	7.0	1988.80
.07	.00	18.35	.00	.000	.015	.000	.000	1978.83	1207.74
.002518	289.	288.	298.	0	11	0	.00	45.08	1252.82

CCHV= .100 CEHV= .300
 *SECNO 12300.000
 3280 CROSS SECTION 12300.00 EXTENDED 2.34 FEET

3301 HV CHANGED MORE THAN HVINS

DOWNSTREAM FACE OF TOMIYASU BRIDGE

12300.000	8.90	1991.74	1991.34	.00	1995.15	3.41	.56	.18	1989.40
8562.0	.0	8562.0	.0	.0	578.1	.0	55.4	7.4	1989.40
.08	.00	14.81	.00	.000	.015	.000	.000	1982.84	1394.43
.001647	277.	278.	272.	4	15	0	.00	73.69	1468.12

CCHV= .100 CEHV= .300

SPECIAL BRIDGE

5227 DOWNSTREAM ELEV IS 1990.80 , NOT 1991.74 HYDRAULIC JUMP OCCURS DOWNSTREAM (IF LOW FLOW CONTROLS)

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.25	1.50	3.00	73.00	50.00	1.00	351.00	1.80	1983.11	1982.84

*SECNO 12400.000
 3280 CROSS SECTION 12400.00 EXTENDED 3.49 FEET

1

16JUN04 14:17:54

PAGE 22

SECNO	DEPTH	CWSEL	CRWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3301 HV CHANGED MORE THAN HVINS

CLASS B LOW FLOW

3420 BRIDGE W.S.= 1991.75 BRIDGE VELOCITY= 15.07 CALCULATED CHANNEL AREA= 557.

EGFRS	EGLWC	H3	QWEIR	QLOW	BAREA	TRAPEZOID	ELLC	ELTRD	WEIRLN
	.00	1995.67	.00	0.	8562.	351.	2535.	2009.42	2012.00
									0.

UPSTREAM FACE OF TOMIYASU LANE BRIDGE

12400.000	9.78	1992.89	.00	.00	1995.67	2.78	.52	.00	1989.40
8562.0	.0	8562.0	.0	.0	639.6	.0	56.4	7.5	1989.40
.08	.00	13.39	.00	.000	.015	.000	.000	1983.11	2222.53
.001199	79.	75.	77.	0	0	0	.00	72.72	2295.25

CCHV= .100 CEHV= .300
 *SECNO 12500.000
 3280 CROSS SECTION 12500.00 EXTENDED 1.47 FEET

3301 HV CHANGED MORE THAN HVINS

TRANSITION DOWNSTREAM TRAP
 PLANS STA 38+89.86
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

12500.000	8.87	1992.57	1992.28	.00	1995.98	3.41	.12	.19	1991.10
8562.0	.0	8562.0	.0	.0	577.6	.0	57.7	7.6	1991.10
.08	.00	14.82	.00	.000	.015	.000	.000	1983.70	2495.63
.001678	86.	89.	91.	3	11	0	.00	75.87	2571.50

CCHV= .100 CEHV= .300
 *SECNO 12600.000
 3280 CROSS SECTION 12600.00 EXTENDED 1.69 FEET

3301 HV CHANGED MORE THAN HVINS

7185 MINIMUM SPECIFIC ENERGY

1

SECNO	DEPTH	CWSEL	CRWS	WSELK	EG	HV	HL	OLOSS	L-BANK	ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK	ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA	
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST	

3720 CRITICAL DEPTH ASSUMED

TRANSITION UPSTREAM RECT

PLANS STA 38+14.44

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

12600.000	9.66	1995.29	1995.29	.00	2000.17	4.88	.15	.44	1993.60	
8562.0	.0	8562.0	.0	.0	483.1	.0	58.6	7.8	1993.60	
.08	.00	17.72	.00	.000	.015	.000	.000	1985.63	1000.00	
.002403	75.	75.	75.	0	8	0	.00	50.00	1050.00	

CCHV= .100 CEHV= .300

*SECNO 12700.000

3280 CROSS SECTION 12700.00 EXTENDED 2.72 FEET

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

PLANS STA 35+00.00

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

12700.000	9.67	1997.82	1997.82	.00	2002.69	4.87	.75	.00	1995.10	
8562.0	.0	8562.0	.0	.0	483.3	.0	62.1	8.1	1995.10	
.09	.00	17.72	.00	.000	.015	.000	.000	1988.15	2430.44	
.002401	317.	313.	310.	0	5	0	.00	50.00	2480.44	

CCHV= .100 CEHV= .300

*SECNO 12800.000

3280 CROSS SECTION 12800.00 EXTENDED 2.72 FEET

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

PLANS STA 31+00.00

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

12800.000	9.67	2001.02	2001.02	.00	2005.89	4.87	.97	.00	1998.30	
8562.0	.0	8562.0	.0	.0	483.3	.0	66.5	8.6	1998.30	
.09	.00	17.72	.00	.000	.015	.000	.000	1991.35	2505.21	
.002402	405.	405.	405.	0	5	0	.00	50.00	2555.21	

CCHV= .100 CEHV= .300

*SECNO 12900.000

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

DOWNSTREAM FACE OF MIRA VISTA BRIDGE

1

16JUN04 14:17:54

PAGE 24

PLANS STA 28+43.76

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

12900.000	9.67	2003.14	2003.14	.00	2008.01	4.87	.62	.00	2004.20	
8562.0	.0	8562.0	.0	.0	483.3	.0	69.4	8.9	2004.20	
.10	.00	17.72	.00	.000	.015	.000	.000	1993.47	2630.84	
.002402	260.	259.	258.	0	5	0	.00	50.00	2680.84	

CCHV= .100 CEHV= .300

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	.00	1.50	3.00	50.00	50.00	.00	350.00	.00	1993.90	1993.47

*SECNO 13000.000

6070, LOW FLOW BY NORMAL BRIDGE

EGPRS= .000 EGLWC= 2008.439 ELLC= 2020.900 PCWSE= 2003.135 ELTRD= 2004.200

3370 NORMAL BRIDGE, NRD= 0 MIN ELTRD= 2004.20 MAX ELLC= 2020.90

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

UPSTREAM FACE OF MIRA VISTA STREET BRIDGE

PLANS STA 28+10.59

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

13000.000	9.66	2003.56	2003.56	.00	2008.44	4.88	.08	.00	2004.20	
8562.0	.0	8562.0	.0	.0	482.9	.0	69.8	8.9	2004.20	
.10	.00	17.73	.00	.000	.015	.000	.000	1993.90	2587.74	
.002407	33.	33.	33.	0	19	0	.00	50.00	2637.74	

CCHV= .100 CEHV= .300

*SECNO 13100.000

3280 CROSS SECTION 13100.00 EXTENDED 2.66 FEET

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

PLANS STA 27+00.00

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

13100.000	9.67	2008.66	2008.66	.00	2013.53	4.87	.24	.00	2006.00
8562.0	.0	8562.0	.0	.0	483.4	.0	70.9	9.0	2006.00
.10	.00	17.71	.00	.000	.015	.000	.000	1998.99	994.85
.002400	98.	98.	98.	0	5	0	.00	50.00	1044.85

CCHV= .100 CEHV= .300

*SECNO 13200.000

1

16JUN04 14:17:54

PAGE 25

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOFWID	ENDST

3280 CROSS SECTION 13200.00 EXTENDED 2.57 FEET

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

TRANSITION - DOWNSTREAM RECT

PLANS STA 24+90.00

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

13200.000	9.67	2011.07	2011.07	.00	2015.94	4.87	.51	.00	2008.50
8562.0	.0	8562.0	.0	.0	483.3	.0	73.2	9.3	2008.50
.10	.00	17.72	.00	.000	.015	.000	.000	2001.40	995.00
.002401	209.	211.	211.	0	5	0	.00	50.00	1045.00

CCHV= .100 CEHV= .300

*SECNO 13300.000

3280 CROSS SECTION 13300.00 EXTENDED 5.46 FEET

3301 HV CHANGED MORE THAN HVINS

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 2.24

TRANSITION - UPSTREAM TRAP

PLANS STA 24+12.75

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

13300.000	12.47	2014.76	2010.83	.00	2016.34	1.59	.07	.33	2009.30
8562.0	.0	8562.0	.0	.0	847.4	.0	74.4	9.4	2009.30
.11	.00	10.10	.00	.000	.015	.000	.000	2002.29	997.50
.000478	80.	80.	80.	5	11	0	.00	75.00	1072.50

CCHV= .100 CEHV= .300

*SECNO 13400.000

3280 CROSS SECTION 13400.00 EXTENDED 5.00 FEET

DOWNSTREAM FACE OF PACHUCA BRIDGE

PLANS STA 23+16.50

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

13400.000	11.93	2014.70	2011.30	.00	2016.44	1.74	.05	.05	2009.70
8562.0	.0	8562.0	.0	.0	808.1	.0	76.3	9.6	2009.70
.11	.00	10.60	.00	.000	.015	.000	.000	2002.77	2794.52
.000600	100.	100.	100.	2	14	0	.00	75.00	2869.52

1

16JUN04 14:17:54

PAGE 26

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOFWID	ENDST

CCHV= .100 CEHV= .300

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	.00	1.50	3.00	75.00	50.00	.00	438.00	1.80	2003.07	2002.77

*SECNO 13500.000

6070, LOW FLOW BY NORMAL BRIDGE

EGERS= .000 EGLWC= 2016.742 ELIC= 2030.070 FCWSE= 2014.699 ELTRI= 2012.330

3280 CROSS SECTION 13500.00 EXTENDED 4.64 FEET

3370 NORMAL BRIDGE, NRD= 0 MIN ELTRD= 2012.33 MAX ELLC= 2030.07

UPSTREAM FACE OF PACHUCA STREET BRIDGE
PLANS STA 22+83.50

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

13500.000	11.56	2014.63	2011.59	.00	2016.50	1.87	.02	.04	2010.00
8562.0	.0	8562.0	.0	.0	780.9	.0	77.0	9.6	2010.00
.11	.00	10.96	.00	.000	.015	.000	.000	2003.07	1409.50
.000619	37.	36.	37.	2	23	0	.00	75.00	1484.50

CCHV= .100 CEHV= .300

*SECNO 13600.000

3280 CROSS SECTION 13600.00 EXTENDED 1.56 FEET

3301 HV CHANGED MORE THAN HVINS

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

TRANSITION DOWNSTREAM TRAP

PLANS STA 21+81.14

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

13600.000	8.55	2014.66	2014.66	.00	2018.37	3.72	.09	.55	2013.10
8562.0	.0	8562.0	.0	.0	553.5	.0	78.3	9.8	2013.10
.11	.00	15.47	.00	.000	.015	.000	.000	2006.11	1395.50
.001903	152.	88.	89.	0	15	0	.00	75.00	1470.50

1

16JUN04 14:17:54

PAGE 27

SECNO	DEPTH	CWSEL	CRWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AOB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

CCHV= .100 CEHV= .300

*SECNO 13700.000

3280 CROSS SECTION 13700.00 EXTENDED 2.24 FEET

3301 HV CHANGED MORE THAN HVINS

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

TRANSITION UPSTREAM RECT

PLANS STA 21+06.00

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

13700.000	9.68	2016.24	2016.24	.00	2021.10	4.86	.16	.34	2014.00
8562.0	.0	8562.0	.0	.0	483.9	.0	79.2	9.9	2014.00
.11	.00	17.70	.00	.000	.015	.000	.000	2006.56	1000.00
.002393	75.	75.	75.	0	8	0	.00	50.00	1050.00

CCHV= .100 CEHV= .300

*SECNO 13800.000

3280 CROSS SECTION 13800.00 EXTENDED 2.66 FEET

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

PLANS STA 18+00.00

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

13800.000	9.66	2018.06	2018.06	.00	2022.94	4.88	.73	.00	2015.40
8562.0	.0	8562.0	.0	.0	483.1	.0	82.6	10.2	2015.40
.12	.00	17.72	.00	.000	.015	.000	.000	2008.40	1000.00
.002403	306.	306.	306.	0	5	0	.00	50.00	1050.00

CCHV= .100 CEHV= .300

*SECNO 13900.000

3280 CROSS SECTION 13900.00 EXTENDED .48 FEET

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

GRADEBREAK AT DOWNSTREAM FACE OF VISTA DEL SOL AVENUE

PLANS STA 15+00.00

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

13900.000	9.67	2019.88	2019.88	.00	2024.75	4.87	.72	.00	2019.40
8562.0	.0	8562.0	.0	.0	483.3	.0	86.0	10.6	2019.40
.12	.00	17.72	.00	.000	.015	.000	.000	2010.21	1000.00
.002401	300.	300.	300.	0	5	0	.00	50.00	1050.00

1

16JUN04 14:17:54

PAGE 28

SECNO	DEPTH	CWSEL	CRWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

CCHV= .100 CEHV= .300

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
.00	1.50	3.00	50.00	50.00	.00	425.00	.00	2010.89	2010.21	

*SECNO 14000.000

6070, LOW FLOW BY NORMAL BRIDGE

EGPRS= .000 EGLWC= 2025.429 ELLC= 2039.390 PCWSE= 2019.876 ELTRD= 2021.130
3280 CROSS SECTION 14000.00 EXTENDED 1.15 FEET

3370 NORMAL BRIDGE, NPD= 0 MIN ELTRD= 2021.13 MAX ELLC= 2039.39

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

GRADEBREAK NEAR UPSTREAM FACE OF VISTA DEL SOL AVENUE BRIDGE

PLANS STA 14+43.43

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

14000.000	9.66	2020.55	2020.55	.00	2025.43	4.88	.14	.00	2019.40
8562.0	.0	8562.0	.0	.0	483.0	.0	86.6	10.6	2019.40
.12	.00	17.73	.00	.000	.015	.000	.000	2010.89	1000.00
.002405	57.	57.	57.	0	19	0	.00	50.00	1050.00

CCHV= .100 CEHV= .300

*SECNO 14100.000

3301 HV CHANGED MORE THAN HVINS

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

TRANSITION DOWNSTREAM RECT

PLANS STA 13+42.00

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

14100.000	10.10	2022.92	2022.92	.00	2026.71	3.79	.23	.11	2024.00
8562.0	.0	8562.0	.0	.0	548.3	.0	87.8	10.8	2024.00
.12	.00	15.62	.00	.000	.015	.000	.000	2012.82	1548.30
.002172	101.	101.	101.	0	8	0	.00	73.20	1621.50

1

16JUN04 14:17:54

PAGE 29

SECNO	DEPTH	CWSEL	CRWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

CCHV= .100 CEHV= .300

*SECNO 14200.000

3280 CROSS SECTION 14200.00 EXTENDED .11 FEET

3301 HV CHANGED MORE THAN HVINS

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

TRANSITION UPSTREAM 60' RECT TO 50' RECT

PLANS STA 12+67.00

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

14200.000	8.57	2022.81	2022.81	.00	2027.12	4.30	.17	.15	2022.70
8562.0	.0	8562.0	.0	.0	514.4	.0	88.7	10.9	2022.70
.12	.00	16.64	.00	.000	.015	.000	.000	2014.24	1000.00
.002248	75.	75.	75.	0	11	0	.00	60.00	1060.00

CCHV= .100 CEHV= .300

*SECNO 14220.000

3280 CROSS SECTION 14220.00 EXTENDED 1.05 FEET

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

14220.000	8.56	2023.18	2023.18	.00	2027.50	4.32	.05	.01	2024.10
8562.0	.0	8562.0	.0	.0	513.4	.0	88.9	10.9	2022.13
.13	.00	16.68	.00	.000	.015	.000	.000	2014.62	1000.00
.002262	20.	20.	20.	0	5	0	.00	60.00	1060.00

CCHV= .100 CEHV= .300
*SECNO 14240.000
3280 CROSS SECTION 14240.00 EXTENDED 1.03 FEET

7185 MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED
14240.000 8.56 2023.56 2023.56 .00 2027.88 4.32 .05 .00 2024.50
8562.0 .0 8562.0 .0 .0 513.6 .0 89.2 10.9 2022.53
.13 .00 16.67 .00 .000 .015 .000 2015.00 1000.00
.002260 20. 20. 20. 0 5 0 .00 60.00 1060.00

1 16JUN04 14:17:54 PAGE 30

SECNO	DEPTH	CWSEL	CRISW	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

CCHV= .100 CEHV= .300
*SECNO 14300.000
7185 MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED
DOWNSTREAM FACE OF UPRR BRIDGE - HENDERSON SPUR
14300.000 8.56 2023.86 2023.86 .00 2028.18 4.32 .05 .00 2028.80
8562.0 .0 8562.0 .0 .0 513.6 .0 89.4 11.0 2028.80
.13 .00 16.67 .00 .000 .015 .000 2015.30 1701.50
.002260 20. 20. 20. 0 5 0 .00 60.00 1761.50

CCHV= .100 CEHV= .300

SPECIAL BRIDGE

5227 DOWNSTREAM ELEV IS 2022.31 , NOT 2023.86 HYDRAULIC JUMP OCCURS DOWNSTREAM (IF LOW FLOW CONTROLS)

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.25	1.50	3.00	17.00	60.00	4.00	452.00	.00	2015.80	2015.30

*SECNO 14400.000
3280 CROSS SECTION 14400.00 EXTENDED 2.21 FEET

3301 HV CHANGED MORE THAN HVINS

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 1.56

CLASS B LOW FLOW

3420 BRIDGE W.S.= 2024.54 BRIDGE VELOCITY= 17.02 CALCULATED CHANNEL AREA= 489.

EGPRS	EGLWC	H3	QWEIR	QLOW	BAFEA	TRAPEZOID AREA	ELLC	ELTRD	WEIRLN
.00	2029.69	.00	0.	8562.	452.	795.	2030.00	2031.20	0.

UPSTREAM FACE OF UPRR BRIDGE - HENDERSON SPUR
14400.000 11.51 2027.31 .00 .00 2029.69 2.39 1.52 .00 2025.10
8562.0 .0 8562.0 .0 .0 690.4 .0 89.7 11.0 2028.80
.13 .00 12.40 .00 .000 .015 .000 2015.80 1782.00
.000930 20. 20. 20. 0 0 0 .00 60.00 1842.00

1 16JUN04 14:17:54 PAGE 31

SECNO	DEPTH	CWSEL	CRISW	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

CCHV= .100 CEHV= .300
*SECNO 14450.000
3280 CROSS SECTION 14450.00 EXTENDED 3.56 FEET

14450.000 11.06 2027.19 2024.69 .00 2029.77 2.59 .02 .06 2025.10
8562.0 .0 8562.0 .0 .0 663.5 .0 90.0 11.0 2023.63
.13 .00 12.90 .00 .000 .015 .000 2016.13 1000.00
.000986 20. 20. 20. 2 15 0 .00 60.00 1060.00

CCHV= .100 CEHV= .300
*SECNO 14500.000
3280 CROSS SECTION 14500.00 EXTENDED 2.02 FEET

3301 HV CHANGED MORE THAN HVINS

14500.000	9.52	2026.62	2025.65	.00	2030.11	3.49	.06	.27	2024.60
8562.0	.0	8562.0	.0	.0	571.1	.0	90.7	11.1	2024.60
.13	.00	14.99	.00	.000	.015	.000	.000	2017.10	1000.00
.001640	50.	50.	50.	3	15	0	.00	60.00	1060.00

CCHV= .100 CEHV= .300

*SECNO 14550.000

3280 CROSS SECTION 14550.00 EXTENDED 1.08 FEET

3301 HV CHANGED MORE THAN HVINS

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

14550.000	8.55	2026.48	2026.48	.00	2030.80	4.32	.08	.25	2025.40
8562.0	.0	8562.0	.0	.0	513.3	.0	91.2	11.2	2025.40
.13	.00	16.68	.00	.000	.015	.000	.000	2017.93	1000.00
.002263	40.	40.	40.	0	11	0	.00	60.06	1060.06

CCHV= .100 CEHV= .300

*SECNO 14600.000

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

DOWNSTREAM FACE OF WARM SPRINGS ROAD BRIDGE

1

16JUN04 14:17:54

PAGE 32

SECNO	DEPTH	CWSEL	CRWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
14600.000	8.56	2026.93	2026.93	.00	2031.25	4.31	.05	.00	2030.20
8562.0	.0	8562.0	.0	.0	513.7	.0	91.4	11.2	2030.20
.13	.00	16.67	.00	.000	.015	.000	.000	2018.37	1390.42
.002258	20.	20.	20.	0	5	0	.00	60.00	1450.42

SPECIAL BRIDGE

5227 DOWNSTREAM ELEV IS 2025.77 , NOT 2026.93 HYDRAULIC JUMP OCCURS DOWNSTREAM (IF LOW FLOW CONTROLS)

SB	XK	XKOR	COFQ	RDLEN	BWC	BWF	BAREA	SS	ELCHU	ELCHD
1.25	1.50	3.00	103.00	60.00	2.13	588.00	.00	2018.71	2018.37	

CCHV= .100 CEHV= .300

*SECNO 14700.000

3280 CROSS SECTION 14700.00 EXTENDED 1.43 FEET

3301 HV CHANGED MORE THAN HVINS

CLASS B LOW FLOW

3420 BRIDGE W.S.= 2027.33 BRIDGE VELOCITY= 16.82 CALCULATED CHANNEL AREA= 499.

EGPRS	EGLWC	H3	QWEIR	QLOW	BAREA	TRAPEZOID	ELLC	ELTRD	WEIRLN
.00	2032.39	.00	0.	8562.	588.	AREA	1156.	2038.69	2040.21
									0.

BEGIN CHANGES FOR LONGFORD HOMES CLOMP

UPSTREAM FACE OF WARM SPRINGS ROAD BRIDGE

PLANS STA 9+39.84

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

14700.000	10.46	2029.33	.00	.00	2032.39	3.06	1.15	.00	2027.90
8562.0	.0	8562.0	.0	.0	609.7	.0	92.9	11.3	2029.88
.13	.00	14.04	.00	.000	.015	.000	.000	2018.87	1000.00
.001334	112.	112.	112.	0	0	0	.00	60.00	1060.00

CCHV= .100 CEHV= .300

*SECNO 14750.000

3280 CROSS SECTION 14750.00 EXTENDED .38 FEET

1

16JUN04 14:17:54

PAGE 33

SECNO	DEPTH	CWSEL	CRWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3301 HV CHANGED MORE THAN HVINS

PT
PLANS STA 8+83.50
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
14750.000 9.38 2028.88 2028.38 .00 2032.71 3.84 .09 .23 2028.50
8562.0 .0 8562.0 .0 .0 544.8 .0 93.6 11.4 2030.51
.13 .00 15.72 .00 .000 .015 .000 .000 2019.50 1000.00
.001871 56. 56. 56. 3 11 0 .00 60.00 1060.00

CCHV= .100 CEHV= .300

*SECNO 14800.000

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

BEGIN RECTANGULAR CHANNEL BOTTOM TRANSITION

PLANS STA 7+84.00

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
14800.000 8.41 2029.01 2029.01 .00 2033.11 4.10 .20 .08 2029.60
8562.0 .0 8562.0 .0 .0 526.9 .0 94.9 11.6 2031.61
.13 .00 16.25 .00 .000 .015 .000 .000 2020.60 1000.00
.002202 100. 100. 100. 0 11 0 .00 65.00 1065.00

CCHV= .100 CEHV= .300

*SECNO 14850.000

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

FVI

PLANS STA 6+81.44

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
14850.000 8.42 2030.16 2030.16 .00 2034.25 4.09 .23 .00 2030.80
8562.0 .0 8562.0 .0 .0 527.5 .0 96.1 11.7 2032.75
.14 .00 16.23 .00 .000 .015 .000 .000 2021.74 1000.00
.002194 103. 103. 103. 0 5 0 .00 65.00 1065.00

CCHV= .100 CEHV= .300

*SECNO 14900.000

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

BRIDGE AT TOFAZ STREET

1

16JUN04 14:17:54

PAGE 34

PLANS STA 6+44.08
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
14900.000 8.41 2030.42 2030.42 .00 2034.52 4.09 .08 .00 2031.00
8562.0 .0 8562.0 .0 .0 527.2 .0 96.5 11.8 2033.02
.14 .00 16.24 .00 .000 .015 .000 .000 2022.01 1000.00
.002197 37. 37. 37. 0 5 0 .00 65.00 1065.00

SPECIAL BRIDGE

5227 DOWNSTREAM ELEV IS 2029.21 , NOT 2030.42 HYDRAULIC JUMP OCCURS DOWNSTREAM (IF LOW FLOW CONTROLS)

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	.90	1.50	3.00	90.00	65.00	1.50	455.00	.00	2022.40	2022.01

CCHV= .100 CEHV= .300

*SECNO 14950.000

3280 CROSS SECTION 14950.00 EXTENDED 1.09 FEET

3301 HV CHANGED MORE THAN HVINS

CLASS B LOW FLOW

3420 BRIDGE W.S.= 2030.47 BRIDGE VELOCITY= 16.32 CALCULATED CHANNEL AREA= 512.

EGPRS	EGLWC	H3	QWEIR	QLOW	BAREA	TRAPEZOID AREA	ELLC	ELTRD	WEIRLN
.00	2035.15	.00	0.	8562.	455.	1118.	2040.00	2042.00	0.

BRIDGE AT TOFAZ STREET -- RIGHT WALL HEIGHT ADJUSTED

PLANS STA 5+91.39

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
14950.000 9.69 2032.09 .00 .00 2035.15 3.06 .63 .00 2031.00
8562.0 .0 8562.0 .0 .0 610.3 .0 97.2 11.8 2031.00
.14 .00 14.03 .00 .000 .015 .000 .000 2022.40 1000.00
.001407 53. 53. 53. 0 0 0 .00 65.00 1065.00

CCHV= .100 CEHV= .300

*SECNO 15000.000

3280 CROSS SECTION 15000.00 EXTENDED .31 FEET

3301 HV CHANGED MORE THAN HVINS

PVI
PLANS STA 5+28.97
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

1

16JUN04 14:17:54

PAGE 35

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
15000.000	8.91	2031.82	2031.32	.00	2035.45	3.63	.14	.17	2031.51
8562.0	.0	8562.0	.0	.0	559.7	.0	98.4	12.0	2031.51
.14	.00	15.30	.00	.000	.015	.000	.000	2022.91	1000.00
.001831	85.	85.	85.	3	11	0	.00	65.00	1065.00

CCHV= .100 CEHV= .300

*SECNO 15050.000

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

PC

PLANS STA 4+44.34

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

15050.000	8.44	2031.73	2031.73	.00	2035.80	4.07	.12	.13	2031.89
8562.0	.0	8562.0	.0	.0	529.2	.0	99.2	12.1	2031.89
.14	.00	16.18	.00	.000	.015	.000	.000	2023.29	1000.00
.002173	62.	62.	62.	0	8	0	.00	65.00	1065.00

CCHV= .100 CEHV= .300

*SECNO 15100.000

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

PVI

PLANS STA 3+28.97

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

15100.000	8.41	2032.39	2032.39	.00	2036.49	4.10	.25	.01	2032.58
8562.0	.0	8562.0	.0	.0	527.0	.0	100.6	12.2	2032.58
.14	.00	16.25	.00	.000	.015	.000	.000	2023.98	1000.00
.002200	115.	115.	115.	0	5	0	.00	65.00	1065.00

CCHV= .100 CEHV= .300

*SECNO 15110.000

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

PT

PLANS STA 3+25.54

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

15110.000	8.41	2032.43	2032.43	.00	2036.53	4.09	.01	.00	2033.02
8562.0	.0	8562.0	.0	.0	527.4	.0	100.6	12.2	2033.02
.14	.00	16.24	.00	.000	.015	.000	.000	2024.02	1000.00
.002196	3.	3.	3.	0	5	0	.00	65.00	1065.00

1

16JUN04 14:17:54

PAGE 36

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

CCHV= .100 CEHV= .300

*SECNO 15150.000

3301 HV CHANGED MORE THAN HVINS

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 1.70

BEGIN TRANSITION FROM TRAPEZOIDAL TO RECTANGULAR CHANNEL

PLANS STA 1+25.54

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

15150.000	9.97	2035.21	2033.09	.00	2037.00	1.79	.24	.23	2036.00
8562.0	.0	8562.0	.0	.0	797.9	.0	103.6	12.6	2036.00
.15	.00	10.73	.00	.000	.015	.000	.000	2025.24	1000.00
.000759	200.	200.	200.	5	11	0	.00	95.00	1095.00

CCHV= .100 CEHV= .300

*SECNO 15200.000

PLANS STA 0+12.31

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM									
15200.000	9.04	2034.98	2033.80	.00	2037.24	2.26	.10	.14	2037.00
8562.0	.0	8562.0	.0	.0	710.1	.0	105.6	12.9	2037.00
.15	.00	12.06	.00	.000	.015	.000	.000	2025.94	1000.00
.001092	113.	113.	113.	2	15	0	.00	95.00	1095.00

CCHV= .100 CEHV= .300
 *SECNO 15250.000

3301 HV CHANGED MORE THAN HVINS

PC PLANS STA -0+49.25 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM									
15250.000	8.09	2034.42	2034.36	.00	2037.60	3.19	.09	.28	2037.00
8562.0	.0	8562.0	.0	.0	597.7	.0	106.5	13.0	2037.00
.15	.00	14.32	.00	.000	.015	.000	.000	2026.33	1000.01
.001820	62.	62.	62.	3	11	0	.00	92.25	1092.26

1

16JUN04 14:17:54

PAGE 37

SECNO	DEPTH	CWSEL	CRWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

CCHV= .100 CEHV= .300
 *SECNO 15300.000

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

BEGIN CHANNEL IMPROVEMENTS/BEGIN TRAP CHANNEL BOTTOM TRANSITION

PLANS STA -1+00

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

END OF REVISIONS FOR LONGFORD HOMES CLOMR

15300.000	8.19	2034.83	2034.83	.00	2038.11	3.28	.09	.03	2037.00
8562.0	.0	8562.0	.0	.0	588.7	.0	107.2	13.1	2037.00
.15	.00	14.54	.00	.000	.015	.000	.000	2026.64	1000.00
.001860	51.	51.	51.	0	5	0	.00	90.00	1090.00

CCHV= .100 CEHV= .300
 *SECNO 15400.000

3301 HV CHANGED MORE THAN HVINS

15400.000	8.86	2036.36	2035.11	.00	2038.88	2.51	.69	.08	2040.00
8562.0	.0	8562.0	.0	.0	673.3	.0	114.0	14.0	2040.00
.16	.00	12.72	.00	.000	.015	.000	.000	2027.50	1211.64
.001169	440.	471.	434.	4	11	0	.00	84.88	1296.52

CCHV= .100 CEHV= .300
 *SECNO 15500.000

3301 HV CHANGED MORE THAN HVINS

7185 MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

DOWNSTREAM FACE OF EASTERN AVENUE BRIDGE

START OF MODEL

ORIGINAL MODEL: DCL1SUFC.DAT

ESTABLISHED WATER SURFACE ELEVATION = 2037.8 FT (SUBCRITICAL CONDITIONS)

15500.000	8.86	2037.11	2037.11	.00	2041.57	4.47	.26	.59	2039.50
8562.0	.0	8562.0	.0	.0	504.9	.0	116.3	14.3	2039.50
.16	.00	16.96	.00	.000	.015	.000	.000	2028.25	1642.82
.002293	214.	166.	136.	0	5	0	.00	57.00	1699.82

1

16JUN04 14:17:54

PAGE 38

THIS RUN EXECUTED 16JUN04 14:17:54

HEC-2 WATER SURFACE PROFILES

Version 4.6.2; May 1991

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

DCL1SUBX

SUMMARY PRINTOUT TABLE 100

	SECNO	EGLWC	ELLC	EGPRS	ELTRD	QPR	QWEIR	CLASS	H3	DEPTH	CWSEL	VCH	EG
*	11500.000	1980.85	1990.52	.00	1972.82	8562.00	.00	59.00	.00	10.85	1975.37	18.79	1980.85
*	11700.000	1987.88	1996.89	.00	1999.84	8562.00	.00	2.00	.00	15.75	1984.00	15.80	1987.88
•	12000.000	1989.65	1998.54	.00	1990.99	8562.00	.00	59.00	.00	12.42	1983.39	20.08	1989.65
*	12400.000	1995.67	2009.42	.00	2012.00	8562.00	.00	2.00	.00	9.78	1992.89	13.39	1995.67
*	13000.000	2008.44	2020.90	.00	2004.20	8562.00	.00	59.00	.00	9.66	2003.56	17.73	2008.44
	13500.000	2016.74	2030.07	.00	2012.33	8562.00	.00	59.00	.00	11.56	2014.63	10.96	2016.50
*	14000.000	2025.43	2039.39	.00	2021.13	8562.00	.00	59.00	.00	9.66	2020.55	17.73	2025.43
*	14400.000	2029.69	2030.00	.00	2031.20	8562.00	.00	2.00	.00	11.51	2027.31	12.40	2029.69
•	14700.000	2032.39	2038.69	.00	2040.21	8562.00	.00	2.00	.00	10.46	2029.33	14.04	2032.39
*	14950.000	2035.15	2040.00	.00	2042.00	8562.00	.00	2.00	.00	9.69	2032.09	14.03	2035.15

1

16JUN04 14:17:54

PAGE 39

DCLISUBX

SUMMARY PRINTOUT TABLE 101

	SECNO	EGOC	ELLC	EGIC	ELTRD	QCULV	QWEIR	CLASS	H4	DEPTH	CWSEL	VCH	EG
1	16JUN04	14:17:54											

PAGE 40

DCLISUBX

SUMMARY PRINTOUT TABLE 150

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRWS	EG	10*KS	VCH	AREA	.01K
*	10600.000	.00	.00	.00	1942.00	8562.00	1952.43	1952.43	1955.75	19.45	14.62	585.58	1941.44
*	10700.000	418.08	.00	.00	1948.00	8562.00	1957.49	1957.49	1960.54	19.69	14.02	610.77	1929.65
*	10800.000	386.03	.00	.00	1952.00	8562.00	1961.34	1961.34	1964.35	19.49	13.91	615.38	1939.36
*	10900.000	388.50	.00	.00	1956.00	8562.00	1965.63	1965.63	1969.12	19.23	14.99	573.56	1952.59
*	11000.000	392.70	.00	.00	1960.00	8562.00	1969.76	1969.76	1973.01	18.54	14.46	597.79	1988.70
*	11100.000	411.30	.00	.00	1960.00	8562.00	1971.56	1971.56	1975.05	18.73	14.98	571.39	1978.49
*	11200.000	430.53	.00	.00	1962.00	8562.00	1972.81	1972.81	1976.96	19.43	16.34	523.90	1942.62
*	11300.000	474.00	.00	.00	1964.00	8562.00	1974.51	1974.51	1978.74	19.35	16.52	518.41	1946.57
•	11400.000	243.55	.00	.00	1964.02	8562.00	1974.87	1974.87	1980.35	26.11	18.79	455.61	1675.71
*	11500.000	100.00	1972.82	1990.52	1964.52	8562.00	1975.37	1975.37	1980.85	26.10	18.79	455.62	1675.77
•	11600.000	215.00	.00	.00	1967.32	8562.00	1979.74	1979.74	1985.98	29.33	20.03	427.41	1580.89
*	11700.000	16.00	1999.84	1996.89	1968.25	8562.00	1984.00	.00	1987.88	15.33	15.80	541.89	2187.08
	11800.000	86.00	.00	.00	1969.57	8562.00	1983.31	1981.96	1988.40	22.24	18.12	472.55	1815.65
*	11900.000	92.00	.00	.00	1970.88	8562.00	1983.30	1983.30	1989.57	29.61	20.11	425.84	1573.35
*	12000.000	5.00	1990.99	1998.54	1970.97	8562.00	1983.39	1983.39	1989.65	29.50	20.08	426.49	1576.50
*	12100.000	252.00	.00	.00	1974.60	8562.00	1985.66	1985.66	1991.25	26.52	18.97	451.23	1662.49
*	12200.000	287.98	.00	.00	1978.83	8562.00	1989.18	1989.18	1994.41	25.18	18.35	466.54	1706.26
	12300.000	277.73	.00	.00	1982.84	8562.00	1991.74	1991.34	1995.15	16.47	14.81	578.08	2109.80
*	12400.000	75.37	2012.00	2009.42	1983.11	8562.00	1992.89	.00	1995.67	11.99	13.39	639.57	2473.11
	12500.000	88.60	.00	.00	1983.70	8562.00	1992.57	1992.28	1995.98	16.78	14.82	577.61	2089.96
*	12600.000	75.00	.00	.00	1985.63	8562.00	1995.29	1995.29	2000.17	24.03	17.72	483.15	1746.46
*	12700.000	313.04	.00	.00	1988.15	8562.00	1997.82	1997.82	2002.69	24.01	17.72	483.32	1747.38
*	12800.000	405.00	.00	.00	1991.35	8562.00	2001.02	2001.02	2005.89	24.02	17.72	483.27	1747.12

*	12900.000	258.77	.00	.00	1993.47	8562.00	2003.14	2003.14	2008.01	24.02	17.72	483.27	1747.12
---	-----------	--------	-----	-----	---------	---------	---------	---------	---------	-------	-------	--------	---------

1

16JUN04	14:17:54
---------	----------

PAGE 41

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10*KS	VCH	AREA	.01K
•	13000.000	33.00	2004.20	2020.90	1993.90	8562.00	2003.56	2003.56	2008.44	24.07	17.73	482.90	1745.12
*	13100.000	98.00	.00	.00	1998.99	8562.00	2008.66	2008.66	2013.53	24.00	17.71	483.39	1747.74
*	13200.000	211.13	.00	.00	2001.40	8562.00	2011.07	2011.07	2015.94	24.01	17.72	483.31	1747.34
*	13300.000	80.00	.00	.00	2002.29	8562.00	2014.76	2010.83	2016.34	4.78	10.10	847.38	3915.82
	13400.000	100.00	.00	.00	2002.77	8562.00	2014.70	2011.30	2016.44	6.00	10.60	808.07	3495.24
	13500.000	36.00	2012.33	2030.07	2003.07	8562.00	2014.63	2011.59	2016.50	6.19	10.96	780.94	3442.12
*	13600.000	88.14	.00	.00	2006.11	8562.00	2014.66	2014.66	2018.37	19.03	15.47	553.50	1962.54
•	13700.000	75.00	.00	.00	2006.56	8562.00	2016.24	2016.24	2021.10	23.93	17.70	483.86	1750.29
*	13800.000	306.00	.00	.00	2008.40	8562.00	2018.06	2018.06	2022.94	24.03	17.72	483.15	1746.46
*	13900.000	300.00	.00	.00	2010.21	8562.00	2019.88	2019.88	2024.75	24.01	17.72	483.32	1747.38
*	14000.000	57.00	2021.13	2039.39	2010.89	8562.00	2020.55	2020.55	2025.43	24.05	17.73	483.03	1745.81
*	14100.000	101.00	.00	.00	2012.82	8562.00	2022.92	2022.92	2026.71	21.72	15.62	548.29	1837.05
*	14200.000	75.00	.00	.00	2014.24	8562.00	2022.81	2022.81	2027.12	22.48	16.64	514.45	1805.67
*	14220.000	20.00	.00	.00	2014.62	8562.00	2023.18	2023.18	2027.50	22.62	16.68	513.41	1800.16
*	14240.000	20.00	.00	.00	2015.00	8562.00	2023.56	2023.56	2027.88	22.60	16.67	513.59	1801.10
*	14300.000	20.00	.00	.00	2015.30	8562.00	2023.86	2023.86	2028.18	22.60	16.67	513.59	1801.10
•	14400.000	20.00	2031.20	2030.00	2015.80	8562.00	2027.31	.00	2029.69	9.30	12.40	690.39	2807.70
	14450.000	20.00	.00	.00	2016.13	8562.00	2027.19	2024.69	2029.77	9.86	12.90	663.46	2726.02
	14500.000	50.00	.00	.00	2017.10	8562.00	2026.62	2025.65	2030.11	16.40	14.99	571.05	2114.49
*	14550.000	40.00	.00	.00	2017.93	8562.00	2026.48	2026.48	2030.80	22.63	16.68	513.32	1799.82
*	14600.000	20.00	.00	.00	2018.37	8562.00	2026.93	2026.93	2031.25	22.58	16.67	513.71	1801.72
*	14700.000	111.98	2040.21	2038.69	2018.87	8562.00	2029.33	.00	2032.39	13.34	14.04	609.67	2344.34
	14750.000	56.34	.00	.00	2019.50	8562.00	2028.88	2028.38	2032.71	18.71	15.72	544.80	1979.47
*	14800.000	99.50	.00	.00	2020.60	8562.00	2029.01	2029.01	2033.11	22.02	16.25	526.90	1824.71
*	14850.000	102.56	.00	.00	2021.74	8562.00	2030.16	2030.16	2034.25	21.94	16.23	527.49	1827.82
*	14900.000	37.36	.00	.00	2022.01	8562.00	2030.42	2030.42	2034.52	21.97	16.24	527.24	1826.52

1

16JUN04	14:17:54
---------	----------

PAGE 42

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10*KS	VCH	AREA	.01K
*	14950.000	52.69	2042.00	2040.00	2022.40	8562.00	2032.09	.00	2035.15	14.07	14.03	610.28	2282.74
	15000.000	84.63	.00	.00	2022.91	8562.00	2031.82	2031.32	2035.45	18.31	15.30	559.68	2001.18
*	15050.000	62.42	.00	.00	2023.29	8562.00	2031.73	2031.73	2035.80	21.73	16.18	529.16	1836.72
*	15100.000	115.37	.00	.00	2023.98	8562.00	2032.39	2032.39	2036.49	22.00	16.25	527.02	1825.34
*	15110.000	3.43	.00	.00	2024.02	8562.00	2032.43	2032.43	2036.53	21.96	16.24	527.36	1827.15
*	15150.000	200.00	.00	.00	2025.24	8562.00	2035.21	2033.09	2037.00	7.59	10.73	797.92	3108.66
	15200.000	113.23	.00	.00	2025.94	8562.00	2034.98	2033.80	2037.24	10.92	12.06	710.11	2590.93
	15250.000	61.56	.00	.00	2026.33	8562.00	2034.42	2034.36	2037.60	18.20	14.32	597.73	2006.90
*	15300.000	50.75	.00	.00	2026.64	8562.00	2034.83	2034.83	2038.11	18.60	14.54	588.68	1985.03
	15400.000	471.40	.00	.00	2027.50	8562.00	2036.36	2035.11	2038.88	11.69	12.72	673.28	2504.35
*	15500.000	166.19	.00	.00	2028.25	8562.00	2037.11	2037.11	2041.57	22.93	16.96	504.88	1787.85

1

16JUN04	14:17:54
---------	----------

PAGE 43

DCL1SUBX

SUMMARY PRINTOUT TABLE 150

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
*	10600.000	8562.00	1952.43	.00	.00	3.13	89.43	.00
*	10700.000	8562.00	1957.49	.00	5.07	.00	102.48	418.08
*	10800.000	8562.00	1961.34	.00	3.85	.00	103.33	386.03
•	10900.000	8562.00	1965.63	.00	4.29	.00	86.46	388.50
*	11000.000	8562.00	1969.76	.00	4.13	.00	97.92	392.70
*	11100.000	8562.00	1971.56	.00	1.80	.00	81.81	411.30
*	11200.000	8562.00	1972.81	.00	1.25	.00	64.44	430.53
*	11300.000	8562.00	1974.51	.00	1.69	.00	61.43	474.00
*	11400.000	8562.00	1974.87	.00	.36	.00	42.00	243.55
*	11500.000	8562.00	1975.37	.00	.50	.00	42.00	100.00
*	11600.000	8562.00	1979.74	.00	4.38	.00	34.40	215.00
•	11700.000	8562.00	1984.00	.00	4.26	.00	34.40	16.00
	11800.000	8562.00	1983.31	.00	-.70	.00	34.40	86.00
*	11900.000	8562.00	1983.30	.00	-.01	.00	34.30	92.00
*	12000.000	8562.00	1983.39	.00	.09	.00	34.34	5.00
*	12100.000	8562.00	1985.66	.00	2.27	.00	40.80	252.00
•	12200.000	8562.00	1989.18	.00	3.52	.00	45.08	287.98
	12300.000	8562.00	1991.74	.00	2.57	.00	73.69	277.73
*	12400.000	8562.00	1992.89	.00	1.14	.00	72.72	75.37
	12500.000	8562.00	1992.57	.00	-.32	.00	75.87	88.60
•	12600.000	8562.00	1995.29	.00	2.72	.00	50.00	75.00
*	12700.000	8562.00	1997.82	.00	2.52	.00	50.00	313.04
•	12800.000	8562.00	2001.02	.00	3.20	.00	50.00	405.00
*	12900.000	8562.00	2003.14	.00	2.12	.00	50.00	258.77
1	16JUN04	14:17:54						

PAGE 44

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
*	13000.000	8562.00	2003.56	.00	.42	.00	50.00	33.00
*	13100.000	8562.00	2008.66	.00	5.10	.00	50.00	98.00
*	13200.000	8562.00	2011.07	.00	2.41	.00	50.00	211.13
*	13300.000	8562.00	2014.76	.00	3.69	.00	75.00	80.00
	13400.000	8562.00	2014.70	.00	-.06	.00	75.00	100.00
	13500.000	8562.00	2014.63	.00	-.06	.00	75.00	36.00
*	13600.000	8562.00	2014.66	.00	.02	.00	75.00	88.14
*	13700.000	8562.00	2016.24	.00	1.58	.00	50.00	75.00
*	13800.000	8562.00	2018.06	.00	1.83	.00	50.00	306.00
*	13900.000	8562.00	2019.88	.00	1.81	.00	50.00	300.00
*	14000.000	8562.00	2020.55	.00	.67	.00	50.00	57.00
*	14100.000	8562.00	2022.92	.00	2.37	.00	73.20	101.00
*	14200.000	8562.00	2022.81	.00	-.10	.00	60.00	75.00
*	14220.000	8562.00	2023.18	.00	.36	.00	60.00	20.00
*	14240.000	8562.00	2023.56	.00	.38	.00	60.00	20.00

*	14300.000	8562.00	2023.86	.00	.30	.00	60.00	20.00
*	14400.000	8562.00	2027.31	.00	3.45	.00	60.00	20.00
	14450.000	8562.00	2027.19	.00	-.12	.00	60.00	20.00
	14500.000	8562.00	2026.62	.00	-.57	.00	60.00	50.00
*	14550.000	8562.00	2026.48	.00	-.14	.00	60.06	40.00
*	14600.000	8562.00	2026.93	.00	.45	.00	60.00	20.00
*	14700.000	8562.00	2029.33	.00	2.40	.00	60.00	111.98
	14750.000	8562.00	2028.88	.00	-.45	.00	60.00	56.34
•	14800.000	8562.00	2029.01	.00	.13	.00	65.00	99.50
*	14850.000	8562.00	2030.16	.00	1.15	.00	65.00	102.56
*	14900.000	8562.00	2030.42	.00	.27	.00	65.00	37.36

1

16JUN04 14:17:54

PAGE 45

	SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
*	14950.000	8562.00	2032.09	.00	1.67	.00	65.00	52.69
	15000.000	8562.00	2031.82	.00	-.27	.00	65.00	84.63
*	15050.000	8562.00	2031.73	.00	-.09	.00	65.00	62.42
*	15100.000	8562.00	2032.39	.00	.66	.00	65.00	115.37
*	15110.000	8562.00	2032.43	.00	.05	.00	65.00	3.43
*	15150.000	8562.00	2035.21	.00	2.78	.00	95.00	200.00
	15200.000	8562.00	2034.98	.00	-.23	.00	95.00	113.23
	15250.000	8562.00	2034.42	.00	-.56	.00	92.25	61.56
*	15300.000	8562.00	2034.83	.00	.41	.00	90.00	50.75
	15400.000	8562.00	2036.36	.00	1.54	.00	84.88	471.40
•	15500.000	8562.00	2037.11	.00	.74	.00	57.00	166.19

1

16JUN04 14:17:54

PAGE 46

SUMMARY OF ERRORS AND SPECIAL NOTES

CAUTION SECNO=	10600.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	10700.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	10700.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	10800.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	10800.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	10900.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	10900.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	11000.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	11000.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	11100.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	11100.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	11200.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	11200.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	11300.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	11300.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	11400.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	11400.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	11500.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	11500.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	11600.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	11600.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	11700.000	PROFILE=	1	HYDRAULIC JUMP D.S.

CAUTION SECNO=	11900.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	11900.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	12000.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	12000.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	12100.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	12100.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	12200.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	12200.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	12400.000	PROFILE=	1	HYDRAULIC JUMP D.S.
CAUTION SECNO=	12600.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	12600.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY

1

16JUN04 14:17:54

PAGE 47

CAUTION SECNO=	12700.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	12700.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	12800.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	12800.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	12900.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	12900.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	13000.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	13000.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	13100.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	13100.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	13200.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	13200.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
WARNING SECNO=	13300.000	PROFILE=	1	CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
CAUTION SECNO=	13600.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	13600.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	13700.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	13700.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	13800.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	13800.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	13900.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	13900.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	14000.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	14000.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	14100.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	14100.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	14200.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	14200.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	14220.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	14220.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	14240.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	14240.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	14300.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	14300.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	14400.000	PROFILE=	1	HYDRAULIC JUMP D.S.
WARNING SECNO=	14400.000	PROFILE=	1	CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
CAUTION SECNO=	14550.000	PROFILE=	1	CRITICAL DEPTH ASSUMED

1

16JUN04 14:17:54

PAGE 48

CAUTION SECNO=	14550.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	14600.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	14600.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	14700.000	PROFILE=	1	HYDRAULIC JUMP D.S.
CAUTION SECNO=	14800.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	14800.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	14850.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	14850.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY

CAUTION SECNO=	14900.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	14900.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	14950.000	PROFILE=	1	HYDRAULIC JUMP D.S.
CAUTION SECNO=	15050.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	15050.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	15100.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	15100.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	15110.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	15110.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
WARNING SECNO=	15150.000	PROFILE=	1	CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE
CAUTION SECNO=	15300.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	15300.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY
CAUTION SECNO=	15500.000	PROFILE=	1	CRITICAL DEPTH ASSUMED
CAUTION SECNO=	15500.000	PROFILE=	1	MINIMUM SPECIFIC ENERGY

HEC-2 Model for Supercritical Conditions

DCL1SPRX.dat

```

1*****
*   HEC-2 WATER SURFACE PROFILES   *
*   *                               *
*   Version   4.6.2; May 1991      *
*   *                               *
*   RUN DATE   16JUN04   TIME   14:15:51 *
*****

```

```

*****
*   U.S. ARMY CORPS OF ENGINEERS   *
*   HYDROLOGIC ENGINEERING CENTER  *
*   609 SECOND STREET, SUITE D     *
*   DAVIS, CALIFORNIA 95616-4687   *
*   (916) 756-1104                 *
*****

```

```

X   X   XXXXXXXX   XXXXX   XXXXX
X   X   X           X   X   X   X
X   X   X           X           X
XXXXXXXX XXXX   X   XXXXX   XXXXX
X   X   X           X           X
X   X   X           X   X   X
X   X   XXXXXXXX   XXXXX   XXXXXXXX

```

```

1
16JUN04   14:15:51

```

PAGE 1

THIS RUN EXECUTED 16JUN04 14:15:51

```

*****
HEC-2 WATER SURFACE PROFILES
Version   4.6.2; May 1991
*****

```

```

T1   758.002 PHASE 209
T2   CLOMR FOR LONGFORD HOMES
T3   DCL1SUPX
T4   HEC-2 MODEL FROM DUCK CREEK/BLUE DIAMOND FIS RESTUDY: DCL1SUPC.DAT
T4   FLOODPLAIN/FLOODWAY MODEL; BREAKOUT AT WARM SPRINGS RD CONTAINED
T4   SUPERCRITICAL
T4   STREAM NAME: DUCK CREEK
T4   UPSTREAM LIMIT: CROSS SECTION 15400, DOWNSTREAM OF EASTERN AVE
T4   DOWNSTREAM LIMIT: CROSS SECTION 10900

```

J1	ICHECK	INQ	NINV	IDIR	STRT	METRIC	HVINS	Q	WSEL	FQ
		0		1				8562	2037.8	
J2	NPROF	IPLOT	PREVS	XSECV	XSECH	FN	ALLDC	IBW	CHNIM	ITRACE
	1		-1					-1	-6	0

J3 VARIABLE CODES FOR SUMMARY PRINTOUT

```

1
100   101   150   200
16JUN04   14:15:51

```

PAGE 2

NC	0.08	0.11	0.015	0.1	0.3
DOWNSTREAM FACE OF EASTERN AVENUE BRIDGE					
X1	15500	6	1642.82	1699.82	214.02
GR	2040	1400.58	2039.5	1642.82	2028.25
GR	2044	1982.77			
NC	0.08	0.11	0.015	0.1	0.3

X1	15400	8	1203.85	1302.87	439.74	434.2	471.4			
GR	2040	1000	2040	1203.85	2036	1212.42	2027.5	1221.41	2027.5	1289.16
GR	2036	1295.88	2040	1302.87	2044	1611.48				
BEGIN CHANNEL IMPROVEMENTS/BEGIN TRAP CHANNEL BOTTOM TRANSITION										
PLANS STA -1+00										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
LIMIT OF REVISIONS FOR LONGFORD HOMES CLOMR										
NC	0.015	0.015	0.015	0.1	0.3					
X1	15300	7	1000	1090	50.75	50.75	50.75			
GR	2037	1000	2034.74	1000	2027.24	1015	2026.64	1045	2027.24	1075
GR	2034.7	1090	2037	1090						
PC										
PLANS STA -0+49.25										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
NC	0.015	0.015	0.015	0.1	0.3					
X1	15250	7	1000	1092.26	61.56	61.56	61.56			
GR	2037	1000	2034.43	1000	2026.93	1015	2026.33	1047.26	2026.93	1077.26
GR	2034.4	1092.26	2037	1092.26						
PLANS STA 0+12.31										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
NC	0.015	0.015	0.015	0.1	0.3					
X1	15200	7	1000	1095	113.23	113.23	113.23			
GR	2037	1000	2034.04	1000	2026.54	1015	2025.94	1050	2026.54	1080
GR	2034.0	1095	2037	1095						
BEGIN TRANSITION FROM TRAPEZOIDAL TO RECTANGULAR CHANNEL										
PLANS STA 1+25.54										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
NC	0.015	0.015	0.015	0.1	0.3					
X1	15150	7	1000	1095	200	200	200			
GR	2036	1000	2033.34	1000	2025.84	1015	2025.24	1050	2025.84	1080
GR	2033.3	1095	2036	1095						
FT										
PLANS STA 3+25.54										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
NC	0.015	0.015	0.015	0.1	0.3					
X1	15110	7	1000	1065	3.43	3.43	3.43	0	0.02	
GR	2033	1000	2032.02	1000	2024.6	1000	2024	1035	2024.6	1065
GR	2032.0	1065	2033	1065						
PVI										
PLANS STA 3+28.97										
16JUN04 14:15:51										
PAGE 3										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
NC	0.015	0.015	0.015	0.1	0.3					
X1	15100	0	0	0	115.37	115.37	115.37	0	-0.02	
PC										
PLANS STA 4+44.34										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
NC	0.015	0.015	0.015	0.1	0.3					
X1	15050	0	0	0	62.42	62.42	62.42	0	-0.69	
PVI										
PLANS STA 5+28.97										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
NC	0.015	0.015	0.015	0.1	0.3					
X1	15000	0	0	0	84.63	84.63	84.63	0	-0.51	
BRIDGE AT TOPAZ STREET -- RIGHT WALL HEIGHT ADJUSTED										
PLANS STA 5+91.39										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
NC	0.015	0.015	0.015	0.1	0.3					
X1	14950	7	1000	1065	52.69	52.69	52.69			
GR	2031	1000	2030.42	1000	2023	1000	2022.4	1035	2023	1065
GR	2030.4	1065	2031	1065						
SB	0.90	1.5	3	90	65	1.5	455	0	2022.40	2022.01
BRIDGE AT TOPAZ STREET										
PLANS STA 6+44.08										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
NC	0.015	0.015	0.015	0.1	0.3					
X1	14900	5	1000	1065	37.36	37.36	37.36			
X2			1	2040	2042			2		
GR	2031	1000	2022.61	1000	2022.01	1035	2022.61	1065	2033.02	1065
PVI										
PLANS STA 6+81.44										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
NC	0.015	0.015	0.015	0.1	0.3					
X1	14850	5	1000	1065	102.56	102.56	102.56			
GR	2030.8	1000	2022.34	1000	2021.74	1035	2022.34	1065	2032.75	1065
BEGIN RECTANGULAR CHANNEL BOTTOM TRANSITION										
PLANS STA 7+84.00										

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

NC	0.015	0.015	0.015	0.1	0.3					
X1	14800	5	1000	1065	99.5	99.5	99.5			
GR	2029.6	1000	2021.2	1000	2020.6	1035	2021.2	1065	2031.61	1065

PT

PLANS STA 8+83.50

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

1

16JUN04 14:15:51

PAGE 4

NC	0.015	0.015	0.015	0.1	0.3					
X1	14750	5	1000	1060	56.34	56.34	56.34			
GR	2028.5	1000	2020.1	1000	2019.5	1030	2020.1	1060	2030.51	1060

BEGIN CHANGES FOR LONGFORD HOMES CLOMR

UPSTREAM FACE OF WARM SPRINGS ROAD BRIDGE

PLANS STA 9+39.84

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

NC	0.015	0.015	0.015	0.1	0.3					
X1	14700	5	1000	1060	111.98	111.98	111.98			
GR	2027.9	1000	2019.47	1000	2018.87	1030	2019.47	1060	2029.88	1060

SB	1.25	1.5	3	103	60	2.13	588	0	2018.87	2018.37
NC	0.015	0.015	0.015	0.1	0.3					

DOWNSTREAM FACE OF WARM SPRINGS ROAD BRIDGE

X1	14600	4	1390.42	1450.42	20	20	20			
X2			1	2038.69	2040.21				2	
GR	2030.2	1390.42	2018.37	1390.42	2018.37	1450.42	2030.2	1450.42		
NC	0.015	0.015	0.015	0.1	0.3					

X1	14550	4	1000	1060.06	40	40	40			
GR	2025.4	1000	2017.93	1000	2017.93	1060	2025.4	1060.06		
NC	0.015	0.015	0.015	0.1	0.3					

1

16JUN04 14:15:51

PAGE 5

X1	14500	4	1000	1060	50	50	50			
GR	2024.6	1000	2017.1	1000	2017.1	1060	2024.6	1060		
NC	0.015	0.015	0.015	0.1	0.3					

X1	14450	4	1000	1060	20	20	20			
GR	2025.1	1000	2016.13	1000	2016.13	1060	2023.63	1060		

NC	0.015	0.015	0.015	0.1	0.3					
UPSTREAM FACE OF UPRR BRIDGE - HENDERSON SPUR										
X1	14400	4	1782	1842	20	20	20			
GR	2025.1	1782	2015.8	1782	2015.8	1842	2028.8	1842		
SB	1.25	1.5	3	17	60	4	452	0	2015.8	2015.3
DOWNSTREAM FACE OF UPRR BRIDGE - HENDERSON SPUR										
NC	0.015	0.015	0.015	0.1	0.3					
X1	14300	4	1701.5	1761.5	20	20	20			
X2			1	2030	2031.2			2		
GR	2028.8	1701.5	2015.3	1701.5	2015.3	1761.5	2028.8	1761.5		
NC	0.015	0.015	0.015	0.1	0.3					
X1	14240	4	1000	1060	20	20	20			
GR	2024.5	1000	2015	1000	2015	1060	2022.53	1060		
NC	0.015	0.015	0.015	0.1	0.3					
X1	14220	4	1000	1060	20	20	20			
GR	2024.1	1000	2014.62	1000	2014.62	1060	2022.13	1060		
NC	0.015	0.015	0.015	0.1	0.3					
TRANSITION UPSTREAM 60' RECT TO 50' RECT										
PLANS STA 12+67.00										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
X1	14200	4	1000	1060	75	75	75			
GR	2022.7	1000	2014.24	1000	2014.24	1060	2022.7	1060		

1

16JUN04 14:15:51

PAGE 6

NC	0.015	0.015	0.015	0.1	0.3					
TRANSITION DOWNSTREAM RECT										

PLANS STA 13+42.00

PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

X1	14100	8	1545.26	1624.79	101	101	101			
GR	2024	1545.26	2020	1556.5	2019.82	1559.32	2012.82	1559.32	2012.82	1609.32
GR	2019.8	1609.32	2020	1612.61	2024	1624.79				

NC	0.015	0.015	0.015	0.1	0.3					
GRADEBREAK NEAR UPSTREAM FACE OF VISTA DEL SOL AVENUE BRIDGE										
PLANS STA 14+43.43										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
X1	14000	4	1000	1050	57	57	57			
GR	2019.4	1000	2010.89	1000	2010.89	1050	2019.4	1050		
NC	0.015	0.015	0.015	0.1	0.3					
SB	1.5	3	50	50		425	0	2010.89	2010.21	
GRADEBREAK AT DOWNSTREAM FACE OF VISTA DEL SOL AVENUE										
PLANS STA 15+00.00										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
X1	13900	4	1000	1050	300	300	300			
X2			1	2039.39	2021.13					
GR	2019.4	1000	2010.21	1000	2010.21	1050	2019.4	1050		

NC	0.015	0.015	0.015	0.1	0.3					
PLANS STA 18+00.00										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										
X1	13800	4	1000	1050	306	306	306			
GR	2015.4	1000	2008.4	1000	2008.4	1050	2015.4	1050		
NC	0.015	0.015	0.015	0.1	0.3					
TRANSITION UPSTREAM RECT										
PLANS STA 21+06.00										
PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM										

1

16JUN04 14:15:51

PAGE 7

X1	13700	6	1000	1050	75	75	75			
GR	2014	1000	2013.5	1000	2006.56	1000	2006.56	1050	2013.5	1050
GR	2014	1050								

NC	0.015	0.015	0.015	0.1	0.3					
TRANSITION DOWNSTREAM TRAF										

PLANS STA 21+81.14
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 X1 13600 4 1395.5 1470.5 151.8 88.79 88.14
 GR 2013.1 1395.5 2006.11 1408 2006.11 1458 2013.1 1470.5

NC 0.015 0.015 0.015 0.1 0.3
 UPSTREAM FACE OF PACHUCA STREET BRIDGE
 PLANS STA 22+83.50
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 X1 13500 4 1409.5 1484.5 37.16 36.94 36
 GR 2010 1409.5 2003.07 1422 2003.07 1472 2010 1484.5

NC 0.015 0.015 0.015 0.1 0.3
 SB 1.5 3 75 50 438 1.8 2003.07 2002.77
 DOWNSTREAM FACE OF PACHUCA BRIDGE
 PLANS STA 23+16.50
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 X1 13400 4 2794.52 2869.52 100.24 100
 Y2 1 2030.07 2012.33
 GR 2009.7 2794.52 2002.77 2807.02 2002.77 2857.02 2009.7 2869.52

NC 0.015 0.015 0.015 0.1 0.3
 TRANSITION - UPSTREAM TRAP
 PLANS STA 24+12.75
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 X1 13300 4 997.5 1072.5 80 80 80
 GR 2009.3 997.5 2002.29 1010 2002.29 1060 2009.3 1072.5

NC 0.015 0.015 0.015 0.1 0.3
 TRANSITION - DOWNSTREAM RECT
 PLANS STA 24+90.00
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 X1 13200 4 995 1045 209.19 210.5 211.13
 GR 2008.5 995 2001.4 995 2001.4 1045 2008.5 1045

NC 0.015 0.015 0.015 0.1 0.3
 PLANS STA 27+00.00
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 X1 13100 6 994.85 1044.85 98 98 98
 GR 2006 994.85 2005 994.85 1998.99 994.85 1998.99 1044.85 2005 1044.85
 GR 2006 1044.85

NC 0.015 0.015 0.015 0.1 0.3
 UPSTREAM FACE OF MIRA VISTA STREET BRIDGE
 PLANS STA 28+10.59
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM

1 16JUN04 14:15:51

X1 13000 4 2587.74 2637.74 33 33 33
 GR 2004.2 2587.74 1993.9 2587.74 1993.9 2637.74 2004.2 2637.74

NC 0.015 0.015 0.015 0.1 0.3
 SB 1.5 3 50 50 350 0 1993.9 1993.47
 DOWNSTREAM FACE OF MIRA VISTA BRIDGE
 PLANS STA 28+43.76
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 X1 12900 4 2630.84 2680.84 260.12 257.73 258.77
 X2 1 2020.9 2004.2
 GR 2004.2 2630.84 1993.47 2630.84 1993.47 2680.84 2004.2 2680.84

NC 0.015 0.015 0.015 0.1 0.3
 PLANS STA 31+00.00
 PLANS ELEVATIONS ADJUSTED -2.27 FT TO NGVD 29 DATUM
 X1 12800 4 2505.21 2555.21 405 405 405
 GR 1998.3 2505.21 1991.35 2505.21 1991.35 2555.21 1998.3 2555.21

NC 0.015 0.015 0.015 0.1 0.3
 PLANS STA 35+00.00
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 X1 12700 4 2430.44 2480.44 317.32 309.52 313.04
 GR 1995.1 2430.44 1988.15 2430.44 1988.15 2480.44 1995.1 2480.44

NC 0.015 0.015 0.015 0.1 0.3
 TRANSITION UPSTREAM RECT
 PLANS STA 38+14.44
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 X1 12600 4 1000 1050 75 75 75
 GR 1993.6 1000 1985.63 1000 1985.63 1050 1993.6 1050

NC 0.015 0.015 0.015 0.1 0.3
 TRANSITION DOWNSTREAM TRAP
 PLANS STA 38+89.86
 PLANS ELEVATIONS ADJUSTED -2.37 FT TO NGVD 29 DATUM
 X1 12500 4 2495.63 2571.5 85.83 90.77 88.6
 GR 1991.1 2495.63 1983.7 2508.99 1983.7 2559.02 1991.1 2571.5

NC 0.015 0.015 0.015 0.1 0.3
 UPSTREAM FACE OF TOMIYASU LANE BRIDGE
 X1 12400 4 2222.53 2295.25 78.79 77.02 75.37
 GR 1989.4 2222.53 1983.11 2233.89 1983.11 2283.89 1989.4 2295.25

NC	0.015	0.015	0.015	0.1	0.3					
SB	1.25	1.5	3	73	50	1	351	1.8	1983.11	1982.84
DOWNSTREAM FACE OF TOMIYASU BRIDGE										
X1	12300	4	1394.43	1468.12	277.2	272.41	277.73			
X2			1	2009.42	2012			2		
GR	1989.4	1394.43	1982.84	1406.28	1982.84	1456.28	1989.4	1468.12		

1 16JUN04 14:15:51 PAGE 9

NC	0.015	0.015	0.015	0.1	0.3					
X1	12200	4	1207.74	1252.82	289.39	297.62	287.98			
GR	1988.8	1207.74	1978.83	1207.74	1978.83	1252.82	1988.8	1252.82		
NC	0.015	0.015	0.015	0.1	0.3					
X1	12100	4	1205.25	1246.05	252	252	252			
GR	1984.6	1205.25	1974.6	1205.25	1974.6	1246.05	1984.6	1246.05		

NC	0.015	0.015	0.015	0.1	0.3					
UPSTREAM FACE OF CROSSING										
X1	12000	4	970.15	1004.49	5	5	5			
GR	1990	970.15	1970.97	970.15	1970.97	1004.49	1990	1004.49		

NC	0.015	0.015	0.015	0.1	0.3					
SB	1.5	3	34.3	34.3			260	0	1970.97	1970.88
DOWNSTREAM FACE OF CROSSING										
X1	11900	4	996.53	1030.83	92	92	92			
X2			1	1998.54	1990.99					
GR	1990	996.53	1970.88	996.53	1970.88	1030.83	1990.99	1030.83		

NC	0.015	0.015	0.015	0.1	0.3					
X1	11800	4	1000	1034.4	86	86	86			
GR	1981.1	1000	1969.57	1000	1969.57	1034.4	1981.1	1034.4		

NC	0.015	0.015	0.015	0.1	0.3					
UPSTREAM FACE OF CROSSING										
X1	11700	4	966.89	1001.29	16	16	16			
GR	1979.8	966.89	1968.25	966.89	1968.25	1001.29	1979.8	1001.29		

NC	0.015	0.015	0.015	0.1	0.3					
SB	0.9	1.5	3	34.4	34.4	1.5	297	0	1968.25	1967.32
DOWNSTREAM FACE OF CROSSING										
X1	11600	4	1000	1034.4	215.89	214.6	215			
X2			1	1996.89	1999.84			1.33		
GR	1979.8	1000	1967.32	1000	1967.32	1034.4	1979.8	1034.4		

NC	0.015	0.015	0.015	0.1	0.3					
UPSTREAM FACE OF PECOS ROAD BRIDGE										
X1	11500	4	2258.08	2300.08	100	100	100			
GR	1975.3	2258.08	1964.52	2258.08	1964.52	2300.08	1975.3	2300.08		

NC	0.015	0.015	0.015	0.1	0.3					
SB	1.5	3	42	42			252	0	1964.52	1964.02
DOWNSTREAM FACE OF PECOS ROAD BRIDGE										
X1	11400	4	1000	1042	243.24	244.99	243.55			
X2			1	1990.52	1972.82					
GR	1975.5	1000	1964.02	1000	1964.02	1042	1975.5	1042		

1 16JUN04 14:15:51 PAGE 10

NC	0.015	0.015	0.015	0.1	0.3					
X1	11300	6	1846.27	1907.7	469.26	455.15	474			
GR	1972	1846.27	1968	1854.64	1964	1863.11	1964	1892.84	1968	1900.18
GR	1972	1907.7								

NC	0.015	0.015	0.015	0.1	0.3					
X1	11200	6	1924.66	1989.1	319.86	510.47	430.53			
GR	1972	1924.66	1968	1933.3	1962	1940.2	1962	1974.26	1968	1981.39
GR	1972	1989.1								

NC	0.015	0.015	0.015	0.1	0.3					
----	-------	-------	-------	-----	-----	--	--	--	--	--

X1	11100	8	1886.46	1971.49	325.47	495.3	411.3			
GR	1972	1886.46	1968	1899.6	1964	1906.8	1960	1912.18	1960	1941.39
GR	1964	1946.06	1968	1955.18	1972	1971.49				

NC	0.08	0.11	0.015	0.1	0.3					
X1	11000	8	1814.89	1912.16	347.02	470.02	392.7			
GR	1972	1799.08	1968	1814.89	1964	1845.64	1960	1853.3	1960	1887.79

GR	1964	1894.39	1968	1900.91	1972	1912.16				
NC	0.08	0.11	0.015	0.1	0.3					
X1	10900	7	1859.99	1943.58	386.71	376.94	388.5			
GR	1964	1859.99	1960	1889.41	1956	1897.52	1956	1933.17	1960	1938.52
GR	1964	1943.58	1968	1950.63						
NC	0.015	0.015	0.015	0.1	0.3					

X1	10800	6	2155.44	2258.77	410.33	392.26	386.03			
GR	1960	2155.44	1956	2186.29	1952	2195.29	1952	2229.27	1956	2236.88
GR	1960	2258.77								

1 16JUN04 14:15:51 PAGE 11

NC	0.015	0.015	0.015	0.1	0.3
----	-------	-------	-------	-----	-----

X1	10700	7	1984.66	2093.9	430.71	421.11	418.08			
GR	1956	1984.66	1952	2025.37	1948	2033.98	1948	2067.44	1952	2074.65
GR	1956	2083.13	1960	2093.9						
NC	0.015	0.015	0.015	0.1	0.3					

1 16JUN04 14:15:51 PAGE 12

DOWNSTREAM LIMIT OF MODEL
ORIGINAL MODEL: DCLISUBC.DAT
ESTABLISHED WATER SURFACE ELEVATION = 1949.3 FT (SUPERCRITICAL CONDITI

X1	10600	8	2209.95	2299.38	356.88	402.83	378.87			
GR	1950	2209.95	1948	2229.01	1944	2237.56	1942	2242.81	1942	2270.77
GR	1944	2274.76	1948	2281.50	1952	2299.38				

16JUN04 14:15:51

PAGE 13

SECNO	DEPTH	CWSEL	CRISW	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*PROF 1

CRITICAL DEPTH TO BE CALCULATED AT ALL CROSS SECTIONS

0

CCHV= .100 CEHV= .300

*SECNO 15500.000

3720 CRITICAL DEPTH ASSUMED

15500.000	8.85	2037.10	2037.10	2037.80	2041.57	4.47	.00	.00	2039.50
8562.0	.0	8562.0	.0	.0	504.5	.0	.0	.0	2039.50
.00	.00	16.97	.00	.000	.015	.000	.000	2028.25	1642.82
.002299	0.	0.	0.	0	10	0	.00	57.00	1699.82

CCHV= .100 CEHV= .300

*SECNO 15400.000

3301 HV CHANGED MORE THAN HVINS

3302 WARNING: CONVEYANCE CHANGE OUTSIDE OF ACCEPTABLE RANGE, KRATIO = 1.71

15400.000	5.23	2032.73	2035.12	.00	2040.62	7.89	.61	.34	2040.00
8562.0	.0	8562.0	.0	.0	379.8	.0	1.7	.3	2040.00
.00	.00	22.54	.00	.000	.015	.000	.000	2027.50	1215.88
.006710	214.	166.	136.	12	11	0	.00	77.42	1293.30

CCHV= .100 CEHV= .300

*SECNO 15300.000

3301 HV CHANGED MORE THAN HVINS

3685 20 TRIALS ATTEMPTED WSEL,CWSEL

3693 PROBABLE MINIMUM SPECIFIC ENERGY

3720 CRITICAL DEPTH ASSUMED

15300.000	8.16	2034.80	2034.80	.00	2038.11	3.31	1.52	1.58	2037.00
8562.0	.0	8562.0	.0	.0	586.2	.0	6.9	1.2	2037.00
.01	.00	14.61	.00	.000	.015	.000	.000	2026.64	1000.00
.001895	440.	471.	434.	20	14	0	.00	90.00	1090.00

16JUN04 14:15:51

PAGE 14

SECNO	DEPTH	CWSEL	CRISW	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

CCHV= .100 CEHV= .300

*SECNO 15250.000

3301 HV CHANGED MORE THAN HVINS

15250.000	7.05	2033.38	2034.32	.00	2037.87	4.50	.12	.12	2037.00
8562.0	.0	8562.0	.0	.0	503.1	.0	7.5	1.3	2037.00
.01	.00	17.02	.00	.000	.015	.000	.000	2026.33	1002.11
.003025	51.	51.	51.	6	5	0	.00	88.09	1090.20

CCHV= .100 CEHV= .300

*SECNO 15200.000

3301 HV CHANGED MORE THAN HVINS

15200.000	6.43	2032.37	2033.81	.00	2037.59	5.22	.21	.07	2037.00
8562.0	.0	8562.0	.0	.0	467.1	.0	8.2	1.4	2037.00
.01	.00	18.33	.00	.000	.015	.000	.000	2025.94	1003.33
.003876	62.	62.	62.	18	8	0	.00	88.40	1091.73

CCHV= .100 CEHV= .300

*SECNO 15150.000

15150.000	6.24	2031.48	2033.09	.00	2037.09	5.61	.46	.04	2036.00
8562.0	.0	8562.0	.0	.0	450.6	.0	9.4	1.6	2036.00
.01	.00	19.00	.00	.000	.015	.000	.000	2025.24	1003.70
.004316	113.	113.	113.	15	11	0	.00	87.65	1091.36

CCHV= .100 CEHV= .300
*SECNO 15110.000

3301 HV CHANGED MORE THAN HVINS

3685 20 TRIALS ATTEMPTED WSEL,CWSEL
3693 PROBABLE MINIMUM SPECIFIC ENERGY
3720 CRITICAL DEPTH ASSUMED

15110.000	8.41	2032.43	2032.43	.00	2036.53	4.09	.60	2.43	2033.02
8562.0	.0	8562.0	.0	.0	527.3	.0	11.7	2.0	2033.02
.02	.00	16.24	.00	.000	.015	.000	.000	2024.02	1000.00
.002197	200.	200.	200.	20	11	0	.00	65.00	1065.00

1
16JUN04 14:15:51

PAGE 15

SECNO	DEPTH	CWSEL	CRWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

CCHV= .100 CEHV= .300
*SECNO 15100.000

15100.000	8.33	2032.33	2032.41	.00	2036.51	4.18	.01	.01	2033.00
8562.0	.0	8562.0	.0	.0	521.9	.0	11.7	2.0	2033.00
.02	.00	16.41	.00	.000	.015	.000	.000	2024.00	1000.00
.002267	3.	3.	3.	0	5	0	.00	65.00	1065.00

CCHV= .100 CEHV= .300
*SECNO 15050.000

3301 HV CHANGED MORE THAN HVINS

15050.000	7.39	2030.70	2031.74	.00	2036.08	5.38	.31	.12	2032.31
8562.0	.0	8562.0	.0	.0	460.0	.0	13.0	2.1	2032.31
.02	.00	18.61	.00	.000	.015	.000	.000	2023.31	1000.00
.003344	115.	115.	115.	6	5	0	.00	65.00	1065.00

CCHV= .100 CEHV= .300
*SECNO 15000.000

3301 HV CHANGED MORE THAN HVINS

15000.000	7.01	2029.81	2031.23	.00	2035.79	5.98	.23	.06	2031.80
8562.0	.0	8562.0	.0	.0	436.4	.0	13.7	2.2	2031.80
.02	.00	19.62	.00	.000	.015	.000	.000	2022.80	1000.00
.003937	62.	62.	62.	18	8	0	.00	65.00	1065.00

CCHV= .100 CEHV= .300
*SECNO 14950.000

14950.000	6.95	2029.35	2030.81	.00	2035.44	6.09	.34	.01	2031.00
8562.0	.0	8562.0	.0	.0	432.4	.0	14.5	2.4	2031.00
.02	.00	19.80	.00	.000	.015	.000	.000	2022.40	1000.00
.004053	85.	85.	85.	18	11	0	.00	65.00	1065.00

1
16JUN04 14:15:51

PAGE 16

SECNO	DEPTH	CWSEL	CRWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

SPECIAL BRIDGE

5290 UPSTREAM ELEV IS 2032.06 ,NOT 2029.35 NEW BACKWATER REQUIRED

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
.90	1.50	3.00	90.00	65.00	1.50	455.00	.00	2022.40	2022.01	

CCHV= .100 CEHV= .300
*SECNO 14900.000

CLASS B LOW FLOW

3420 BRIDGE W.S.= 2030.47 BRIDGE VELOCITY= 16.32 CALCULATED CHANNEL AREA= 512.

EGPRS	EGLWC	H3	QWEIR	QLOW	BAREA	TRAPEZOID AREA	ELLC	ELTRD	WEIRLN
.00	2034.87	.00	0.	8562.	455.	1118.	2040.00	2040.00	0.

14900.000	7.20	2029.21	.00	.00	2034.87	5.66	.57	.00	2031.00
8562.0	.0	8562.0	.0	.0	448.6	.0	15.0	2.4	2033.02
.02	.00	19.09	.00	.000	.015	.000	.000	2022.01	1000.00
.003616	53.	53.	53.	0	0	0	.00	65.00	1065.00

CCHV= .100 CEHV= .300

*SECNO 14850.000

14850.000	7.05	2028.79	2030.18	.00	2034.70	5.92	.14	.03	2030.80
8562.0	.0	8562.0	.0	.0	438.7	.0	15.4	2.5	2032.75
.02	.00	19.52	.00	.000	.015	.000	.000	2021.74	1000.00
.003875	37.	37.	37.	19	8	0	.00	65.00	1065.00

CCHV= .100 CEHV= .300

*SECNO 14800.000

3301 HV CHANGED MORE THAN HVINS

14800.000	6.48	2027.08	2029.01	.00	2034.13	7.06	.45	.11	2029.60
8562.0	.0	8562.0	.0	.0	401.6	.0	16.4	2.7	2031.61
.02	.00	21.32	.00	.000	.015	.000	.000	2020.60	1000.00
.005099	103.	103.	103.	14	11	0	.00	65.00	1065.00

1

16JUN04 14:15:51

PAGE 17

SECNO	DEPTH	CWSEL	CRWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XLN	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

CCHV= .100 CEHV= .300

*SECNO 14750.000

14750.000	6.93	2026.43	2028.36	.00	2033.62	7.20	.50	.01	2028.50
8562.0	.0	8562.0	.0	.0	397.7	.0	17.3	2.8	2030.51
.03	.00	21.53	.00	.000	.015	.000	.000	2019.50	1000.00
.004896	100.	100.	100.	7	11	0	.00	60.00	1060.00

CCHV= .100 CEHV= .300

*SECNO 14700.000

3301 HV CHANGED MORE THAN HVINS

14700.000	6.70	2025.57	2027.72	.00	2033.28	7.71	.29	.05	2027.90
8562.0	.0	8562.0	.0	.0	384.3	.0	17.8	2.9	2029.88
.03	.00	22.28	.00	.000	.015	.000	.000	2018.87	1000.00
.005443	56.	56.	56.	7	11	0	.00	60.00	1060.00

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.25	1.50	3.00	103.00	60.00	2.13	588.00	.00	2018.87	2018.37

CCHV= .100 CEHV= .300

*SECNO 14600.000

3301 HV CHANGED MORE THAN HVINS

CLASS C LOW FLOW

3420 BRIDGE W.S.= 2026.70 BRIDGE VELOCITY= 18.32 CALCULATED CHANNEL AREA= 453.

EGPRS	EGLWC	H3	QWEIR	QLOW	BAREA	TRAPEZOID AREA	ELLC	ELTRD	WEIRLN
.00	2031.65	.00	0.	8562.	588.	1147.	2038.69	2040.21	0.

14600.000	7.23	2025.60	.00	.00	2031.65	6.04	1.64	.00	2030.20
8562.0	.0	8562.0	.0	.0	434.0	.0	18.9	3.0	2030.20
.03	.00	19.73	.00	.000	.015	.000	.000	2018.37	1390.42
.003780	112.	112.	112.	0	0	0	.00	60.00	1450.42

1

16JUN04 14:15:51

PAGE 18

SECNO	DEPTH	CWSEL	CRWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XLN	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

CCHV= .100 CEHV= .300

*SECNO 14550.000

3301 HV CHANGED MORE THAN HVINS

3685 20 TRIALS ATTEMPTED WSEL,CWSEL

14550.000	6.86	2024.79	2026.51	.00	2031.50	6.70	.09	.07	2025.40
8562.0	.0	8562.0	.0	.0	412.0	.0	19.1	3.1	2025.40
.03	.00	20.78	.00	.000	.015	.000	.000	2017.93	1000.00
.004436	20.	20.	20.	20	8	0	.00	60.06	1060.06

CCHV= .100 CEHV= .300

*SECNO 14500.000

3301 HV CHANGED MORE THAN HVINS

14500.000	6.41	2023.51	2025.65	.00	2031.20	7.69	.20	.10	2024.60
8562.0	.0	8562.0	.0	.0	384.7	.0	19.4	3.1	2024.60
.03	.00	22.26	.00	.000	.015	.000	.000	2017.10	1000.00
.005486	40.	40.	40.	18	11	0	.00	60.00	1060.00

CCHV= .100 CEHV= .300

*SECNO 14450.000

3301 HV CHANGED MORE THAN HVINS

14450.000	6.05	2022.18	2024.69	.00	2030.81	8.63	.30	.09	2025.10
8562.0	.0	8562.0	.0	.0	363.2	.0	19.9	3.2	2023.63
.03	.00	23.58	.00	.000	.015	.000	.000	2016.13	1000.00
.006559	50.	50.	50.	17	11	0	.00	60.00	1060.00

CCHV= .100 CEHV= .300

*SECNO 14400.000

14400.000	5.97	2021.77	2024.37	.00	2030.65	9.88	.13	.02	2025.10
8562.0	.0	8562.0	.0	.0	358.0	.0	20.0	3.2	2028.80
.03	.00	23.91	.00	.000	.015	.000	.000	2015.80	1782.00
.006856	20.	20.	20.	7	11	0	.00	60.00	1842.00

1

16JUN04 14:15:51

PAGE 19

SECNO	DEPTH	CWSEL	CRWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.25	1.50	3.00	17.00	60.00	4.00	452.00	.00	2015.80	2015.30

CCHV= .100 CEHV= .300

*SECNO 14300.000

3301 HV CHANGED MORE THAN HVINS

CLASS C LOW FLOW

3420 BRIDGE W.S.= 2023.27 BRIDGE VELOCITY= 19.80 CALCULATED CHANNEL AREA= 418.

EGPRS	EGLWC	H3	QWEIR	QLOW	BAREA	TRAPEZOID AREA	ELLC	ELTRD	WEIRLN
.00	2029.07	.00	0.	8562.	452.	795.	2030.00	2031.20	0.

14300.000	6.68	2021.98	.00	.00	2029.07	7.09	1.58	.00	2028.80
8562.0	.0	8562.0	.0	.0	400.8	.0	20.2	3.2	2028.80
.03	.00	21.36	.00	.000	.015	.000	.000	2015.30	1701.50
.004832	20.	20.	20.	0	0	0	.00	60.00	1761.50

CCHV= .100 CEHV= .300

*SECNO 14240.000

14240.000	6.54	2021.54	2023.55	.00	2028.94	7.40	.10	.03	2024.50
8562.0	.0	8562.0	.0	.0	392.2	.0	20.4	3.3	2022.53
.03	.00	21.83	.00	.000	.015	.000	.000	2015.00	1000.00
.005167	20.	20.	20.	8	11	0	.00	60.00	1060.00

CCHV= .100 CEHV= .300

*SECNO 14220.000

14220.000	6.35	2020.97	2023.17	.00	2028.79	7.82	.11	.04	2024.10
8562.0	.0	8562.0	.0	.0	381.7	.0	20.6	3.3	2022.13
.03	.00	22.43	.00	.000	.015	.000	.000	2014.62	1000.00
.005622	20.	20.	20.	8	11	0	.00	60.00	1060.00

CCHV= .100 CEHV= .300
 *SECNO 14200.000
 14200.000 6.22 2020.46 2022.80 .00 2028.63 8.18 .12 .04 2022.70
 8562.0 .0 8562.0 .0 .0 373.1 .0 20.7 3.3 2022.70
 .03 .00 22.95 .00 .000 .015 .000 .000 2014.24 1000.00
 .006030 20. 20. 20. 8 11 0 .00 60.00 1060.00

1

16JUN04 14:15:51

PAGE 20

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

CCHV= .100 CEHV= .300
 *SECNO 14100.000

3301 HV CHANGED MORE THAN HVINS

14100.000 7.72 2020.54 2022.92 .00 2027.99 7.45 .42 .22 2024.00
 8562.0 .0 8562.0 .0 .0 390.8 .0 21.4 3.4 2024.00
 .03 .00 21.91 .00 .000 .015 .000 .000 2012.82 1554.98
 .005264 75. 75. 75. 4 14 0 .00 59.28 1614.26

CCHV= .100 CEHV= .300
 *SECNO 14000.000

3301 HV CHANGED MORE THAN HVINS

14000.000 6.97 2017.86 2020.55 .00 2027.22 9.36 .58 .19 2019.40
 8562.0 .0 8562.0 .0 .0 348.8 .0 22.2 3.5 2019.40
 .03 .00 24.55 .00 .000 .015 .000 .000 2010.89 1000.00
 .006396 101. 101. 101. 13 11 0 .00 50.00 1050.00

CCHV= .100 CEHV= .300

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAPEA	SS	ELCHU	ELCHD
.00	1.50	3.00	50.00	50.00	.00	425.00	.00	2010.89	2010.21	

*SECNO 13900.000

6070, LOW FLOW BY NORMAL BRIDGE

EGPRS= .000 EGLWC= 2025.638 ELLC= 2039.390 PCWSE= 2017.862 ELTRD= 2021.130

3370 NORMAL BRIDGE, NRD= 0 MIN ELTRD= 2021.13 MAX ELLC= 2039.39

13900.000 6.82 2017.03 2019.88 .00 2026.80 9.77 .38 .04 2019.40
 8562.0 .0 8562.0 .0 .0 341.3 .0 22.7 3.6 2019.40
 .03 .00 25.09 .00 .000 .015 .000 .000 2010.21 1000.00
 .006832 57. 57. 57. 8 19 0 .00 50.00 1050.00

CCHV= .100 CEHV= .300

1

16JUN04 14:15:51

PAGE 21

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

*SECNO 13800.000

3280 CROSS SECTION 13800.00 EXTENDED .00 FEET

13800.000 7.00 2015.40 2018.08 .00 2024.68 9.28 1.97 .15 2015.40
 8562.0 .0 8562.0 .0 .0 350.2 .0 25.1 4.0 2015.40
 .04 .00 24.45 .00 .000 .015 .000 .000 2008.40 1000.00
 .006314 300. 300. 300. 7 11 0 .00 50.00 1050.00

CCHV= .100 CEHV= .300

*SECNO 13700.000

13700.000 7.07 2013.63 2016.23 .00 2022.73 9.10 1.90 .06 2014.00
 8562.0 .0 8562.0 .0 .0 353.8 .0 27.6 4.3 2014.00
 .04 .00 24.20 .00 .000 .015 .000 .000 2006.56 1000.00
 .006125 306. 306. 306. 8 11 0 .00 50.00 1050.00

CCHV= .100 CEHV= .300

*SECNO 13600.000

3301 HV CHANGED MORE THAN HVINS

13600.000	5.52	2011.63	2014.64	.00	2022.04	10.41	.55	.13	2013.10
8562.0	.0	8562.0	.0	.0	330.7	.0	28.1	4.4	2013.10
.04	.00	25.89	.00	.000	.015	.000	.000	2006.11	1398.12
.009049	75.	75.	75.	14	11	0	.00	69.75	1467.88

CCHV= .100 CEHV= .300
*SECNO 13500.000

3301 HV CHANGED MORE THAN HVINS

13500.000	5.05	2008.12	2011.59	.00	2020.88	12.76	.92	.24	2010.00
8562.0	.0	8562.0	.0	.0	298.7	.0	28.8	4.6	2010.00
.04	.00	28.67	.00	.000	.015	.000	.000	2003.07	1412.89
.012294	152.	88.	89.	13	14	0	.00	68.23	1481.11

CCHV= .100 CEHV= .300

1 16JUN04 14:15:51

PAGE 22

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	.00	1.50	3.00	75.00	50.00	.00	438.00	1.80	2003.07	2002.77

*SECNO 13400.000

6070, LOW FLOW BY NORMAL BRIDGE

EGPRS= .000 EGLWC= 2019.296 ELLC= 2030.070 PCWSE= 2008.120 ELTRD= 2012.330

3370 NORMAL BRIDGE, NRD= 0 MIN ELTRD= 2012.33 MAX ELLC= 2030.07

13400.000	5.10	2007.87	2011.28	.00	2020.37	12.50	.44	.08	2009.70
8562.0	.0	8562.0	.0	.0	301.8	.0	29.0	4.6	2009.70
.04	.00	28.37	.00	.000	.015	.000	.000	2002.77	2797.82
.011920	37.	36.	37.	5	23	0	.00	68.39	2866.22

CCHV= .100 CEHV= .300
*SECNO 13300.000

3301 HV CHANGED MORE THAN HVINS

13300.000	5.34	2007.63	2010.82	.00	2018.90	11.26	1.10	.37	2009.30
8562.0	.0	8562.0	.0	.0	317.9	.0	29.7	4.8	2009.30
.04	.00	26.93	.00	.000	.015	.000	.000	2002.29	1000.48
.010173	100.	100.	100.	7	14	0	.00	69.05	1069.52

CCHV= .100 CEHV= .300
*SECNO 13200.000

3301 HV CHANGED MORE THAN HVINS

13200.000	7.01	2008.41	2011.07	.00	2017.66	9.26	.63	.60	2008.50
8562.0	.0	8562.0	.0	.0	350.6	.0	30.4	4.9	2008.50
.04	.00	24.42	.00	.000	.015	.000	.000	2001.40	995.00
.006292	80.	80.	80.	2	14	0	.00	50.00	1045.00

CCHV= .100 CEHV= .300
*SECNO 13100.000

1 16JUN04 14:15:51

PAGE 23

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3301 HV CHANGED MORE THAN HVINS

13100.000	6.58	2005.57	2008.66	.00	2016.08	10.51	1.46	.10	2006.00
8562.0	.0	8562.0	.0	.0	329.2	.0	32.0	5.1	2006.00
.05	.00	26.01	.00	.000	.015	.000	.000	1998.99	994.85
.007630	209.	211.	211.	10	11	0	.00	50.00	1044.85

CCHV= .100 CEHV= .300
*SECNO 13000.000

3301 HV CHANGED MORE THAN HVINS

13000.000	5.47	1999.37	2003.59	.00	2014.63	15.26	.98	.48	2004.20
8562.0	.0	8562.0	.0	.0	273.1	.0	32.7	5.2	2004.20
.05	.00	31.35	.00	.000	.015	.000	.000	1993.90	2587.74
.013547	98.	98.	98.	14	11	0	.00	50.00	2637.74

CCHV= .100 CEHV= .300

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
.00	1.50	3.00	50.00	50.00	.00	350.00	.00	1993.90	1993.47	

*SECNO 12900.000

6070,LOW FLOW BY NORMAL BRIDGE

EGPRS= .000 EGLWC= 2012.457 ELLC= 2020.900 PCWSE= 1999.368 ELTRD= 2004.200

3370 NORMAL BRIDGE, NRD= 0 MIN ELTRD= 2004.20 MAX ELLC= 2020.90

12900.000	5.47	1998.94	2003.13	.00	2014.17	15.24	.45	.01	2004.20
8562.0	.0	8562.0	.0	.0	273.3	.0	32.9	5.3	2004.20
.05	.00	31.32	.00	.000	.015	.000	.000	1993.47	2630.84
.013512	33.	33.	33.	6	19	0	.00	50.00	2680.84

CCHV= .100 CEHV= .300
*SECNO 12800.000

1

16JUN04 14:15:51

PAGE 24

SECNO	DEPTH	CWSEL	CRWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

3301 HV CHANGED MORE THAN HVINS

12800.000	5.87	1997.22	2001.01	.00	2010.45	13.23	3.13	.60	1998.30
8562.0	.0	8562.0	.0	.0	293.3	.0	34.6	5.6	1998.30
.05	.00	29.19	.00	.000	.015	.000	.000	1991.35	2505.21
.010868	260.	259.	258.	8	14	0	.00	50.00	2555.21

CCHV= .100 CEHV= .300
*SECNO 12700.000

3301 HV CHANGED MORE THAN HVINS

12700.000	6.28	1994.43	1997.81	.00	2005.99	11.56	3.96	.50	1995.10
8562.0	.0	8562.0	.0	.0	313.8	.0	37.4	6.0	1995.10
.05	.00	27.29	.00	.000	.015	.000	.000	1988.15	2430.44
.008833	405.	405.	405.	7	14	0	.00	50.00	2480.44

CCHV= .100 CEHV= .300
*SECNO 12600.000

12600.000	6.39	1992.02	1995.29	.00	2003.18	11.15	2.69	.12	1993.60
8562.0	.0	8562.0	.0	.0	319.5	.0	39.7	6.4	1993.60
.06	.00	26.80	.00	.000	.015	.000	.000	1985.63	1000.00
.008360	317.	313.	310.	7	14	0	.00	50.00	1050.00

CCHV= .100 CEHV= .300
*SECNO 12500.000

3301 HV CHANGED MORE THAN HVINS

12500.000	4.94	1988.64	1992.27	.00	2002.16	13.52	.78	.24	1991.10
8562.0	.0	8562.0	.0	.0	290.2	.0	40.2	6.5	1991.10
.06	.00	29.51	.00	.000	.015	.000	.000	1983.70	2500.06
.013305	75.	75.	75.	14	11	0	.00	67.30	2567.36

CCHV= .100 CEHV= .300
*SECNO 12400.000

1

16JUN04 14:15:51

PAGE 25

SECNO	DEPTH	CWSEL	CRWS	WSELF	EG	HV	HL	OLOSS	L-BANK ELEV
-------	-------	-------	------	-------	----	----	----	-------	-------------

Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK	ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA	
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST	

3301 HV CHANGED MORE THAN HVINS

12400.000	5.09	1988.20	1991.61	.00	2000.75	12.56	1.12	.29	1989.40	
8562.0	.0	8562.0	.0	.0	301.1	.0	40.8	6.6	1989.40	
.06	.00	28.44	.00	.000	.015	.000	.000	1983.11	2224.70	
.012002	86.	89.	91.	8	14	0	.00	68.38	2293.08	

CCHV= .100 CEHV= .300

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	1.25	1.50	3.00	73.00	50.00	1.00	351.00	1.80	1983.11	1982.84

*SECNO 12300.000
CLASS C LOW FLOW

3420 BRIDGE W.S.= 1988.25 BRIDGE VELOCITY= 27.76 CALCULATED CHANNEL AREA= 299.

EGPRS	EGLWC	H3	QWEIR	QLOW	BAREA	TRAPEZOID	ELLC	ELTRD	WEIRLN	
	.00	2000.07	.00	0.	8562.	351.	2535.	2009.42	2012.00	0.

12300.000	5.18	1988.02	.00	.00	2000.07	12.06	.68	.00	1989.40	
8562.0	.0	8562.0	.0	.0	307.3	.0	41.3	6.7	1989.40	
.06	.00	27.87	.00	.000	.015	.000	.000	1982.84	1396.93	
.011296	79.	75.	77.	0	0	0	.00	68.70	1465.62	

CCHV= .100 CEHV= .300

*SECNO 12200.000

3301 HV CHANGED MORE THAN HVINS

12200.000	7.00	1985.83	1989.21	.00	1997.26	11.43	2.63	.19	1988.80	
8562.0	.0	8562.0	.0	.0	315.6	.0	43.3	7.1	1988.80	
.06	.00	27.13	.00	.000	.015	.000	.000	1978.83	1207.74	
.008031	277.	278.	272.	8	14	0	.00	45.08	1252.82	

CCHV= .100 CEHV= .300

1

16JUN04 14:15:51

PAGE 26

SECNO	DEPTH	CWSEL	CRISW	WSELK	EG	HV	HL	OLOSS	L-BANK	ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK	ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA	
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST	

*SECNO 12100.000

3301 HV CHANGED MORE THAN HVINS

12100.000	7.32	1981.92	1985.66	.00	1994.70	12.77	2.43	.13	1984.60	
8562.0	.0	8562.0	.0	.0	298.5	.0	45.3	7.4	1984.60	
.07	.00	28.68	.00	.000	.015	.000	.000	1974.60	1205.25	
.008879	289.	288.	298.	9	14	0	.00	40.80	1246.05	

CCHV= .100 CEHV= .300

*SECNO 12000.000

12000.000	8.65	1979.62	1983.38	.00	1992.53	12.91	2.15	.01	1990.00	
8562.0	.0	8562.0	.0	.0	296.9	.0	47.1	7.6	1990.00	
.07	.00	28.84	.00	.000	.015	.000	.000	1970.97	970.15	
.008223	252.	252.	252.	10	14	0	.00	34.34	1004.49	

CCHV= .100 CEHV= .300

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	.00	1.50	3.00	34.30	34.30	.00	260.00	.00	1970.97	1970.88

*SECNO 11900.000

6070, LOW FLOW BY NORMAL BRIDGE

EGPRS= .000 EGLWC= 1992.293 ELLC= 1998.540 FCWSE= 1979.617 ELTRD= 1990.990

3370 NORMAL BRIDGE, NRD= 0 MIN ELTRD= 1990.99 MAX ELLC= 1998.54

11900.000	8.64	1979.52	1983.30	.00	1992.48	12.96	.04	.00	1990.00
8562.0	.0	8562.0	.0	.0	296.4	.0	47.1	7.6	1990.99
.07	.00	28.89	.00	.000	.015	.000	.000	1970.88	996.53
.008264	5.	5.	5.	4	9	0	.00	34.30	1030.83

CCHV= .100 CEHV= .300
 *SECNO 11800.000

3301 HV CHANGED MORE THAN HVINS

11800.000	8.39	1977.96	1981.99	.00	1991.62	13.66	.79	.07	1981.10
8562.0	.0	8562.0	.0	.0	288.7	.0	47.7	7.7	1981.10
.07	.00	29.66	.00	.000	.015	.000	.000	1969.57	1000.00
.008927	92.	92.	92.	7	11	0	.00	34.40	1034.40

1

16JUN04 14:15:51

PAGE 27

SECNO	DEPTH	CWSEL	CRISW	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

CCHV= .100 CEHV= .300
 *SECNO 11700.000

3301 HV CHANGED MORE THAN HVINS

11700.000	8.20	1976.45	1980.68	.00	1990.76	14.31	.79	.06	1979.80
8562.0	.0	8562.0	.0	.0	282.0	.0	48.3	7.8	1979.80
.07	.00	30.36	.00	.000	.015	.000	.000	1968.25	966.89
.009550	86.	86.	86.	7	11	0	.00	34.40	1001.29

CCHV= .100 CEHV= .300

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	.90	1.50	3.00	34.40	34.40	1.50	297.00	.00	1969.25	1967.32

*SECNO 11600.000

3301 HV CHANGED MORE THAN HVINS

CLASS C LOW FLOW

3420 BRIDGE W.S.= 1977.17 BRIDGE VELOCITY= 27.74 CALCULATED CHANNEL AREA= 293.

EGPRS	EGLWC	H3	QWEIR	QLOW	BAREA	TRAPEZOID AREA	ELLC	ELTRD	WEIRLN
.00	1989.63	.00	0.	8562.	297.	942.	1996.89	1999.84	0.

11600.000	8.75	1976.07	.00	.00	1988.63	12.56	2.13	.00	1979.80
8562.0	.0	8562.0	.0	.0	301.0	.0	48.4	7.8	1979.80
.07	.00	28.45	.00	.000	.015	.000	.000	1967.32	1000.00
.007911	16.	16.	16.	0	0	0	.00	34.40	1034.40

CCHV= .100 CEHV= .300
 *SECNO 11500.000

3301 HV CHANGED MORE THAN HVINS

11500.000	6.50	1971.02	1975.37	.00	1986.30	15.28	2.06	.27	1975.30
8562.0	.0	8562.0	.0	.0	272.9	.0	49.8	8.0	1975.30
.07	.00	31.37	.00	.000	.015	.000	.000	1964.52	2258.08
.011848	216.	215.	215.	12	11	0	.00	42.00	2300.08

1

16JUN04 14:15:51

PAGE 28

SECNO	DEPTH	CWSEL	CRISW	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

CCHV= .100 CEHV= .300

SPECIAL BRIDGE

SB	XK	XKOR	COFQ	RDLEN	BWC	BWP	BAREA	SS	ELCHU	ELCHD
	.00	1.50	3.00	42.00	42.00	.00	250.00	.00	1964.52	1964.00

*SECNO 11400.000

6070,LOW FLOW BY NORMAL BRIDGE

EGPRS= .000 EGLWC= 1984.198 ELLC= 1990.520 PCWSE= 1971.017 ELTRD= 1972.820

3301 HV CHANGED MORE THAN HVINS

3370 NORMAL BRIDGE, NRD= 0 MIN ELTRD= 1972.82 MAX ELLC= 1990.52

11400.000	6.80	1970.82	1974.87	.00	1984.80	13.98	1.11	.39	1975.50
8562.0	.0	8562.0	.0	.0	285.3	.0	50.4	8.1	1975.50
.07	.00	30.01	.00	.000	.015	.000	.000	1964.02	1000.00
.010360	100.	100.	100.	3	15	0	.00	42.00	1042.00

CCHV= .100 CEHV= .300

*SECNO 11300.000

3301 HV CHANGED MORE THAN HVINS

11300.000	7.56	1971.56	1974.47	.00	1981.55	9.99	2.06	1.20	1972.00
8562.0	.0	8562.0	.0	.0	337.5	.0	52.2	8.3	1972.00
.08	.00	25.37	.00	.000	.015	.000	.000	1964.00	1847.20
.007032	243.	244.	245.	6	14	0	.00	59.66	1906.86

CCHV= .100 CEHV= .300

*SECNO 11200.000

3301 HV CHANGED MORE THAN HVINS

11200.000	8.67	1970.67	1972.84	.00	1978.17	7.49	2.63	.75	1972.00
8562.0	.0	8562.0	.0	.0	389.7	.0	56.1	9.0	1972.00
.08	.00	21.97	.00	.000	.015	.000	.000	1962.00	1927.52
.004487	469.	474.	455.	7	11	0	.00	59.02	1986.55

1

16JUN04 14:15:51

PAGE 29

SECNO	DEPTH	CWSEL	CRISW	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST

CCHV= .100 CEHV= .300

*SECNO 11100.000

3301 HV CHANGED MORE THAN HVINS

11100.000	9.46	1969.46	1971.55	.00	1976.04	6.58	1.85	.27	1972.00
8562.0	.0	8562.0	.0	.0	415.9	.0	60.1	9.6	1972.00
.09	.00	20.59	.00	.000	.015	.000	.000	1960.00	1894.79
.004122	320.	431.	510.	8	11	0	.00	66.36	1961.15

CCHV= .100 CEHV= .300

*SECNO 11000.000

11000.000	7.93	1967.93	1969.72	.00	1974.06	6.13	1.85	.14	1968.00
8562.0	.0	8562.0	.0	.0	430.9	.0	64.1	10.3	1972.00
.09	.00	19.87	.00	.000	.015	.000	.000	1960.00	1815.35
.004905	325.	411.	495.	7	8	0	.00	85.47	1900.81

CCHV= .100 CEHV= .300

*SECNO 10900.000

3301 HV CHANGED MORE THAN HVINS

10900.000	7.17	1963.17	1965.63	.00	1971.53	8.36	2.31	.22	1964.00
8562.0	.0	8562.0	.0	.0	368.9	.0	67.7	11.0	1964.00
.10	.00	23.21	.00	.000	.015	.000	.000	1956.00	1866.06
.007158	347.	393.	420.	5	11	0	.00	76.48	1942.54

CCHV= .100 CEHV= .300

*SECNO 10800.000

3301 HV CHANGED MORE THAN HVINS

10800.000	6.60	1958.60	1961.31	.00	1968.15	9.55	3.26	.12	1960.00
8562.0	.0	8562.0	.0	.0	345.2	.0	70.9	11.8	1960.00
.10	.00	24.80	.00	.000	.015	.000	.000	1952.00	2166.24
.009991	387.	389.	377.	6	11	0	.00	84.87	2251.11

CCHV= .100 CEHV= .300

1

SECNO	DEPTH	CWSEL	CRIWS	WSELK	EG	HV	HL	OLOSS	L-BANK ELEV
Q	QLOB	QCH	QROB	ALOB	ACH	AROB	VOL	TWA	R-BANK ELEV
TIME	VLOB	VCH	VROB	XNL	XNCH	XNR	WTN	ELMIN	SSTA
SLOPE	XLOBL	XLCH	XLOBR	ITRIAL	IDC	ICONT	CORAR	TOPWID	ENDST
*SECNO 10700.000									
10700.000	6.71	1954.71	1957.54	.00	1964.32	9.61	3.82	.01	1956.00
8562.0	.0	8562.0	.0	.0	344.1	.0	74.0	12.5	1960.00
.11	.00	24.88	.00	.000	.015	.000	.000	1948.00	1997.80
.009815	410.	386.	392.	7	11	0	.00	82.60	2080.39

CCHV= .100 CEHV= .300

*SECNO 10600.000

3301 HV CHANGED MORE THAN HVINS

DOWNSTREAM LIMIT OF MODEL

ORIGINAL MODEL: DCL1SUBC.DAT

ESTABLISHED WATER SURFACE ELEVATION = 1949.3 FT (SUPERCRITICAL CONDITI

10600.000	7.31	1949.31	1952.40	.00	1960.10	10.79	4.10	.12	1950.00
8562.0	.0	8562.0	.0	.0	324.8	.0	77.2	13.2	1952.00
.11	.00	26.36	.00	.000	.015	.000	.000	1942.00	2216.61
.009812	431.	418.	421.	6	14	0	.00	70.72	2287.33

1

16JUN04 14:15:51

PAGE 31

THIS RUN EXECUTED 16JUN04 14:15:51

HEC-2 WATER SURFACE PROFILES

Version 4.6.2; May 1991

NOTE- ASTERISK (*) AT LEFT OF CROSS-SECTION NUMBER INDICATES MESSAGE IN SUMMARY OF ERRORS LIST

DCL1SUFx

SUMMARY PRINTOUT TABLE 100

SECNO	EGLWC	ELLC	EGPRS	ELTRD	QPR	QWEIR	CLASS	H3	DEPTH	CWSEL	VCH	EG
* 14900.000	2034.87	2040.00	.00	2042.00	8562.00	.00	2.00	.00	7.20	2029.21	19.09	2034.87
14600.000	2031.65	2038.69	.00	2040.21	8562.00	.00	3.00	.00	7.23	2025.60	19.73	2031.65
14300.000	2029.07	2030.00	.00	2031.20	8562.00	.00	3.00	.00	6.68	2021.98	21.36	2029.07
13900.000	2025.64	2039.39	.00	2021.13	8562.00	.00	59.00	.00	6.82	2017.03	25.09	2026.80
13400.000	2019.30	2030.07	.00	2012.33	8562.00	.00	59.00	.00	5.10	2007.87	28.37	2020.37
12900.000	2012.46	2020.90	.00	2004.20	8562.00	.00	59.00	.00	5.47	1998.94	31.32	2014.17
12300.000	2000.07	2009.42	.00	2012.00	8562.00	.00	3.00	.00	5.18	1988.02	27.87	2000.07
11900.000	1992.29	1998.54	.00	1990.99	8562.00	.00	59.00	.00	8.64	1979.52	28.89	1992.48
11600.000	1988.63	1996.89	.00	1999.84	8562.00	.00	3.00	.00	8.75	1976.07	28.45	1988.63
11400.000	1984.20	1990.52	.00	1972.82	8562.00	.00	59.00	.00	6.80	1970.82	30.01	1984.80

1

16JUN04 14:15:51

PAGE 32

DCL1SUFx

SUMMARY PRINTOUT TABLE 101

SECNO	EGOC	ELLC	EGIC	ELTRD	QCULV	QWEIR	CLASS	H4	DEPTH	CWSEL	VCH	EG
-------	------	------	------	-------	-------	-------	-------	----	-------	-------	-----	----

1

16JUN04 14:15:51

PAGE 33

DCL1SUFx

SUMMARY PRINTOUT TABLE 150

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10*KS	VCH	AREA	.01K
*	15500.000	.00	.00	.00	2028.25	8562.00	2037.10	2037.10	2041.57	22.99	16.97	504.46	1785.62
•	15400.000	166.19	.00	.00	2027.50	8562.00	2032.73	2035.12	2040.62	67.10	22.54	379.80	1045.20
*	15300.000	471.40	.00	.00	2026.64	8562.00	2034.80	2034.80	2038.11	18.85	14.61	586.18	1971.81
	15250.000	50.75	.00	.00	2026.33	8562.00	2033.38	2034.32	2037.87	30.25	17.02	503.10	1556.85
	15200.000	61.56	.00	.00	2025.94	8562.00	2032.37	2033.81	2037.59	38.76	18.33	467.06	1375.20
	15150.000	113.23	.00	.00	2025.24	8562.00	2031.48	2033.09	2037.09	43.16	19.00	450.59	1303.30
*	15110.000	200.00	.00	.00	2024.02	8562.00	2032.43	2032.43	2036.53	21.97	16.24	527.26	1826.60
	15100.000	3.43	.00	.00	2024.00	8562.00	2032.33	2032.41	2036.51	22.67	16.41	521.88	1798.15
	15050.000	115.37	.00	.00	2023.31	8562.00	2030.70	2031.74	2036.08	33.44	18.61	460.03	1480.63
	15000.000	62.42	.00	.00	2022.80	8562.00	2029.81	2031.23	2035.79	39.37	19.62	436.42	1364.57
	14950.000	84.63	.00	.00	2022.40	8562.00	2029.35	2030.81	2035.44	40.53	19.80	432.36	1344.90
*	14900.000	52.69	2042.00	2040.00	2022.01	8562.00	2029.21	999999.00	2034.87	36.16	19.09	448.56	1423.87
	14850.000	37.36	.00	.00	2021.74	8562.00	2028.79	2030.18	2034.70	38.75	19.52	438.66	1375.44
	14800.000	102.56	.00	.00	2020.60	8562.00	2027.08	2029.01	2034.13	50.99	21.32	401.60	1199.02
	14750.000	99.50	.00	.00	2019.50	8562.00	2026.43	2028.36	2033.62	48.96	21.53	397.72	1223.70
	14700.000	56.34	.00	.00	2018.87	8562.00	2025.57	2027.72	2033.28	54.43	22.28	384.31	1160.50
	14600.000	111.98	2040.21	2038.69	2018.37	8562.00	2025.60	999999.00	2031.65	37.80	19.73	434.01	1392.55
*	14550.000	20.00	.00	.00	2017.93	8562.00	2024.79	2026.51	2031.50	44.36	20.78	412.04	1285.59
	14500.000	40.00	.00	.00	2017.10	8562.00	2023.51	2025.65	2031.20	54.86	22.26	384.68	1155.93
	14450.000	50.00	.00	.00	2016.13	8562.00	2022.18	2024.69	2030.81	65.59	23.58	363.17	1057.20
	14400.000	20.00	.00	.00	2015.80	8562.00	2021.77	2024.37	2030.65	68.56	23.91	358.04	1034.04
	14300.000	20.00	2031.20	2030.00	2015.30	8562.00	2021.98	999999.00	2029.07	48.32	21.36	400.78	1231.67
	14240.000	20.00	.00	.00	2015.00	8562.00	2021.54	2023.55	2028.94	51.67	21.83	392.20	1191.15
	14220.000	20.00	.00	.00	2014.62	8562.00	2020.97	2023.17	2028.79	56.22	22.43	381.65	1141.87

1

16JUN04 14:15:51

PAGE 34

	SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10*KS	VCH	AREA	.01K
	14200.000	20.00	.00	.00	2014.24	8562.00	2020.46	2022.80	2028.63	60.30	22.95	373.14	1102.62
	14100.000	75.00	.00	.00	2012.82	8562.00	2020.54	2022.92	2027.99	52.64	21.91	390.81	1180.05
	14000.000	101.00	.00	.00	2010.89	8562.00	2017.86	2020.55	2027.22	63.96	24.55	348.78	1070.63
	13900.000	57.00	2021.13	2039.39	2010.21	8562.00	2017.03	2019.88	2026.80	68.32	25.09	341.30	1035.88
	13800.000	300.00	.00	.00	2008.40	8562.00	2015.40	2018.08	2024.68	63.14	24.45	350.24	1077.47
	13700.000	306.00	.00	.00	2006.56	8562.00	2013.63	2016.23	2022.73	61.25	24.20	353.77	1094.01
	13600.000	75.00	.00	.00	2006.11	8562.00	2011.63	2014.64	2022.04	90.49	25.89	330.71	900.07
	13500.000	88.14	.00	.00	2003.07	8562.00	2008.12	2011.59	2020.88	122.94	28.67	298.66	772.20
	13400.000	36.00	2012.33	2030.07	2002.77	8562.00	2007.87	2011.28	2020.37	119.20	28.37	301.76	784.23
	13300.000	100.00	.00	.00	2002.29	8562.00	2007.63	2010.82	2018.90	101.73	26.93	317.90	848.90
	13200.000	80.00	.00	.00	2001.40	8562.00	2008.41	2011.07	2017.66	62.92	24.42	350.65	1079.36
	13100.000	211.13	.00	.00	1998.99	8562.00	2005.57	2008.66	2016.08	76.30	26.01	329.16	980.16
	13000.000	98.00	.00	.00	1993.90	8562.00	1999.37	2003.59	2014.63	135.47	31.35	273.11	735.63
	12900.000	33.00	2004.20	2020.90	1993.47	8562.00	1998.94	2003.13	2014.17	135.12	31.32	273.34	736.57
	12800.000	258.77	.00	.00	1991.35	8562.00	1997.22	2001.01	2010.45	108.68	29.19	293.32	821.30
	12700.000	405.00	.00	.00	1988.15	8562.00	1994.43	1997.81	2005.99	88.33	27.29	313.79	911.03
	12600.000	313.04	.00	.00	1985.63	8562.00	1992.02	1995.29	2003.18	83.60	26.80	319.47	936.40

12500.000	75.00	.00	.00	1983.70	8562.00	1988.64	1992.27	2002.16	133.05	29.51	290.17	742.28
12400.000	88.60	.00	.00	1983.11	8562.00	1988.20	1991.61	2000.75	120.02	28.44	301.11	781.55
12300.000	75.37	2012.00	2009.42	1982.84	8562.00	1988.02	999999.00	2000.07	112.96	27.87	307.26	805.58
12200.000	277.73	.00	.00	1978.83	8562.00	1985.83	1989.21	1997.26	80.31	27.13	315.59	955.42
12100.000	287.98	.00	.00	1974.60	8562.00	1981.92	1985.66	1994.70	88.79	28.68	298.51	908.62
12000.000	252.00	.00	.00	1970.97	8562.00	1979.62	1983.38	1992.53	82.23	28.84	296.92	944.19
11900.000	5.00	1990.99	1998.54	1970.88	8562.00	1979.52	1983.30	1992.48	82.64	28.89	296.36	941.86
11800.000	92.00	.00	.00	1969.57	8562.00	1977.96	1981.99	1991.62	89.27	29.66	288.68	906.18
11700.000	86.00	.00	.00	1968.25	8562.00	1976.45	1980.68	1990.76	95.50	30.36	282.04	876.16

1

16JUN04	14:15:51	PAGE	35
---------	----------	------	----

SECNO	XLCH	ELTRD	ELLC	ELMIN	Q	CWSEL	CRIWS	EG	10*KS	VCH	AREA	.01K
11600.000	16.00	1999.84	1996.89	1967.32	8562.00	1976.07	999999.00	1988.63	79.11	28.45	301.00	962.62
11500.000	215.00	.00	.00	1964.52	8562.00	1971.02	1975.37	1986.30	118.48	31.37	272.90	786.59
11400.000	100.00	1972.82	1990.52	1964.02	8562.00	1970.82	1974.87	1984.80	103.60	30.01	285.34	841.19
11300.000	243.55	.00	.00	1964.00	8562.00	1971.56	1974.47	1981.55	70.32	25.37	337.54	1021.00
11200.000	474.00	.00	.00	1962.00	8562.00	1970.67	1972.84	1978.17	44.87	21.97	389.73	1278.26
11100.000	430.53	.00	.00	1960.00	8562.00	1969.46	1971.55	1976.04	41.22	20.59	415.91	1333.56
11000.000	411.30	.00	.00	1960.00	8562.00	1967.93	1969.72	1974.06	49.05	19.87	430.93	1222.52
10900.000	392.70	.00	.00	1956.00	8562.00	1963.17	1965.63	1971.53	71.58	23.21	368.90	1012.03
10800.000	388.50	.00	.00	1952.00	8562.00	1958.60	1961.31	1968.15	99.91	24.80	345.24	856.57
10700.000	386.03	.00	.00	1948.00	8562.00	1954.71	1957.54	1964.32	98.15	24.88	344.11	864.25
10600.000	418.08	.00	.00	1942.00	8562.00	1949.31	1952.40	1960.10	98.12	26.36	324.77	864.34

1

16JUN04	14:15:51	PAGE	36
---------	----------	------	----

DCL1SUPX

SUMMARY PRINTOUT TABLE 150

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
* 15500.000	8562.00	2037.10	.00	.00	- .70	57.00	.00
* 15400.000	8562.00	2032.73	.00	-4.37	.00	77.42	166.19
* 15300.000	8562.00	2034.80	.00	2.07	.00	90.00	471.40
15250.000	8562.00	2033.38	.00	-1.42	.00	88.09	50.75
15200.000	8562.00	2032.37	.00	-1.00	.00	88.40	61.56
15150.000	8562.00	2031.48	.00	- .89	.00	87.65	112.23
* 15110.000	8562.00	2032.43	.00	.95	.00	65.00	200.00
15100.000	8562.00	2032.33	.00	- .10	.00	65.00	3.43
15050.000	8562.00	2030.79	.00	-1.63	.00	65.00	115.37
15000.000	8562.00	2029.81	.00	- .98	.00	65.00	62.42
14950.000	8562.00	2029.35	.00	- .46	.00	65.00	84.63
* 14900.000	8562.00	2029.21	.00	- .14	.00	65.00	52.69
14850.000	8562.00	2028.79	.00	- .42	.00	65.00	37.36
14800.000	8562.00	2027.08	.00	-1.71	.00	65.00	102.56
14750.000	8562.00	2026.43	.00	- .65	.00	60.00	99.50
14700.000	8562.00	2025.57	.00	- .85	.00	60.00	56.34
14600.000	8562.00	2025.60	.00	.03	.00	60.00	111.48
* 14550.000	8562.00	2024.79	.00	- .81	.00	60.00	20.00

14500.000	8562.00	2023.51	.00	-1.28	.00	60.00	40.00
14450.000	8562.00	2022.18	.00	-1.33	.00	60.00	50.00
14400.000	8562.00	2021.77	.00	-.41	.00	60.00	20.00
14300.000	8562.00	2021.98	.00	.21	.00	60.00	20.00
14240.000	8562.00	2021.54	.00	-.44	.00	60.00	20.00
14220.000	8562.00	2020.97	.00	-.56	.00	60.00	20.00

1

16JUN04 14:15:51

PAGE 37

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
14200.000	8562.00	2020.46	.00	-.51	.00	60.00	20.00
14100.000	8562.00	2020.54	.00	.08	.00	59.28	75.00
14000.000	8562.00	2017.86	.00	-2.68	.00	50.00	101.00
13900.000	8562.00	2017.03	.00	-.83	.00	50.00	57.00
13800.000	8562.00	2015.40	.00	-1.62	.00	50.00	300.00
13700.000	8562.00	2013.63	.00	-1.77	.00	50.00	306.00
13600.000	8562.00	2011.63	.00	-2.00	.00	69.75	75.00
13500.000	8562.00	2008.12	.00	-3.51	.00	68.23	88.14
13400.000	8562.00	2007.87	.00	-.25	.00	68.39	36.00
13300.000	8562.00	2007.63	.00	-.23	.00	69.05	100.00
13200.000	8562.00	2008.41	.00	.77	.00	50.00	80.00
13100.000	8562.00	2005.57	.00	-2.83	.00	50.00	211.13
13000.000	8562.00	1999.37	.00	-6.21	.00	50.00	98.00
12900.000	8562.00	1998.94	.00	-.43	.00	50.00	33.00
12800.000	8562.00	1997.22	.00	-1.72	.00	50.00	258.77
12700.000	8562.00	1994.43	.00	-2.79	.00	50.00	405.00
12600.000	8562.00	1992.02	.00	-2.40	.00	50.00	313.04
12500.000	8562.00	1988.64	.00	-3.38	.00	67.30	75.00
12400.000	8562.00	1988.20	.00	-.44	.00	68.38	88.60
12300.000	8562.00	1988.02	.00	-.18	.00	68.70	75.37
12200.000	8562.00	1985.83	.00	-2.19	.00	45.08	277.73
12100.000	8562.00	1981.92	.00	-3.91	.00	40.80	287.98
12000.000	8562.00	1979.62	.00	-2.30	.00	34.34	252.00
11900.000	8562.00	1979.52	.00	-.09	.00	34.30	5.00
11800.000	8562.00	1977.96	.00	-1.56	.00	34.40	92.00
11700.000	8562.00	1976.45	.00	-1.51	.00	34.40	86.00

1

16JUN04 14:15:51

PAGE 38

SECNO	Q	CWSEL	DIFWSP	DIFWSX	DIFKWS	TOPWID	XLCH
11600.000	8562.00	1976.07	.00	-.38	.00	34.40	16.00
11500.000	8562.00	1971.02	.00	-5.05	.00	42.00	215.00
11400.000	8562.00	1970.82	.00	-.19	.00	42.00	100.00
11300.000	8562.00	1971.56	.00	.73	.00	59.66	243.55
11200.000	8562.00	1970.67	.00	-.88	.00	59.02	474.00
11100.000	8562.00	1969.46	.00	-1.21	.00	66.36	430.53
11000.000	8562.00	1967.93	.00	-1.53	.00	85.47	411.30
10900.000	8562.00	1963.17	.00	-4.76	.00	76.48	392.70

10800.000	8562.00	1958.60	.00	-4.57	.00	84.87	388.50
10700.000	8562.00	1954.71	.00	-3.89	.00	82.60	386.03
10600.000	8562.00	1949.31	.00	-5.40	.00	70.72	418.08

1

16JUN04 14:15:51

PAGE 39

SUMMARY OF ERRORS AND SPECIAL NOTES

CAUTION SECNO= 15500.000 PROFILE= 1 CRITICAL DEPTH ASSUMED

WARNING SECNO= 15400.000 PROFILE= 1 CONVEYANCE CHANGE OUTSIDE ACCEPTABLE RANGE

CAUTION SECNO= 15300.000 PROFILE= 1 CRITICAL DEPTH ASSUMED

CAUTION SECNO= 15300.000 PROFILE= 1 PROBABLE MINIMUM SPECIFIC ENERGY

CAUTION SECNO= 15300.000 PROFILE= 1 20 TRIALS ATTEMPTED TO BALANCE WSEL

CAUTION SECNO= 15110.000 PROFILE= 1 CRITICAL DEPTH ASSUMED

CAUTION SECNO= 15110.000 PROFILE= 1 PROBABLE MINIMUM SPECIFIC ENERGY

CAUTION SECNO= 15110.000 PROFILE= 1 20 TRIALS ATTEMPTED TO BALANCE WSEL

CAUTION SECNO= 14900.000 PROFILE= 1 BRIDGE DROWNS U.S. PROFILE
NEW BACKWATER REQUIRED

CAUTION SECNO= 14550.000 PROFILE= 1 20 TRIALS ATTEMPTED TO BALANCE WSEL

[illegible]



Federal Emergency Management Agency

Washington, D.C. 20472

AUG 13 2003

CERTIFIED MAIL
RETURN RECEIPT REQUESTED

IN REPLY REFER TO:
Case No.: 03-09-0980X

The Honorable Mary J. Kincaid-Chauncey
Chair, Clark County Board
of Commissioners
500 South Grand Central Parkway
Las Vegas, NV 89155

Community: Clark County, NV
Community No.: 320003
Panels Affected: 32003C2562 E, 2566 E,
2567 E, 2568 E, 2569 E,
2580 E, 2583 E, 2585 E,
2590 E, and 2910 E

Effective Date of **AUG 13 2003**
This Revision:

102-I-A-C

Dear Ms. Kincaid-Chauncey:

This responds to a request that the Federal Emergency Management Agency (FEMA) revise the effective Flood Insurance Rate Map (FIRM) and Flood Insurance Study (FIS) report for Clark County, Nevada and Incorporated Areas, in accordance with Part 65 of the National Flood Insurance Program (NFIP) regulations. In a letter dated April 30, 2002, Mr. Kevin Eubanks, P.E., Assistant General Manager, Clark County Regional Flood Control District, requested that FEMA revise the FIRM and FIS report to show the effects of an updated floodplain delineation study based on a revised hydrologic analysis and a revised hydraulic analysis that incorporated more detailed topographic information and construction of the Lower Duck Creek Detention Basin to reflect existing watershed conditions along Duck Creek from approximately 300 feet east of Hollywood Boulevard to just downstream of Industrial Road and along Blue Diamond Wash – North Branch (North Branch) and Blue Diamond Wash – Middle Branch (Middle Branch) from their respective confluences with Duck Creek to the Union Pacific Railroad (UPRR). In addition, this request included revisions to Duck Creek Tributary from its confluence with Duck Creek to approximately 300 feet west of Interstate Highway 15 (I-15) and to Duck Creek South Channel (South Channel) from its confluence with Duck Creek to its divergence from Duck Creek. In response to Mr. Eubanks's request, we issued a Letter of Map Revision (LOMR) on April 7, 2003 (Case No. 02-09-913P). On the annotated FIRM panels attached to that LOMR, we inadvertently used an incorrect digital projection of the floodplain and floodway boundary delineations. We therefore issued a LOMR on April 21, 2003 (Case No. 03-09-0861X), with the proper revised FIRM panels. Subsequent to the April 21 LOMR, Mr. Michael Ludwig, P.E., Senior Designer, G. C. Wallace, Inc., informed us of discrepancies between the revised FIRM and the flood profiles. In addition, Mr. Ludwig provided survey data to show the exact low chord and roadway elevations to be used for the flood profiles. This LOMR revises and supersedes the April 21 LOMR.

All data required to complete our review of this request were submitted with letters from Mr. Eubanks and Mr. Ludwig.

We have completed our review of the submitted data and the flood data shown on the effective FIRM and in the effective FIS report. We have revised the FIRM and FIS report to modify the elevations, floodplain and floodway boundary delineations, and zone designations of the flood having a 1-percent chance of

being equaled or exceeded in any given year (base flood) along the revised reaches of Duck Creek, Duck Creek Tributary, South Channel, North Branch, and Middle Branch. The revision request renamed the reach of Duck Creek shown on the effective FIRM from approximately 300 feet downstream of Giles Street to just downstream of Industrial Road as Duck Creek Tributary, and the reach of Duck Creek Tributary shown on the effective FIRM from its confluence with Duck Creek to approximately 300 feet west of I-15 was renamed as Duck Creek.

As a result of the modifications along Duck Creek, the effective Special Flood Hazard Area (SFHA), the area that would be inundated by the base flood, designated Zone A, with no Base Flood Elevations (BFEs) determined, from approximately 300 feet upstream of U.S. Highway 95 to approximately 200 feet upstream of Pebble Road was redesignated Zone AE, with BFEs determined; a regulatory floodway was added from just upstream of Patrick Lane to approximately 200 feet upstream of Pebble Road; the width of the SFHA and the BFEs increased in some areas and decreased in other areas; and new BFEs were added. As a result of the modifications along North Branch, the effective SFHAs designated Zone A and Zone AO (Depth 1), an SFHA subject to shallow flooding with an average depth of 1 foot, from the confluence with Duck Creek to just downstream of Amigo Street were redesignated Zone AE, and a regulatory floodway was added; the effective SFHA designated Zone AO (Depth 1, Velocity 3), an SFHA subject to alluvial fan flooding with an average depth of 1 foot and flood velocity of 3 feet per second, from I-15 to the UPRR was redesignated Zone A; and the width of the SFHA and the BFEs decreased. As a result of the modifications along Middle Branch, the effective SFHAs designated Zone AO (Depth 1) and Zone A were redesignated Zone AE, and a regulatory floodway was added, from the confluence with Duck Creek to Amigo Street; from Amigo Street to approximately 1,600 feet upstream, the base flood is contained in a culvert; the effective SFHA designated Zone AO (Depth 1, Velocity 4) from I-15 to the UPRR was redesignated Zone AE; the width of the SFHA and the BFEs decreased; and SFHAs resulting from the Blue Diamond Wash – Middle Branch (Right Bank Overflow) and (Left Bank Overflow) designated Zone AE were added from I-15 to Blue Diamond Road and Valley View Boulevard respectively. As a result of the modifications along South Channel, the width of the SFHA and the BFEs increased, and the width of the regulatory floodway decreased.

The modifications are shown on the enclosed annotated copies of FIRM Panels 32003C2562 E, 32003C2566 E, 32003C2567 E, 32003C2568 E, 32003C2569 E, 32003C2580 E, 32003C2583 E, 32003C2585 E, 32003C2590 E, and 32003C2910 E; Profile Panels 01P, 02P, 14P, and 15P; and affected portions of the Summary of Discharges Table and Floodway Data Table. In addition, Profile Panels 03P and 04P were added for Middle Branch; Profile Panels 07P and 08P were added for Blue Diamond Wash – Middle Branch (Right Bank Overflow) and Blue Diamond Wash – Middle Branch (Left Bank Overflow), respectively; Profile Panels 03P and 04P for North Branch were renumbered as Profile Panels 09P and 10P, and Profile Panel 11P was added; Profile Panels 07P, 08P, and 09P for Duck Creek and Profile Panels 10P through 13P for Duck Creek Downstream of Blue Diamond were deleted; and Profile Panels 102P through 113P were added to the FIS report. This LOMR hereby revises the above-referenced panels of the effective FIRM and the affected portions of the FIS report, both dated September 27, 2002.

Because this revision request also affects the City of Henderson, a separate LOMR for that community was issued on the same date as this LOMR.

The modifications are effective as of the date shown above. The map panels as listed above and as modified by this letter will be used for all flood insurance policies and renewals issued for your community.

The following table is a partial listing of existing and modified BFEs:

Location	Existing BFE (feet)	Modified BFE (feet)
Duck Creek:		
At Stephanie Street	1,667*	1,656*
At Patrick Lane	None	1,886*
At Interstate Highway 215	None	2,074*
At Silverado Ranch Boulevard	2,229*	2,230*
At I-15	2,284*	2,282*
Duck Creek Tributary:		
At Gabriel Street	2,258*	2,260*
At Industrial Road	2,289*	2,292*
Duck Creek South Channel:		
At Silverado Ranch Boulevard	2,224*	2,225*
Blue Diamond Wash – North Branch:		
At Paradise Road	1 [#]	2,098*
At Las Vegas Boulevard	2,235*	2,230*
At UPRR	1 [#]	None
Blue Diamond Wash – Middle Branch:		
At Vision Street	1 [#]	2,114*
At Las Vegas Boulevard	2,240*	2,238*
At I-15	2,268*	2,264*
At Industrial Road	1 [#]	2,292*
At UPRR	1 [#]	2,428*
Blue Diamond Wash – Middle Branch (Right Bank Overflow):		
At Industrial Road	1 [#]	2,277*
Blue Diamond Wash – Middle Branch (Left Bank Overflow):		
At Industrial Road	None	2,276*

*Referenced to the North American Vertical Datum, rounded to the nearest whole foot

[#]Depth in feet above ground, rounded to the nearest whole foot

Public notification of the proposed modified BFEs in the April 21 LOMR was given in the *Las Vegas Review-Journal* on May 1 and May 8, 2003, and a notice of the changes will be published in the *Federal Register*. The 90-day appeal period for any interested party to request that FEMA reconsider the determination made by the April 21 LOMR ended on August 6, 2003. FEMA received no valid requests for changes to the modified BFEs. Because the BFEs were not modified from those in the April 21 LOMR, public notification of the proposed modified BFEs will not be made for this LOMR.

Because this LOMR will not be printed and distributed to primary users, such as local insurance agents and mortgage lenders, your community will serve as a repository for these new data. We encourage you to disseminate the information reflected by this LOMR throughout the community, so that interested persons, such as property owners, local insurance agents, and mortgage lenders, may benefit from the information. We also encourage you to prepare a related article for publication in your community's local newspaper. This article should describe the assistance that officials of your community will give to interested persons by providing these data and interpreting the NFIP maps.

We will not physically revise and republish the FIRM and FIS report for your community to reflect the modifications made by this LOMR at this time. When changes to the previously cited FIRM panels and FIS report warrant physical revision and republication in the future, we will incorporate the modifications made by this LOMR at that time.

The floodway is provided to your community as a tool to regulate floodplain development. Therefore, the floodway modifications described in this LOMR, while acceptable to FEMA, must also be acceptable to your community and adopted by appropriate community action, as specified in Paragraph 60.3(d) of the NFIP regulations.

This LOMR is based on minimum floodplain management criteria established under the NFIP. Your community is responsible for approving all floodplain development and for ensuring all necessary permits required by Federal or State law have been received. State, county, and community officials, based on knowledge of local conditions and in the interest of safety, may set higher standards for construction in the SFHA. If the State, county, or community has adopted more restrictive or comprehensive floodplain management criteria, these criteria take precedence over the minimum NFIP criteria.


This determination has been made pursuant to Section 206 of the Flood Disaster Protection Act of 1973 (Public Law 93-234) and is in accordance with the National Flood Insurance Act of 1968, as amended (Title XIII of the Housing and Urban Development Act of 1968, Public Law 90-448), 42 U.S.C. 4001-4128, and 44 CFR Part 65. Pursuant to Section 1361 of the National Flood Insurance Act of 1968, as amended, communities participating in the NFIP are required to adopt and enforce floodplain management regulations that meet or exceed minimum NFIP criteria. These criteria are the minimum and do not supersede any State or local requirements of a more stringent nature. This includes adoption of the effective FIRM to which the regulations apply and the modifications described in this LOMR. Our records show that your community has met this requirement.

A Consultation Coordination Officer (CCO) has been designated to assist your community. The CCO will be the primary liaison between your community and FEMA. For information regarding your CCO, please contact:

Mr. Jack Eldridge
Chief, National Flood Insurance Program Branch
Federal Emergency Management Agency, Region IX
1111 Broadway Street, Suite 1200
Oakland, CA 94607-4052
(510) 627-7184

If you have any questions regarding floodplain management regulations for your community or the NFIP in general, please call the CCO for your community at the telephone number cited above. If you have any questions regarding this LOMR, please call our Map Assistance Center, toll free, at 1-877-FEMA MAP (1-877-336-2627).

Sincerely,



Max H. Yuan, P.E., Project Engineer
Hazard Study Branch
Emergency Preparedness
and Response Directorate

For: Doug Bellomo, P.E., Acting Chief
Hazard Study Branch
Emergency Preparedness
and Response Directorate

Enclosures

cc: The Honorable James Gibson
Mayor, City of Henderson

Mr. Kevin Eubanks, P.E.
Assistant General Manager
Clark County Regional Flood
Control District

Mr. Curt Chandler, P.E.
Land Development Manager
Department of Public Works
City of Henderson

Mr. Robert Thompson, P.E.
Department of Public Works
Clark County

Mr. Jerry E. Pruitt, P.E.
Vice President
G. C. Wallace, Inc.



Federal Emergency Management Agency

Washington, D.C. 20472

AUG 13 2003

CERTIFIED MAIL
RETURN RECEIPT REQUESTED

IN REPLY REFER TO:
Case No.: 03-09-0980X

The Honorable James Gibson
Mayor, City of Henderson
240 South Water Street
Henderson, NV 89015

Community: City of Henderson, NV
Community No.: 320005
Panels Affected: 32003C2580 E and 2590 E
Effective Date of **AUG 13 2003**
This Revision:

102-I-A-C

Dear Mayor Gibson:

This responds to a request that the Federal Emergency Management Agency (FEMA) revise the effective Flood Insurance Rate Map (FIRM) and Flood Insurance Study (FIS) report for Clark County, Nevada and Incorporated Areas (the effective FIRM and FIS report for your community), in accordance with Part 65 of the National Flood Insurance Program (NFIP) regulations. In a letter dated April 30, 2002, Mr. Kevin Eubanks, P.E., Assistant General Manager, Clark County Regional Flood Control District, requested that FEMA revise the FIRM and FIS report to show the effects of an updated floodplain delineation study based on a revised hydrologic analysis and a revised hydraulic analysis that incorporated more detailed topographic information and the Lower Duck Creek Detention Basin to reflect existing watershed conditions along Duck Creek from approximately 300 feet east of Hollywood Boulevard to just downstream of Industrial Road and along Blue Diamond Wash – North and Middle Branches from their respective confluences with Duck Creek to the Union Pacific Railroad. In addition, this request included revisions to Duck Creek Tributary from its confluence with Duck Creek to approximately 300 feet west of Interstate Highway 15 and to Duck Creek South Channel from its confluence with Duck Creek to its divergence from Duck Creek. In response to Mr. Eubanks's request, we issued a Letter of Map Revision (LOMR) on April 7, 2003 (Case No. 02-09-913P). On the annotated FIRM panels attached to that LOMR, we inadvertently used an incorrect digital projection of the floodplain and floodway boundary delineations. We therefore issued a LOMR on April 21, 2003 (Case No. 03-09-0861X), with the proper revised FIRM panels. Subsequent to the April 21 LOMR, Mr. Michael Ludwig, P.E., Senior Designer, G. C. Wallace, Inc., informed us of discrepancies between the revised FIRM and the flood profiles. In addition, Mr. Ludwig provided survey data to show the exact low chord and roadway elevations to be used for the flood profiles. This LOMR revises and supersedes the April 21 LOMR.

All data required to complete our review of this request were submitted with letters from Mr. Eubanks and Mr. Ludwig.

We have completed our review of the submitted data and the flood data shown on the effective FIRM and in the effective FIS report. We have revised the FIRM and FIS report to modify the elevations, floodplain and floodway boundary delineations, and zone designations of the flood having a 1-percent chance of being equaled or exceeded in any given year (base flood) along Duck Creek. As a result of the modifications, the effective Special Flood Hazard Area (SFHA), the area that would be inundated by the base flood, designated Zone A, with no Base Flood Elevations (BFEs) determined, along Duck Creek from Patrick Lane to Pecos Road was redesignated Zone AE, with BFEs determined; a regulatory floodway was added; and the width of the SFHA decreased. The modifications are shown on the enclosed annotated copies of FIRM Panels 32003C2580 E and 32003C2590 E, Profile Panels 106P and 107P, and affected portions of the Summary of Discharges Table and Floodway Data Table. In addition, Profile Panels 07P, 08P, and 09P for Duck Creek and Profile Panels 10P through 13P for Duck Creek Downstream of Blue Diamond were deleted, and Profile Panels 102P through 113P were added to the FIS report. This LOMR hereby revises the above-referenced panels of the effective FIRM and the affected portions of the FIS report, both dated September 27, 2002.

Because this revision request also affects the unincorporated areas of Clark County, a separate LOMR for that community was issued on the same date as this LOMR.

The modifications are effective as of the date shown above. The map panels as listed above and as modified by this letter will be used for all flood insurance policies and renewals issued for your community.

The following table is a partial listing of existing and modified BFEs:

Location	Existing BFE (feet)*	Modified BFE (feet)*
Duck Creek:		
At Sunset Road	None	1,928
Approximately 1,400 feet downstream of Pecos Road	None	1,972

*Referenced to the North American Vertical Datum, rounded to the nearest whole foot

Public notification of the proposed modified BFEs in the April 21 LOMR was given in the *Las Vegas Review-Journal* on May 1 and May 8, 2003, and a notice of the changes will be published in the *Federal Register*. The 90-day appeal period for any interested party to request that FEMA reconsider the determination made by the April 21 LOMR ended on August 6, 2003. FEMA received no valid requests for changes to the modified BFEs. Because the BFEs were not modified from those in the April 21 LOMR, public notification of the proposed modified BFEs will not be made for this LOMR.

Because this LOMR will not be printed and distributed to primary users, such as local insurance agents and mortgage lenders, your community will serve as a repository for these new data. We encourage you to

disseminate the information reflected by this LOMR throughout the community, so that interested persons, such as property owners, local insurance agents, and mortgage lenders, may benefit from the information. We also encourage you to prepare a related article for publication in your community's local newspaper. This article should describe the assistance that officials of your community will give to interested persons by providing these data and interpreting the NFIP maps.

We will not physically revise and republish the FIRM and FIS report for your community to reflect the modifications made by this LOMR at this time. When changes to the previously cited FIRM panels and FIS report warrant physical revision and republication in the future, we will incorporate the modifications made by this LOMR at that time.

The floodway is provided to your community as a tool to regulate floodplain development. Therefore, the floodway modifications described in this LOMR, while acceptable to FEMA, must also be acceptable to your community and adopted by appropriate community action, as specified in Paragraph 60.3(d) of the NFIP regulations.

This LOMR is based on minimum floodplain management criteria established under the NFIP. Your community is responsible for approving all floodplain development and for ensuring all necessary permits required by Federal or State law have been received. State, county, and community officials, based on knowledge of local conditions and in the interest of safety, may set higher standards for construction in the SFHA. If the State, county, or community has adopted more restrictive or comprehensive floodplain management criteria, these criteria take precedence over the minimum NFIP criteria.

This determination has been made pursuant to Section 206 of the Flood Disaster Protection Act of 1973 (Public Law 93-234) and is in accordance with the National Flood Insurance Act of 1968, as amended (Title XIII of the Housing and Urban Development Act of 1968, Public Law 90-448), 42 U.S.C. 4001-4128, and 44 CFR Part 65. Pursuant to Section 1361 of the National Flood Insurance Act of 1968, as amended, communities participating in the NFIP are required to adopt and enforce floodplain management regulations that meet or exceed minimum NFIP criteria. These criteria are the minimum and do not supersede any State or local requirements of a more stringent nature. This includes adoption of the effective FIRM to which the regulations apply and the modifications described in this LOMR. Our records show that your community has met this requirement.

A Consultation Coordination Officer (CCO) has been designated to assist your community. The CCO will be the primary liaison between your community and FEMA. For information regarding your CCO, please contact:

Mr. Jack Eldridge
Chief, National Flood Insurance Program Branch
Federal Emergency Management Agency, Region IX
1111 Broadway Street, Suite 1200
Oakland, CA 94607-4052
(510) 627-7184

If you have any questions regarding floodplain management regulations for your community or the NFIP in general, please call the CCO for your community at the telephone number cited above. If you have any questions regarding this LOMR, please call our Map Assistance Center, toll free, at 1-877-FEMA MAP (1-877-336-2627).

Sincerely,



Max H. Yuan, P.E., Project Engineer
Hazard Study Branch
Emergency Preparedness
and Response Directorate

For: Doug Bellomo, P.E., Acting Chief
Hazard Study Branch
Emergency Preparedness
and Response Directorate

Enclosures

cc: The Honorable Mary J. Kincaid-Chauncey
Chair, Clark County Board
of Commissioners

Mr. Kevin Eubanks, P.E.
Assistant General Manager
Clark County Regional Flood
Control District

Mr. Curt Chandler, P.E.
Land Development Manager
Department of Public Works
City of Henderson

Mr. Robert Thompson, P.E.
Department of Public Works
Clark County

Mr. Jerry E. Pruitt, P.E.
Vice President
G. C. Wallace, Inc.

FLOODING SOURCE			FLOODWAY		BASE FLOOD WATER-SURFACE ELEVATION			
CROSS SECTION	DISTANCE ¹	WIDTH (FEET)	SECTION AREA (SQUARE FEET)	MEAN VELOCITY (FEET PER SECOND)	REGULATORY	WITHOUT FLOODWAY	WITH FLOODWAY	INCREASE
Duck Creek A-W ²					(FEET NAVD)			
X	27449	93	730	11.7	1,891.5	1,891.5	1,891.6	0.1
Y	28218	88	582	14.7	1,913.9	1,913.9	1,914.2	0.3
Z	29108	84	705	12.2	1,926.3	1,926.3	1,926.7	0.4
AA	29805	103	951	9.0	1,931.2	1,931.2	1,931.7	0.5
AB	30196	105	1105	7.7	1,934.5	1,934.5	1,935.2	0.7
AC	31113	131	1338	6.4	1,939.8	1,939.8	1,940.7	0.9
AD	32111	325	1090	7.9	1,949.0	1,949.0	1,949.0	0.0
AE	32908	83	345	24.8	1,957.1	1,957.1	1,957.1	0.0
AF	33682	77	374	22.9	1,965.6	1,965.6	1,965.6	0.0
AG	34486	80	552	15.5	1,973.7	1,973.7	1,973.7	0.0
AH	35391	61	366	21.0	1,974.2	1,974.2	1,974.5	0.3
AI	35949	34	293	22.4	1,977.4	1,977.4	1,978.4	1.0
AJ	36400	41	228	24.4	1,982.3	1,982.3	1,982.6	0.3
AK	37205	50	244	22.8	1,992.9	1,992.9	1,992.9	0.0
AL	37923	50	220	25.3	1,998.2	1,998.2	1,998.2	0.0
AM	38704	64	223	25.0	2,009.1	2,009.1	2,009.1	0.0
AN	39209	50	253	22.0	2,015.8	2,015.8	2,015.9	0.1
AO	39742	60	243	22.8	2,020.6	2,020.6	2,020.7	0.1
AP	40418	259	1449	5.8	2,036.0	2,036.0	2,036.3	0.3
AQ	41089	103	775	11.0	2,038.3	2,038.3	2,038.6	0.3
AR	41726	100	547	15.7	2,040.2	2,040.2	2,040.2	0.0
AS	42184	82	569	15.0	2,043.1	2,043.1	2,043.1	0.0
AT	42839	80	566	15.1	2,047.4	2,047.4	2,047.4	0.0
AU	44390	501	2241	3.8	2,058.0	2,058.0	2,058.9	0.9
AV	44840	308	1072	8.0	2,060.5	2,060.5	2,060.8	0.3

¹Feet Above Confluence With Las Vegas Wash ²No F

odway Computed

T
A
B
L
E

5

FEDERAL EMERGENCY MANAGE

CLARK COUNTY
AND INCORPORATE

ENT AGENCY

IV
AREAS

REVISED TO
REFLECT LOMR
DATED

FLOODWAY DATA

DUCK CREEK

FLOODING SOURCE		FLOODWAY			WATER		BASE FLOOD SURFACE ELEVATION		
CROSS SECTION	DISTANCE ¹	WIDTH (FEET)	SECTION AREA (SQUARE FEET)	MEAN VELOCITY (FEET PER SECOND)	REGULATORY	W/FLO	OUT JWAY	WITH FLOODWAY	INCREASE
							(FEET NAVD)		
Duck Creek (Continued)									
AW	45751	150	1110	7.7	2,066.8	2,	6.8	2,066.8	0.0
AX	46476	129	625	13.7	2,071.5	2,	1.5	2,071.5	0.0
AY	47165	120	463	18.5	2,072.7	2,	2.7	2,072.7	0.0
AZ	47978	114	636	13.5	2,080.9	2,	0.9	2,080.9	0.0
BA	48773	89	387	21.9	2,081.3	2,	1.3	2,081.7	0.4
BB	49564	90	307	27.6	2,088.2	2,	8.2	2,088.2	0.0
BC	50202	97	251	33.7	2,097.1	2,	7.1	2,097.1	0.0
BD	50769	45	236	31.7	2,108.7	2,	8.7	2,108.7	0.0
BE	51547	46	258	29.0	2,120.9	2,	0.9	2,121.0	0.1
BF	52338	70	247	30.3	2,128.2	2,	8.2	2,128.6	0.4
BG	53161	75	253	29.6	2,145.4	2,	5.4	2,145.4	0.0
BH	53934	83	375	19.9	2,155.6	2,	5.6	2,155.6	0.0
BI	54735	83	519	14.4	2,160.7	2,	0.7	2,160.7	0.0
BJ	55536	91	519	14.4	2,161.6	2,	1.6	2,161.6	0.0
BK	56328	97	359	20.9	2,159.4	2,	9.4	2,160.0	0.6
BL	57099	94	287	26.1	2,165.1	2,	5.1	2,165.1	0.0
BM	57902	75	354	21.1	2,175.5	2,	5.5	2,175.5	0.0
BN	58582	69	435	17.2	2,180.3	2,	0.3	2,180.3	0.0
BO	59067	76	358	20.9	2,180.3	2,	0.3	2,180.3	0.0
BP	59675	120	468	16.0	2,184.6	2,	4.6	2,184.6	0.0
BQ	63045	226	520	8.0	2,220.7	2,	0.7	2,220.7	0.0
BR	63833	222	490	8.5	2,223.9	2,	3.9	2,224.6	0.7

¹Feet Above Confluence With Las Vegas Wash

T
A
B
L
E

5

FEDERAL EMERGENCY MANAGEMENT AGENCY

CLARK COUNTY, NV
AND INCORPORATED AREAS

REVISED TO
REFLECT LOMR
DATED

FLOODWAY DATA

DUCK CREEK

FLOODING SOURCE			FLOODWAY		BASE FLOOD WATER-SURFACE ELEVATION			
CROSS SECTION	DISTANCE ¹	WIDTH (FEET)	SECTION AREA (SQUARE FEET)	MEAN VELOCITY (FEET PER SECOND)	REGULATORY	WITHOUT FLOODWAY	WITH FLOODWAY	INCREASE
(FEET NAVD)								
Duck Creek (Continued)								
BS	65967	262	1022	6.3	2,238.3	2,238.3	2,239.1	0.8
BT	66685	440	1245	5.2	2,243.2	2,243.2	2,243.9	0.7
BU	69540	190	453	4.0	2,264.2	2,264.2	2,264.9	0.7
BV	70200	268	472	3.8	2,270.0	2,270.0	2,270.7	0.7
BW	70856	180	275	6.6	2,274.0	2,274.0	2,274.7	0.7
BX	71675	62	183	7.2	2,281.0	2,281.0	2,281.1	0.1

¹Feet Above Confluence With Las Vegas Wash

T A B L E 5	FEDERAL EMERGENCY MANAGEMENT AGENCY		FLOODWAY DATA	
	CLARK COUNTY AND INCORPORATED AREAS		DUCK CREEK	

REVISED TO
REFLECT LGAR
DATED

FLOODING SOURCE		FLOODWAY			BASE FLOOD WATER-SURFACE ELEVATION			
CROSS SECTION	DISTANCE ¹	WIDTH (FEET)	SECTION AREA (SQUARE FEET)	MEAN VELOCITY (FEET PER SECOND)	REGULATORY	WITHOUT FLOODWAY	WITH FLOODWAY	INCREASE
					(FEET NAVD)			
Blue Diamond Wash-North Branch								
A	100	30	54	23.8	2,081.0	2,081.0	2,081.0	0.0
B	895	10	60	21.5	2,089.8	2,089.8	2,089.8	0.0
C	1395	10	80	16.1	2,097.2	2,097.2	2,097.2	0.0
D	2175	10	71	18.3	2,101.6	2,101.6	2,101.6	0.0
E	2968	10	78	16.5	2,109.0	2,109.0	2,109.0	0.0
F	3638	10	70	18.4	2,113.8	2,113.8	2,113.8	0.0
G	4583	23	56	23.1	2,120.7	2,120.7	2,120.7	0.0
H	5076	116	386	3.3	2,137.2	2,137.2	2,137.2	0.0
I	5951	32	129	10.0	2,152.7	2,152.7	2,153.6	0.9
J	6651	90	167	7.7	2,162.7	2,162.7	2,162.9	0.2
K	7571	42	129	10.0	2,172.1	2,172.1	2,172.1	0.0
L	8331	160	202	6.4	2,183.5	2,183.5	2,183.5	0.0
M	9101	92	179	7.2	2,192.0	2,192.0	2,192.1	0.1
N	9911	50	162	8.0	2,199.0	2,199.0	2,199.9	0.9
O	10691	98	236	5.5	2,211.9	2,211.9	2,212.7	0.8
P	11487	49	75	17.2	2,217.1	2,217.1	2,217.1	0.0
Q	12100	45	55	23.5	2,220.9	2,220.9	2,220.9	0.0
R	12680	80	217	6.0	2,235.0	2,235.0	2,235.8	0.8
S	13490	68	210	6.1	2,244.7	2,244.7	2,245.6	0.9
T	14270	41	130	9.9	2,253.2	2,253.2	2,253.8	0.6
U	15060	32	119	10.8	2,262.3	2,262.3	2,262.9	0.6

¹Feet Above Confluence With Duck Creek

T A B L E 5	FEDERAL EMERGENCY MANAGEMENT AGENCY		FLOODWAY DATA	
	CLARK COUNTY, NV AND INCORPORATED AREAS		BLUE DIAMOND WASH-NORTH BRANCH	

REVISED TO
REFLECT LOMR
DATED

FLOODING SOURCE		FLOODWAY			BASE FLOOD WATER-SURFACE ELEVATION			
CROSS SECTION	DISTANCE ¹	WIDTH (FEET)	SECTION AREA (SQUARE FEET)	MEAN VELOCITY (FEET PER SECOND)	REGULATORY	WITHOUT FLOODWAY	WITH FLOODWAY	INCREASE
(FEET NAVD)								
Blue Diamond Wash-Middle Branch								
A	120	40	65	22.6	2,103.9	2,103.9	2,103.9	0.0
B	818	40	63	23.3	2,114.5	2,114.5	2,114.5	0.0
C	1208	40	68	21.6	2,121.6	2,121.6	2,121.6	0.0
D	1878	40	56	26.3	2,130.4	2,130.4	2,130.5	0.0
E	2458	40	78	18.9	2,147.7	2,147.7	2,147.7	0.0
F	3943	95	93	15.8	2,171.4	2,171.4	2,171.4	0.0
G	4543	81	174	8.4	2,187.8	2,187.8	2,188.3	0.5
H	4843	55	139	10.5	2,191.9	2,191.9	2,191.9	0.0
I	5603	175	210	6.9	2,200.2	2,200.2	2,200.2	0.0
J	6263	140	252	5.8	2,209.2	2,209.2	2,209.2	0.0
K	6663	190	253	5.8	2,213.0	2,213.0	2,213.0	0.0
L	7583	170	205	7.1	2,221.0	2,221.0	2,221.0	0.0
M	8353	155	289	5.1	2,228.8	2,228.8	2,228.8	0.0
N	8813	170	415	3.5	2,234.4	2,234.4	2,235.1	0.7
O	9500	98	393	3.7	2,242.1	2,242.1	2,242.1	0.0
P	10193	60	208	7.0	2,247.4	2,247.4	2,248.2	0.8
Q	10843	180	416	3.5	2,252.7	2,252.7	2,253.4	0.7
R	11798	59	157	9.3	2,263.5	2,263.5	2,264.0	0.5

¹Feet Above Confluence With Duck Creek

T A B L E 5	FEDERAL EMERGENCY MANAGEMENT AGENCY		FLOODWAY DATA	
	CLARK COUNTY, NV AND INCORPORATED AREAS		BLUE DIAMOND WASH-MIDDLE BRANCH	

REVISED TO
REFLECT LSHR
DATED

FLOODING SOURCE			FLOODWAY		BASE FLOOD WATER-SURFACE ELEVATION			
CROSS SECTION	DISTANCE	WIDTH (FEET)	SECTION AREA (SQUARE FEET)	MEAN VELOCITY (FEET PER SECOND)	REGULATORY	WITHOUT FLOODWAY	WITH FLOODWAY	INCREASE
(FEET NAVD)								
DUCK CREEK TRIBUTARY								
A	1000 ¹	409	1035	4.9	2,255.3	2,255.3	2,255.8	0.5
B	1890 ¹	449	851	6.0	2,263.4	2,263.4	2,264.4	1.0
C	2670 ¹	510	1067	4.8	2,273.2	2,273.2	2,273.6	0.4
D	3251 ¹	950	927	5.5	2,288.2	2,288.2	2,288.2	0.0
E	4280 ¹	823	1332	7.1	2,292.6	2,292.6	2,293.4	0.8
DUCK CREEK - SOUTH CHANNEL								
A	230 ²	102	287	8.1	2,210.4	2,210.4	2,210.4	0.0
B	1030 ²	99	255	9.1	2,216.4	2,216.4	2,217.0	0.6
C	1840 ²	127	282	8.2	2,222.2	2,222.2	2,222.7	0.5
D	2330 ²	375	566	4.1	2,227.5	2,227.5	2,228.3	0.8

¹Feet Above Confluence With Duck Creek

²Feet Above Lower Duck Creek Detention Basin

T
A
B
L
E

5

FEDERAL EMERGENCY MANAGEMENT AGENCY
CLARK COUNTY
AND INCORPORATED AREAS

FLOODWAY DATA

DUCK CREEK TRIBUTARY-
DUCK CREEK-SOUTH CHANNEL.

REVISED TO
REFLECT
DATED

Table 3. Summary of Discharges

<u>Flooding Source and Location</u>	<u>Drainage Area (Square Miles)</u>	<u>Peak Discharges</u>		<u>ubic Feet per Second)</u>	
		<u>10-Year</u>	<u>50-Year</u>	<u>100-Year</u>	<u>500-Year</u>
Alluvial Fan In Eastern Henderson	5.54	370	2,200	3,600	-- ¹
Alluvial Fan In Western Henderson	76.0	1,490	13,300	23,370	-- ¹
Abbott Wash At Interstate 15	7.1	1,050	1,940	2,340	3,690
Blue Diamond Fan At Apex	69.5	2,010	8,800	14,820	42,550
Bridge Canyon Wash At Apex	7.3	650	2,680	4,430	12,240
Colorado River At Laughlin	169,300	-- ¹	-- ¹	40,000 ²	-- ¹
Dripping Springs Wash At Apex	4.5	460	1,910	3,150	8,710
Duck Creek At Interstate 15	-- ³	-- ¹	-- ¹	1,326	-- ¹
Upstream of Lower Duck Creek Detention Basin	119.8	-- ¹	-- ¹	6,470	-- ¹
At Mountain Vista Avenue	158.5	-- ¹	-- ¹	8,562	-- ¹
At Boulder Highway	164.8	-- ¹	-- ¹	8,562	-- ¹
Duck Creek Tributary At Interstate 15	-- ³	-- ¹	-- ¹	5,100	-- ¹

¹Discharge not available²Established by the Colorado River Floodway Protection Act, Public Law 99-450³Flow affected by upstream overflows, diversions, or obstructions; drainage area does not apply

Revised data

REVISED TO
REFLECT LOMR
DATED

Table 3. Summary of Discharges (Cont'd)

Flooding Source and Location	Drainage Area (Square Miles)	Peak Discharges (Cubic Feet per Second)			
		10-Year	50-Year	100-Year	500-Year
Georgia Avenue Wash					
At Buchanan Boulevard	1.98	263	781	1,285	4,300
At Mendota Drive	0.95	177	459	727	2,000
At Cross Section E	0.45	68	189	310	1,000
Hemenway Wash					
At Cross Section C	2.86	290	635	815	1,380
At Cross Section E	1.06	80	195	260	420
Hiko Springs Wash					
At Apex	17.9	1,220	5,070	8,370	23,130
Las Vegas Creek					
At Las Vegas Boulevard	13	640	1,280	1,570	2,420
At Confluence with Las Vegas Wash	14	660	1,300	1,600	2,450
Las Vegas Wash					
At Carey Avenue ¹	836	3,050	8,750	11,800	21,400
At Charleston Boulevard	858	3,180	9,000	12,100	21,800
At Losee Road	568	3,960	7,300	8,820	17,000
Below Union Pacific Railroad	-- ²	2,100	2,330	2,440	2,700
Below Interstate 15	-- ²	2,100	2,330	2,370	3,150
Below Confluence with Middle Overflow Area	-- ²	2,720	3,040	3,120	4,500
Below East Cheyenne Avenue	-- ²	2,300	2,560	2,610	3,500
Below Confluence with Unnamed Tributary	-- ²	3,940	7,580	9,220	17,200
Below Las Vegas Boulevard	-- ²	3,940	6,400	6,660	9,300
Below Cutoff Channel	-- ²	3,940	6,530	6,860	10,700
Below Carey Avenue	-- ²	3,940	6,530	6,860	9,700
Below Lake Mead Boulevard	-- ²	3,940	5,500	5,710	7,250
Middle Branch Blue Diamond Wash					
At Union Pacific Railroad	-- ²	-- ³	-- ³	1,961	-- ³
At Interstate 15	97.5	-- ³	-- ³	1,462	-- ³

¹Located outside Corporate Limits²Flow affected by upstream overflows, diversions, or obstructions; drainage area does not apply³Discharge not available

Revised data

**REVISED TO
REFLECT LOMR
DATED**

Table 3. Summary of Discharges (Cont'd)

<u>Flooding Source and Location</u>	<u>Drainage Area (Square Miles)</u>	<u>Peak Discharges (Cubic Feet per Second)</u>			
		<u>10-Year</u>	<u>50-Year</u>	<u>100-Year</u>	<u>500-Year</u>
Muddy River					
At Cooper Avenue	4,035	5,250	14,750	21,300	45,900
Downstream of Wells Siding	3,950	5,270	14,800	21,400	45,500
Upstream of Confluence with Meadow Valley Wash	1,360	3,620	10,900	16,000	34,400
North Branch Blue Diamond Wash					
At Union Pacific Railroad	-- ²	-- ¹	-- ¹	244	-- ¹
At Interstate 15	7.8	-- ¹	-- ¹	1,290	-- ¹
Revised data 					
Overton Wash					
At Upstream Limit of Detailed Study	21.7	2,170	4,510	5,680	8,200
Pulsifer Wash					
At Interstate 15	4.9	930	1,730	2,070	3,230
Southwest Unnamed Wash					
At Apex	3.9	260	1,070	1,770	4,890
Tropicana Wash - Central Branch					
At Flamingo Wash	20.1	-- ¹	-- ¹	5,300	-- ¹
Upstream of Airport Wash	12.1	-- ¹	-- ¹	3,320	-- ¹
Downstream of Koval Road	11.0	-- ¹	-- ¹	3,320	-- ¹
Interstate 15 to 600 feet downstream of Union Pacific Railroad	8.9	-- ¹	-- ¹	800	-- ¹
Just downstream of Union Pacific Railroad	8.1	-- ¹	-- ¹	710	-- ¹

¹Discharge Not Available²Flow affected by upstream overflows, diversions, or obstructions; drainage area does not apply

REVISED TO
REFLECT LOMR
DATED

GENERAL				FLOODPLAIN		FLOODWAY	
HEC-2 XS	STREAM NAME	HEC-2 MODEL	FLOW REGIME	Q (CFS)	WSE (FT)	Q (CFS)	WSE (FT)
10300	DUCK CREEK	DCL1SUBC	SUB	8562	1938.0	8562	1938.8
10400	DUCK CREEK	DCL1SUBC	SUB	8562	1937.6	8562	1938.6
10500	DUCK CREEK	DCL1SUBC	SUB	8562	1946.6	8562	1945.7
10600	DUCK CREEK	DCL1SPRC	SUPER	8562	1949.3	8562	1949.3
10700	DUCK CREEK	DCL1SPRC	SUPER	8562	1954.7	8562	1954.7
10800	DUCK CREEK	DCL1SPRC	SUPER	8562	1958.6	8562	1958.6
10900	DUCK CREEK	DCL1SPRC	SUPER	8562	1963.2	8562	1963.2
11000	DUCK CREEK	DCL1SPRC	SUPER	8562	1968.2	8562	1968.2
11100	DUCK CREEK	DCL1SPRC	SUPER	8562	1971.3	8562	1971.3
11200	DUCK CREEK	DCL1SPRC	SUPER	7820	1970.8	7820	1970.9
11300	DUCK CREEK	DCL1SPRC	SUPER	7700	1971.8	7700	1972.1
11400	DUCK CREEK	DCL1SPRC	SUPER	7700	1971.0	7700	1971.4
11500	DUCK CREEK	DCL1SPRC	SUPER	7700	1971.3	7700	1971.6
11600	DUCK CREEK	DCL1SPRC	SUPER	6562	1975.0	6562	1976.0
11700	DUCK CREEK	DCL1SPRC	SUPER	6562	1975.5	6562	1975.6
11800	DUCK CREEK	DCL1SPRC	SUPER	6562	1977.1	6562	1977.3
11900	DUCK CREEK	DCL1SPRC	SUPER	6562	1978.8	6562	1979.3
12000	DUCK CREEK	DCL1SPRC	SUPER	6562	1978.9	6562	1979.4
12100	DUCK CREEK	DCL1SPRC	SUPER	5562	1979.9	5562	1980.2
12200	DUCK CREEK	DCL1SPRC	SUPER	5562	1984.0	5562	1984.7
12300	DUCK CREEK	DCL1SPRC	SUPER	5562	1986.9	5562	1987.9
12400	DUCK CREEK	DCL1SPRC	SUPER	5562	1987.1	5562	1987.1
12500	DUCK CREEK	DCL1SPRC	SUPER	5562	1987.5	5562	1987.5
12600	DUCK CREEK	DCL1SPRC	SUPER	5562	1990.5	5562	1990.5
12700	DUCK CREEK	DCL1SPRC	SUPER	5562	1993.0	5562	1993.0
12800	DUCK CREEK	DCL1SPRC	SUPER	5562	1995.8	5562	1995.8
12900	DUCK CREEK	DCL1SPRC	SUPER	5562	1997.4	5562	1997.4
13000	DUCK CREEK	DCL1SPRC	SUPER	5562	1997.8	5562	1997.8
13100	DUCK CREEK	DCL1SPRC	SUPER	5562	2003.8	5562	2003.8
13200	DUCK CREEK	DCL1SPRC	SUPER	5562	2006.5	5562	2006.5
13300	DUCK CREEK	DCL1SPRC	SUPER	5562	2006.5	5562	2006.5
13400	DUCK CREEK	DCL1SPRC	SUPER	5562	2006.7	5562	2006.7

GENERAL				FLOODPLAIN		FLOODWAY	
HEC-2 XS	STREAM NAME	HEC-2 MODEL	FLOW REGIME	Q (CFS)	WSE (FT)	Q (CFS)	WSE (FT)
13500	DUCK CREEK	DCL1SPRC	SUPER	5562	2006.9	5562	2006.9
13600	DUCK CREEK	DCL1SPRC	SUPER	5562	2010.5	5562	2010.5
13700	DUCK CREEK	DCL1SPRC	SUPER	5562	2011.8	5562	2011.9
13800	DUCK CREEK	DCL1SPRC	SUPER	5562	2013.4	5562	2013.5
13900	DUCK CREEK	DCL1SPRC	SUPER	5562	2014.7	5562	2014.7
14000	DUCK CREEK	DCL1SPRC	SUPER	5562	2015.4	5562	2015.5
14100	DUCK CREEK	DCL1SPRC	SUPER	5562	2017.6	5562	2017.7
14200	DUCK CREEK	DCL1SPRC	SUPER	5562	2018.2	5562	2018.3
14300	DUCK CREEK	DCL1SUBC	SUB	5562	2024.8	5562	2024.8
14400	DUCK CREEK	DCL1SUBC	SUB	5562	2027.1	5562	2027.1
14500	DUCK CREEK	DCL1SUBC	SUB	5562	2026.8	5562	2026.8
14600	DUCK CREEK	DCL1SUBC	SUB	5562	2028.3	5562	2028.3
14700	DUCK CREEK	DCL1SUBC	SUB	5562	2029.1	5562	2029.1
14800	DUCK CREEK	DCL1SUBC	SUB	6394	2030.2	6394	2030.1
14900	DUCK CREEK	DCL1SUBC	SUB	7883	2031.5	7883	2031.5
15000	DUCK CREEK	DCL1SUBC	SUB	8382	2033.6	8382	2033.9
15100	DUCK CREEK	DCL1SUBC	SUB	8562	2034.0	8562	2034.3
15200	DUCK CREEK	DCL1SUBC	SUB	8562	2034.1	8562	2034.7
15300	DUCK CREEK	DCL1SUBC	SUB	8562	2035.9	8562	2036.2
15400	DUCK CREEK	DCL1SUBC	SUB	8562	2038.3	8562	2038.3
15500	DUCK CREEK	DCL1SUBC	SUB	8562	2037.8	8562	2037.8
15600	DUCK CREEK	DCL1SUBC	SUB	8562	2038.4	8562	2038.4
15700	DUCK CREEK	DCL1SUBC	SUB	8562	2040.7	8562	2040.7
15800	DUCK CREEK	DCL1SUBC	SUB	8562	2043.5	8562	2043.5
15900	DUCK CREEK	DCL1SPRC	SUPER	8562	2045.0	8562	2045.0
16000	DUCK CREEK	DCL1SPRC	SUPER	8562	2044.8	8562	2044.8
16100	DUCK CREEK	DCL1SUBC	SUB	8562	2048.0	8562	2048.0
16200	DUCK CREEK	DCL1SUBC	SUB	8562	2050.6	8562	2050.6
16300	DUCK CREEK	DCL1SUBC	SUB	8562	2052.9	8562	2052.9
16400	DUCK CREEK	DCL1SUBC	SUB	8562	2053.0	8562	2052.8
16500	DUCK CREEK	DCL1SUBC	SUB	8562	2052.7	8562	2052.6
16600	DUCK CREEK	DCL1SUBC	SUB	8562	2054.0	8562	2054.8

HEC-2 MODEL: DCL1SUBC

STREAM NAME: Duck Creek

UPSTREAM LIMIT: Lower Duck Creek Detention Basin

DOWNSTREAM LIMIT: Confluence with Pittman Wash

UPSTREAM HEC-2 SECTION: 22600

DOWNSTREAM HEC-2 SECTION: 1800

FLOW REGIME: Subcritical

STUDY METHOD: Detailed – Floodplain and Floodway model

MODELING SOFTWARE: HEC-2 Version 4.6.2 (8/91) operating inside BOSS RMS 2000

TOPOGRAPHIC MAPPING: Kenney Aerial Mapping, July 2000; NGVD 29

FIELD SURVEY: G.C. Wallace, Inc., September 2000 to November 2001; NGVD 29

ADDITIONAL DESCRIPTION/DISCUSSION:

This is a subcritical floodplain and floodway model. Note that the downstream limit of the floodway is set at Patrick Lane. The split flow option was disabled for this model. Flow rate adjustments for this model are based on flows generated by the base model DCL1SUBA.

Cross section geometry is based on a 4-foot contour interval and field survey, oriented left to right facing downstream. Bridge geometry is based on a detailed field review organized in Section 5.1. All bridges in this reach were modeled using the Special Bridge routine. Note that the cross section geometry of this model is identical to that of the base model, DCLSUBA.

Note that several bridge models were modified to compensate for an internal HEC-1 check during supercritical flow analysis. If critical depth is above the low chord, it will not pass low flow. In order to pass low flow, low chords were raised artificially using engineer judgment. The following bridge locations were modified:

- A. Windmill Lane
- B. Paradise Road/ Maryland Parkway
- C. Robindale Road
- D. Vista del Sol Avenue
- E. Pachuca Street
- F. Mira Vista Street
- G. Tomiyasu Lane
- H. Pine Street Crossings
- I. Pecos Road

The downstream limit of the HEC-2 model is located at the end of the Duck Creek Channel Phase 1 Improvements, which is an interim earth channel. Therefore, the starting water surface elevation is based on normal depth for subcritical flow. Manning's "n" roughness calculations are attached in Section 2.3.


The following projects are incorporated into the HEC-2 model:

- A. Duck Creek Channel Phase 1
- B. Duck Creek Improvements from Tomiyasu Lane to Warm Springs Road
- C. Aviara Apartments Offsite Channel Improvements
- D. Duck Creek Crossing at Robindale Road
- E. Crystal Springs Duck Creek Channel

The floodway analysis uses a combination of Encroachment Methods 1 and 4. Encroachment Method 1 was used when Encroachment Method 4 failed to produce reasonable results. An iterative process was applied with Encroachment Method 1 using


engineering judgment to determine the locations of the encroachment stations in order to approximate equal conveyance loss for both overbanks.

Due to the large volume of HEC-2 output, the input and output files are submitted electronically on CD. See the attached exhibit showing the location and limits of the HEC-2 model.



1" = 5000'

LEGEND

-  LIMITS OF HEC-2 MODEL
-  STREET CENTER LINE
-  CHANNEL CENTER LINE

DCL1SUBC

DUCK CREEK/ BLUE DIAMOND
WASHES FIS RESTUDY

EXHIBIT
HEC-2 MODEL

HEC-2 MODEL: DCL1SPRC

STREAM NAME: Duck Creek

UPSTREAM LIMIT: Lower Duck Creek Detention Basin

DOWNSTREAM LIMIT: Confluence with Pittman Wash

UPSTREAM HEC-2 SECTION: 22600

DOWNSTREAM HEC-2 SECTION: 1800

FLOW REGIME: Supercritical

STUDY METHOD: Detailed – Floodplain and Floodway model

MODELING SOFTWARE: HEC-2 Version 4.6.2 (8/91) operating inside BOSS RMS 2000

TOPOGRAPHIC MAPPING: Kenney Aerial Mapping, July 2000; NGVD 29

FIELD SURVEY: G.C. Wallace, Inc., September 2000 to November 2001; NGVD 29

ADDITIONAL DESCRIPTION/DISCUSSION:

This is a supercritical floodplain and floodway model. Note that the downstream limit of the floodway is set at Patrick Lane. The split flow option was disabled for this model. Flow rate adjustments for this model are based on flows generated by the base model, DCL1SUBA.

Cross section geometry is based on a 4-foot contour interval and field survey, oriented left to right facing downstream. Bridge geometry is based on a detailed field review organized in Section 5.1. All bridges in this reach were modeled using the Special Bridge routine. Note that the cross section geometry of this model is identical to that of the base model, DCLSUBA.

Note that several bridge models were modified to compensate for an internal HEC-1 check during supercritical flow analysis. If critical depth is above the low chord, it will not pass low flow. In order to pass low flow, low chords were raised artificially using engineer judgment. The following bridge locations were modified:

- A. Windmill Lane
- B. Paradise Road/ Maryland Parkway
- C. Robindale Road
- D. Vista del Sol Avenue
- E. Pachuca Street
- F. Mira Vista Street
- G. Tomiyasu Lane
- H. Pine Street Crossings
- I. Pecos Road

The upstream limit of the model is located just upstream of Bermuda Road at the outfall of the Lower Duck Creek Detention Basin, which is a rectangular channel. Therefore, the starting water surface elevation is based on normal depth for supercritical flow. Manning's "n" roughness calculations are attached in Section 2.3.


The following projects are incorporated into the model:

- A. Duck Creek Channel Phase 1
- B. Duck Creek Improvements from Tomiyasu Lane to Warm Springs Road
- C. Aviara Apartments Offsite Channel Improvements
- D. Duck Creek Crossing at Robindale Road
- E. Crystal Springs Duck Creek Channel



The floodway analysis uses a combination of Encroachment Methods 1 and 4. Encroachment Method 1 was used when Encroachment Method 4 failed to produce reasonable results. An iterative process was applied with Encroachment Method 1 using

engineering judgment to determine the locations of the encroachment stations in order to approximate equal conveyance loss for both overbanks.

Due to the large volume of HEC-2 output, the input and output files are submitted electronically on CD. See the attached exhibit showing the location and limits of the HEC-2 model.



LEGEND

-  LIMITS OF HEC-2 MODEL
-  STREET CENTER LINE
-  CHANNEL CENTER LINE

DCL1SPRC

DUCK CREEK/ BLUE DIAMOND
WASHES FIS RESTUDY

EXHIBIT
HEC-2 MODEL



G.C. WALLACE, INC.
Engineers/Planners/Surveyors

1555 SOUTH RAINBOW BLVD./LAS VEGAS, NEVADA 89146

SECTION 5

Electronic Files

Figure 3: Effective FIRM

Figure 4: Proposed FIRM Revisions

Figure 5: HEC-2 Cross Section Map

HEC-2 Model for Subcritical Conditions (DCL1SUBX.dat)

HEC-2 Model for Supercritical Conditions (DCL1SPRX.dat)

HEC-2 Model for Subcritical Conditions (FIS Restudy) (DCL1SUBC.out)

HEC-2 Model for Supercritical Conditions (FIS Restudy) (DCL1SPRC.out)

SECTION 6

Drawings for Proposed Facilities


Duck Creek Channel Improvements

Pictures showing completed facilities

CONSTRUCTION NOTES


CONSTRUCTION ITEMS

- | | |
|---|--------------------------------|
| 8 | CONSTRUCT CHAIN LINK FENCE |
| 9 | CONSTRUCT 10' WIDE ACCESS ROAD |



DUCK CREEK CHANNEL

70%
PRELIMINARY
NOT FOR CONSTRUCTION

[illegible]

DUCK CREEK CHANNEL IMPROVEMENTS

PLAN & PROFILE

STA -2+00 - STA 5+50

CLARK COUNTY, NEVADA, DEPARTMENT OF PUBLIC WORKS

PRELIMINARY
NOT FOR CONSTRUCTION

DESIGNED BY: KJY
DRAWN BY: KJY
CHECKED BY: MS
DATE: Jun 22, 2004 - 2:51pm

SCALE	
HORIZ:	1" = 40'
VERT:	1" = 4'
FIELD BOOK	NONE


SHEET No

C-01




F 990812

L-1743

QUICK CREEK CHANNEL IMPROVEMENTS - FROM 700' WEST OF TOPAZ STREET TO WARM SPRINGS ROADS



- ## REMOVAL ITEMS



PLAN & PROFILE

STA 5+50 - STA 10+00

CLARK COUNTY, NEVADA, DEPARTMENT OF PUBLIC WORKS

PRELIMINARY
NOT FOR CONSTRUCTION

DESIGNED BY: KJY
DRAWN BY: KJY
CHECKED BY: MS
DATE: Jun 22, 2004 - 2:54pm

SCALE	
HORIZ:	1" = 40'
VERT:	1" = 4'
FIELD BOOK	NONE

SHEET No.

C-02

F 990812


L-1743

DUCK CREEK CHANNEL IMPROVEMENTS - FROM 700' WEST OF TOPAZ STREET TO WARM SPRINGS ROADS

The diagram illustrates a sheet index layout. It features a grid of sheets arranged in a staggered pattern. The sheets are labeled as follows:

- BD-1**: Located in the center of the grid.
- BD-2**: Located to the left of BD-1.
- DC-1**: Located to the right of BD-1.
- DC-2**: Located above BD-1.
- DC-3**: Located above BD-2.
- DC-4**: Located below BD-1.
- DC-5**: Located below BD-2.
- DC-6**: Located below DC-5.

The sheets are arranged in a grid where the horizontal and vertical spacing between sheets is consistent, suggesting a standard sheet size and layout.





Bridge at U.P.R.R.
Cross-Section 14240



Downstream face bridge
at Warm Springs Road
Cross-Section 14600